


2025

SURFACE SOLUTIONS AUTOMOTIVE AFTERMARKET



INTRODUCTION



17-40

| Process Solutions | 05 |
|------------------------------------------------|----|
| Cyclonic Multi-Air | 06 |
| MeshPower | 08 |
| Latest products & our full abrasives offering | 10 |
| MyAbrasives online ordering system | 12 |
| Excellence training centres & Norton Advantage | 15 |

METAL WORKING

| CUTTING & GRINDING | 18-19 |
|-------------------------------------------------|--------------|
| Blue Fire cutting & grinding discs | 18 |
| Starline cutting & grinding discs | 19 |
| PANEL PREPARATION & WELD GRINDING | 21-22 |
| Fibre discs, cloth discs & back-up pads | 21 |
| DEBURRING & RUST/PAINT REMOVAL | 23-24 |
| Flap discs | 23 |
| Rapid Blend discs | 24 |
| CLEANING | 25-27 |
| Rapid Strip discs | 25 |
| High strength discs | 26 |
| QUICK CHANGE DISCS FOR SMALL AREAS | 28-35 |
| Plain discs | 28 |
| Mini flap discs | 30 |
| Flexi-flap discs | 31 |
| Rapid discs range | 31 |
| Mini Grinder & Kit | 33 |
| SANDING HARD TO REACH AREAS | 36-38 |
| File belts | 36 |
| Handy rolls | 38 |
| STEP DRILLS, CARBIDE BURRS, WIRE BRUSHES | 39-40 |
| Step drills | 39 |
| Carbide burr kit | 40 |
| Hand brushes | 40 |

MANUAL SANDING 41-50

| PRE-CUT ROLLS | 42 |
|-----------------------------------------|--------------|
| Cyclonic Multi-Air pre-cut rolls | 42 |
| CUT SHEETS & SHEETS | 43-46 |
| Cut sheets | 43 |
| Sheets | 46 |
| ROLLS | 47-48 |
| Self-Grip rolls | 47 |
| Paper rolls | 48 |
| SANDING BLOCKS, KITS & HOSES | 49-50 |
| Sanding Blocks & hoses | 49 |
| Sanding Block kits | 50 |



MACHINE SANDING 51-72

| SANDING DISCS | 52-67 |
|------------------------------------------|-------|
| Cyclonic Multi-Air discs & starter kit | 52 |
| Multi-Air discs | 54 |
| Mesh power discs | 58 |
| Multi-Air back-up pads & interfaces | 59 |
| Blue Fire discs | 60 |
| Norton Pro & Pro Plus discs | 61 |
| Norton Pro & Pro Plus smart repair discs | 62 |
| Norton Pro film discs | 65 |
| Gold Reserve discs | 65 |
| Self-grip back-up pads & interfaces | 66 |
| Dual Action Sander Pneumatic DASP | 67 |
| Vacuums & accessories | 68 |

FINISHING 73-82

| ROTOLO FOAM | 74-76 |
|------------------------------------|-------|
| Norton Pro Plus | 74 |
| Norton MAX | 75 |
| Norton Pro | 76 |
| Gold Reserve | 76 |
| BEARTEX NON-WOVEN | 77-79 |
| Rotolo rolls | 77 |
| BearTex hand pads & discs | 78 |
| Scuff Gel | 79 |
| Back-up pads | 79 |
| WATERPROOF SHEETS | 80-81 |
| Waterproof sheets | 80 |
| Sanding block for waterproof paper | 80 |
| SANDING SPONGES | 82 |

CONTENTS

MASKING SOLUTIONS

| TAPES | 84-88 |
|-----------------------------------|-------|
| Orange & Gold tape | 84 |
| Challenger tape | 85 |
| Masking tape | 86 |
| Standard Foam Tape | 86 |
| Premium perforated trim tape | 86 |
| Polyethylene tape | 87 |
| Fine line tape | 87 |
| Double-sided attachment foam tape | 87 |
| MASKING FILM | 89-90 |
| Plastifilm | 89 |
| Dispenser & cutter for Plastifilm | 90 |
| PREMIUM KRAFT PAPER | 91 |

NORTON

PAINT SYSTEM

| Disposable kits | 94 |
|-------------------|----|
| Refill kits | 95 |
| Reusable hard cup | 95 |
| Starter kit | 95 |
| Mixing cups | 95 |
| Accessories | 96 |




83-92 MICROFINISHING 99-110

| NORTON ICE RANGE | 100-104 |
|------------------------|---------|
| Discs | 100 |
| Foam interfaces | 102 |
| Rosette discs & blocks | 103 |
| Norton Ice starter kit | 104 |
| LIQUID ICE COMPOUNDS | 105-106 |
| ACCESSORIES | 107-109 |
| Polishing heads | 107 |
| Clothes & Tack rags | 108 |
| Clay range | 109 |
| HEADLIGHT REPAIR KIT | 110 |

ONEBOND SOLUTIONS

93-98



| Adhesives for windscreen replacement | 114 |
|--------------------------------------------------|-----|
| Adhesives & sealants for body repair | 118 |
| Applicator guns | 125 |
| Onebond chemicals, wipes, tapes, safety and care | 129 |
| Mixers & Nozzles | 137 |
| Accessories | 139 |

PERSONAL PROTECTION EQUIPMENT

141-147

| Masks & filter pad replacements | 142 |
|---------------------------------|-----|
| Safety Glasses | 144 |
| Gloves | 146 |
| Overalls | 147 |
| | |



From the initial metal working in repair processes to the final detailing and polishing, Norton provides the most powerful, precise, and user-friendly solutions to transform surfaces of car body repair. And when choice and value are required, we provide the widest portfolio of abrasives and system components along with expert knowledge drawn from more than 135 years of experience. Norton are a true full-service, value partner. No matter the application, our passion is in delighting our customers, making them more productive and profitable, every day. Transforming surfaces, reshaping the Automotive Aftermarket, together.





Norton offers products for cutting, grinding, surface preparation, reshaping, sanding, cleaning and rust and excess material removal from high-strength steel and automotive materials in the collision repair sector.

PRODUCT HIGHLIGHT: BLAZE RAPID STRIP Removes rust, scale, old paint and composites quickly and efficiently leaving the surface prepared for the next step.

See page 25.

MANUAL SANDING

From aggressive removal of paint layers to fine sanding, and finishing. In panel repair and preparation, look no further than Multi-Air cut sheets with the original hole configuration from Norton, designed for maximum dust extraction.

PRODUCT HIGHLIGHT: MULTI-AIR PLUS (A975) The best product for final sanding when used in conjunction with the Multi-Air sanding block.

See page 41.

MACHINE SANDING

Whether sanding bare metal, filler, primer, base coat, clear coat, plastics or composites, Norton makes life quicker and easier in the bodyshop. Film discs, foam backed discs, mesh abrasives and Cyclonic Multi-Air which offers innovation as the 'all-in-one' sanding system with the ultimate dust extraction on all surfaces.

PRODUCT HIGHLIGHT: MULTI-AIR CYCLONIC

Colour-coded discs and rolls made using premium abrasive grain, laser cut technology, an anti-clog layer, and foam backing make Cylonic the new go-to system See page 51.



FINISHING

Scratch and scuff removal during the final repair stages need quality products that can be relied upon to achieve a high-quality finish first time. Norton non-woven products, Rotolo Foam and waterproof sheets do just that.

PRODUCT HIGHLIGHT: NORTON PRO PLUS ROTOLO FOAM

Pre-cut sheets with premium abrasive and foam backing gives a superior finish on flat and uneven surfaces thanks to the foam that absorbs the contours.

See page 73.

MASKING SOLUTIONS

Several tapes are available for masking applications which require high heat resistance, to more specialist jobs on edges and in apertures.

PRODUCT HIGHLIGHT: NORTON PREMIUM TAPE

Resists high temperatures, conforms to contours, and leaves no residue when removed.

See page 83.



NORTON PAINT SYSTEM

A practical solution for preparing, mixing, and spraying paint. A faster, cleaner solution, the NPS saves on cleaning time and solvent usage and can be used without the hard cup, improving spraying visibility and providing a more comfortable experience.

See page 93.

MICROFINISHING

For a high gloss finish and mirror shine, Norton has many abrasives, compounds and accessories to choose from to make the polishing process fast and simple.

PRODUCT HIGHLIGHT: LIQUID ICE XTRA CUT

Achieve a polished finish on most common clear coats using only Liquid Ice Xtra Cut, single step process for great results.

See page 99.

ONEBOND SOLUTIONS

The world of OneBond is an emporium of adhesive knowledge, expertise, and contemporary solutions, powered by our understanding of your requirements whatever your sector.

PRODUCT HIGHLIGHT:

OneBond EP Power Metal 60 is a two-part toughened structural epoxy adhesive for use on metal. It offers high rigidity, strength, environmental and temperature resistance. For bonding and weld-bonding fenders, rear body panels, roofs, door reinforcements, door skins, bonnet skins and floor pans. It is also suitable to bond the bed panels and metal and composite side panels of vans, trucks and buses. It is non-conductive and provides corrosion protection.



Norton offers a range of respiratory masks, gloves, glasses and overalls for protection in the bodyshop.

See page 141.

...FOR MORE INFORMATION VISIT www.nortonabrasives.com






THE ULTIMATE SANDING SOLUTION

A truly unique 'all-in-one' sanding solution combining cleaner working conditions with ultimate performance for a unique sanding solution for all applications.



CYCLONIC MULTI-AIR

Thanks to the unique hole pattern based on cyclone formation, Norton Cyclonic improves productivity by up to 32% compared to conventional multi-hole sanding discs, with a 25% increase in dust extraction. Contributing to this increase is new laser-cutting technology meaning holes are cut into the disc, not punched, so discs are flatter, dust extraction is improved, and the abrasive surface areas is increased for a more consistent scratch pattern and improved surface finish throughout the life of the disc.



PRODUCT SPOTLIGHT



A SIMPLE APPLICATION PROCESS

| | STEP | APPLICATION | SHAPE / BACKING | BACK-UP PAD | MACHINE / MANUAL | FINISHING GUIDE |
|----|-----------|------------------------------------------|------------------|---------------|------------------|-----------------|
| | BLUE | stripping & LEVELLING (heavy-duty) | Self-Grip | Hard | 5mm Orbit | 80 / 100 |
| | GREEN | STRIPPING 1 & FILLER LEVELLING | Self-Grip | Hard / Medium | 5mm Orbit | 120 / 150 |
| | RED | 2 FILLER FINISHING | Self-Grip | Medium | 5mm Orbit | 220 / 240 |
| | SALMON | 3 PRIMER SANDING | Micro Soft-Touch | Medium | O 2.5mm Orbit | 320 / 400 |
| 1. | FUCHSIA | 4 PRIMER FINISHING | Micro Soft-Touch | Medium / Soft | O 2.5mm Orbit | 500 / 600 |
| RI | TURQUOISE | FADEOUT & | Micro Soft-Touch | Soft | O 2.5mm Orbit | 800 / 1000 |

SEE PAGE 52 FOR THE FULL NORTON CYCLONIC RANGE

PRODUCT SPOTLIGHT





POWERFUL DUST EXTRACTION

Sanding is traditionally dusty and messy. But, with Norton MeshPower[™], you get powerful dust extraction for virtually dust-free sanding. This means a cleaner, healthier working environment, a better finish and a much more pleasant sanding experience.

An alternative to traditional perforated paper discs, Norton MeshPower is a multi-functional abrasive, designed with thousands of holes created by the unique mesh matrix structure. This hole structure allows dust extraction in any application.






CERAMIC ADVANTAGE

WHY CHOOSE A CERAMIC ABRASIVE?

Ceramic grain provides the ultimate material removal, best productivity, longest life and finest finish.

POWERFUL DUST EXTRACTION MEANS A CLEANER ENVIRONMENT

The open mesh construction of the backing allows dust particles to flow freely through thousands of tiny holes, creating a virtually dust-free sanding environment. Better for your health, better for your application and better for your business!









SEE PAGE 58 FOR THE FULL NORTON MESHPOWER RANGE

LATEST PRODUCTS



ADHESIVES AND SEALANTS FOR AUTOMOTIVE AFTERMARKET

ADHESIVES & SEALANTS FOR WINDSCREEN REPLACEMENT

Glass-bonding adhesives are widely used in the installation and replacement of automotive windscreens, back-lights, quarter glass and other automotive glass, including sun and panoramic roofs.

ADHESIVES FOR PLASTICS REPAIR

Adhesives are needed in order to repair cracks, scratches and holes in automotive exterior plastic parts, including bumpers, spoilers, tailgates and side mirrors.



ADHESIVES & SEALANTS FOR BODY REPAIR

Adhesives & sealants are required for sealing applications in cars and commercial vehicles, mainly for metal repair.

DISCOVERUQUR NEWRRANGE!

You Tube



See page 111



SAINT-GOBAIN

BODYSHOP STORAGE AND ORGANISATION

Introducing two new customisable workstations to increase bodyshop efficiency by keeping all the necessary tools and materials **organised** and **easily accessible**.

The new Smart Station is a compact sanding system featuring an exclusive dispenser for Norton abrasives and holders for sanding machines, pads and mobile phone. Fasten it to the Norton Vacuum System and create a complete mobile sanding solution for a cleaner, safer and more efficient workspace.

The Working Station is a perfect companion for all your body shop jobs. Its durable construction and ergonomic handle allow you to move it everywhere you need. Compatible with all Norton solutions for efficient collision repair, finishing, and polishing, the **two-sided** station can be used by two operators simultaneously, so no time is wasted retrieving items from a cabinet.

See page 70

See page 54



BLAZE YOUR WAY TO GREATER PRODUCTIVITY

NORTON MULTI-AIR BLAZE A995

Sharp design, smooth cut, fast finish, and ultimate strength are key characteristics of the new Multi-Air Blaze A995. Featuring the finest design essentials to help you achieve the best results, the A995 sanding discs deliver superior productivity and optimal dust extraction in car body repair.

10 / INTRODUCTION



A FULL ABRASIVE OFFER

| MANUAL OPERATIONS APPLICATION | | | | | | |
|-------------------------------|--------------------------|-------------------------------------|--------------------------|------------------------------|-------------------|------------|
| PRODUCT | TOOL | METAL | FILLER | PRIMER | PAINT | CLEAR COAT |
| | | BLU | E FIRE | | | |
| CUT SHEETS | SANDING BLOCK | | NORTON PRO | , MULTI-AIR & MULTI-AIR PLUS | | |
| CUISHEEIS | SANDING BLUCK | | | BEARTE | EX HAND PADS & TI | HINFLEX |
| | | | MESHPOWER | | | |
| ROTOLO FOAM | HAND OR SANDING BLOCK | | | NORTON PRO, GOLD RESERVE | | |
| | | BEA | RTEX | | | |
| SHEETS | HAND OR SANDING BLOCK | Q775 FILM, NORTON PRO, GOLD RESERVE | | | | |
| | | | BLACK ICE WATERF | | ICE WATERPROOF | PAPER |
| | | R222 | | | | |
| ROLLS HAND OR SANDING E | | | I/G131 | | | |
| | HAND OR SANDING BLOCK | | CYCLONIC MULTI-AIR | | | |
| | | | NORTON PRO, GOLD RESERVE | | | |
| | | | MESHPOWER | | | |
| SPONGES | HAND | SOFT-TOUCH SPONGES | | | | |

MACHINE OPERATIONS

| MACHINE OP | ERAIIONS | | | APPLICATION | | |
|------------------------------|-----------------------------------|-------------------------------------------------------------------|-----------------|------------------|-------------|---------------|
| PRODUCT | TOOL | METAL | FILLER | PRIMER | PAINT | CLEAR COAT |
| THIN WHEELS | | BLUE FIRE | | | | |
| FIBRE DISCS | | NORZON, METAL | | | | |
| FLAP DISCS | AP DISCS | | | | | |
| RAPID STRIP | RIGHT ANGLE OR DIE GRINDER | RS, RSF, RST, TR Plus | | | | |
| SPEEDLOK | DIE GRINDER | BLAZE & XTREME MINI-FLAP DISCS & SPEEDLOK DISCS, BEARTEX | | | | |
| CLOTH DISCS | ROTARY SANDER | NOR | ZON | | | |
| CYCLONIC MULTI-AIR DISCS | ORBITAL SANDER | | C | YCLONIC MULTI-A | IR | - |
| | | | MULTI-AIR BLAZE | | | |
| MULTI-AIR | ORBITAL SANDER | MULTI-AIF | R NORZON | | | |
| DISCS | STEPHILE STATEEN | MULTI-AIR | | | | |
| | | | | MULTI-AIR | | |
| MULTI-AIR | ORBITAL SANDER | | | MULT | ΓΙ-AIR | |
| SOFT-TOUCH DISCS | | | | | MULTI-AIR | 1 |
| MESHPOWER DISCS | ORBITAL SANDER | | MESHPOWER | 1 | | |
| | | BLUE | | | | |
| SELF-GRIP ⁺ DISCS | ORBITAL SANDER | | NORTON PRO | | | NORTON ICE |
| | | | NORTON PRO, N | IORTON PRO FILM, | T | |
| | | | | | PURE ICE Q1 | 75, Q775 FILM |
| MULTI AIR CUT SHEETS | ORBITAL SANDER | MULTI-AIF | R NORZON | | | |
| | | | | MULTI-AIR | | |
| MESHPOWER CUT SHEETS | ORBITAL SANDER | | MESHPOWER | | | |
| POLISHING COMPOUNDS | RIGHT ANGLE GRINDER / POLISHER | | | | | LIQUID ICE |
| SELF-GRIP DISCS | ORBITAL SANDER | | | | NORTON ICE | |
| JELI UNIF DIJUJ | URBITAL SANDER | | | | SUPERFLE | XIBLE Q775 |

WE'RE MAKING IT EVEN EASIER **TO ORDER OUR GREAT PRODUCTS**



MyAbrasives The online ordering system from Saint-Gobain Abrasives

Our user-friendly ordering system works very much like online retailers you use every day, easy to navigate and get what you need, whether ordering, tracking or research.

With MyAbrasives, the ordering process is so simple:



Search for your product






Go to checkout



ORDERING MADE EASY:

- **1.** Detailed product information and specifications, including images and videos
- **2.** Access to order confirmations, product availability and delivery lead times
- 3. Available from smartphones, tablets and PCs 24/7
- **4.** Automatically creates a list of most frequently ordered products for ease of future ordering
- **5.** Save favourite lists to make ordering quicker and easier



MYABRASIVES OFFERS GREATER FLEXIBILITY:


- **Product search:** you can search by UPC, name, category, EAN number and filter and sort search results, making it much easier for you to find what you need
- Order history and re-ordering: you'll be able to see your past orders across all platforms (EDI, ABx, phone and fax) and these can also be easily re-ordered. Invoices, debit/credit notes and shipping status will also be visible in the 'Order History' section so you can be sure all of your paperwork is safe in one place
- **Quotes:** you can request and track quotes in MyAbrasives rather than having to contact the customer services team separately
- Saved orders: you can save orders for future reference by putting multiple items in your cart and saving it, e.g. as 'Monthly Order'. You can also add a note to indicate the order frequency, e.g. 'order every month except December' and save it so you can re-order quickly and easily
- Bulk orders: if you need to make a bulk order, you can upload a CSV file directly into the system rather than having to search for each product individually
- **Recommended for you:** related products you may need to order
- Extra support: FAQs and how-to videos, or contact our dedicated helpline

Register today

To register call your local customer service team and start using MyAbrasives today.








Automotive Aftermarket

entering part of a select group of industry leaders providing complete automotive reforming adjustmes. Bringing together at reflecced surger of advecters and non-atomice consumation, including a anywaitig with other key Saleh Oxford Summann, hardyn helys blog stops to codmuse all expects of the automotive repair and reflected process.

As a work leader in advances automate for applications in metal exoting, body panel repair, surface preparation, finding and polision, finances exotines you to work with 100% confidences in activities possible exoting by your business. The priority is to priority the sources and advances of the source preparation of the sources and advances of the sources of





DISCOVER MORE ABOUT OUR PRODUCTS AT:

www.nortonabrasives.com





EXCELLENCE TRAINING CENTRES

It is our goal to establish a long-term relationship with our customers, with a strong emphasis on sharing our professional skills, process knowledge and providing up-to-date information regarding industry developments. Our Excellence Training Centres in France, Italy, Germany and Poland, are fully equipped facilities offering professional technical locations for handson training based on best practices in repair shops.

Our training sessions are held on a regular basis and are open to everyone! If you are interested in participating, please contact your local Norton representative to arrange a suitable date.





SUPPORTING SUSTAINABILITY IN THE ABRASIVES INDUSTRY

Mitigating climate change means decarbonising our economies, and here at Saint-Gobain, the goal is simple: by 2050, we must not emit any more carbon than we absorb. We must be carbon-neutral, we must preserve our planet's assets, such as water and rare earth, and we must limit the waste that we generate.

This commitment is rooted in a history of reducing our environmental impact, and it is inseparable from our ambition to provide our customers with solutions to decarbonise and reduce their environmental footprint. Our net-zero ambition is also a concrete expression of our purpose: making the world a better home!

SUSTAINABILITY IS AT THE CORE OF WHAT WE DO, WE HAVE CLEAR COMMITMENTS **BUILT AROUND FIVE PILLARS**:

SUSTAINABILITY AS A DRIVER FOR GROWTH

- Decarbonisation of our customers' applications
- By 2030, 100% of products covered by Environmental Product Declaration / Life Cycle Assessment (ISO 14040)
- Circular economy, recycling services and eco-innovation

LIMIT OUR ENVIRONMENTAL IMPACT

- By 2030, reduce energy consumption and CO₂ emissions by -33% (Scope 1 and 2)²
- -50% water withdrawal and reuse by 2030
- Reduction of waste to landfill, and reuse and recycle
- Increased biodiversity and reduced pollution
- -80% of non-valorised residues by 2030

TAKE ACTIONS ACROSS THE SUPPLY CHAIN



- Reduction of -16% CO₂ value chain emissions by 2030 (Scope 3)
- Decarbonising our transportation
- 100% of packaging recyclable, >30% of recycled or bio-sourced packaging content by 2030

SOLUTIONS WITH END-USERS' SAFETY, HEALTH, COMFORT AND WELLBEING AT HEART

- Customer centricity on safety, health, comfort and wellbeing
- Surface solutions to reduce vibration, noise, dust and VOC
- Greener solutions that respect the planet and the people
- 100% REACH compliant

ENCOURAGE EMPLOYEE ENGAGEMENT

- Awareness and education programs
- Ambassador networks and employee ideation

To understand more and to see practical examples of the steps that we've taken and targets that we work to, for each of these five pillars, please ask your sales representative or visit: www.nortonabrasives.com

| CUTTING & GRINDING | 10 |
|------------------------------------------|----|
| Cutting discs | 18 |
| Grinding discs | |
| PANEL PREPARATION & WELD GRINDING | 21 |
| Fibre discs | |
| DEBURRING & RUST/PAINT REMOVAL | 23 |
| Flap discs | ZJ |
| Rapid Blend discs | |
| CLEANING | 25 |
| Rapid Strip discs | ZJ |
| High strength discs | |
| QUICK CHANGE DISCS FOR SMALL AREAS | 28 |
| Plain discs | 20 |
| Mini flap discs + Flexi flap discs | |
| Rapid Strip discs | |
| Rapid Blend discs | |
| Rapid Prep discs | |
| Mini Grinder & Kit | |
| SANDING HARD TO REACH AREAS | 36 |
| File belts | 30 |
| Handy rolls | |
| STEP DRILLS, CARBIDE BURRS, WIRE BRUSHES | 39 |
| Step drills | 37 |
| Carbide burr kit | |
| Hand brushes | |

NORTO

CUTTING & GRINDING


Designed for all rough applications including: weld removal, surface preparation, metal removal, reshaping and cutting rusted and corroded materials. Norton cutting and grinding discs are the choice of the professional, cutting quickly and comfortably.





* Made-to-order

BLUE FIRE CUTTING DISCS



- Regarding 1.0 and 1.6mm thick discs, high-performance abrasive grain yields up to 50% more cuts than standard aluminium oxide products
- Strong bond system in disc formula provides longer life, reduces workpiece burn and lowers the need for deburring
- Wide range of disc sizes available for cutting and grinding using a straight grinder or angle grinder in small or hard-to-reach areas

| | DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
|---|------------------------------|----------------------|---------------|--------------|-----------|
| | 50 x 1 x 6.35 | 80 | A 60 T-BF41 | 66252842745 | 50 |
| | 50 x 2 x 6.35 | 80 | A 60 T-BF41 | 66252842746 | 50 |
| | 63 x 1 x 6.35 | 80 | A 60 T-BF41 | 66252828238 | 50 |
| | 63 x 1 x 10 | 80 | A 60 T-BF41 | 66252828195 | 50 |
| | 63 x 2 x 6.35 | 80 | A 60 T-BF41 | 66252828239 | 25 |
| | 76 x 1 x 6.35 | 80 | A 60 T-BF41 | 66252828240 | 50 |
| | 76 x 1 x 10 | 80 | A 60 T-BF41 | 66252828241 | 50 |
| _ | 76 x 1.6 x 10 | 80 | A 46 T-BF41 | 66252828242 | 50 |
| | 76 x 2 x 6.35 | 80 | A 60 T-BF41 | 66252828243 | 25 |
| | 76 x 2 x 8 | 80 | A 60 T-BF41 | 66252828244* | 25 |
| | 76 x 2 x 10 | 80 | A 60 T-BF41 | 66252828245 | 25 |
| | 100 x 1 x 10 | 80 | A 60 T-BF41 | 66252828246 | 50 |
| | 100 x 1 x 16 | 80 | A 60 T-BF41 | 66252828247 | 50 |



BLUE FIRE CUTTING DISCS 1111

| | 1 ₁₀₀ | 2 | | |
|------------------------------|----------------------|---------------|-------------|-----------|
| DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
| 115 x 1 x 22.23 | 80 | A 60 T-BF41 | 66252828255 | 25 |
| 125 x 1 x 22.23 | 80 | A 60 T-BF41 | 66252828256 | 25 |
| 125 x 1.6 x 22.23 | 80 | A 60 T-BF41 | 66252828257 | 25 |





.....

| DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
|------------------------------|----------------------|---------------|-------------|-----------|
| 115 x 1 x 22.23 | 80 | C 60 T-BF41 | 66252828253 | 25 |
| 125 x 1 x 22.23 | 80 | C 60 T-BF41 | 66252828254 | 25 |

BLUE FIRE GRINDING DISCS #++++ ML ID

| TYPE 41 | | | | |
|------------------------------------|----------------------|---------------|-------------|-----------|
| DIMENSIONTYPE 01 D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
| 50 x 6 x 6.35 | 80 | A 24 R-BF01 | 66252828248 | 10 |
| 63 x 6 x 10 | 80 | A 24 R-BF01 | 66252828249 | 10 |
| 76 x 7 x 10 | 80 | A 24 R-BF01 | 66252828250 | 10 |






| DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
|------------------------------|----------------------|---------------|-------------|-----------|
| 115 x 6 x 22.23 | 80 | A 24 R-BF27 | 66252828251 | 10 |
| 125 x 6 x 22.23 | 80 | A 24 R-BF27 | 66252828252 | 10 |
| | | | | |

SPINDLES

- Spindles for use on straight grinders
- These products guarantee correct mounting of cutting discs and grinding wheels, even when the wheel arbour does not match the original machine

| SIZE | ART. NO. | PK QTY |
|------|-------------|--------|
| 6mm | 07660739614 | 1 |
| 8mm | 07660739616 | 1 |
| 10mm | 07660739615 | 1 |





STARLINE CUTTING AND GRINDING DISCS

- Good material removal and cut rate
- For general trade and general usage

| DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
|------------------------------|----------------------|---------------|-------------|-----------|
| 115 x 1 x 22.23 | 80 | A 60 R-BF41 | 66252837243 | 25 |
| 115 x 1.6 x 22.23 | 80 | A 46 R-BF41 | 66252837244 | 25 |
| 115 x 2.5 x 22.23 | 80 | A 30 P-BF41 | 66252837249 | 25 |
| 125 x 1.0 x 22.23 | 80 | A 60 R-BF41 | 66252837245 | 25 |
| 125 x 1.6 x 22.23 | 80 | A 46 R-BF41 | 66252837246 | 25 |
| 125 x 2.5 x 22.23 | 80 | A 30 P-BF41 | 66252837250 | 25 |
| 180 x 1.6 x 22.23 | 80 | A 46 R-BF41 | 66252837247 | 25 |
| 180 x 2.5 x 22.23 | 80 | A 30 P-BF41 | 66252837251 | 25 |
| 230 x 1.9 x 22.23 | 80 | A 46 S-BF41 | 66252843278 | 25 |
| 230 x 2.0 x 22.23 | 80 | A 36 R-BF41 | 66252837248 | 25 |
| 230 x 2.5 x 22.23 | 80 | A 30 P-BF41 | 66252837253 | 25 |
| 115 x 3.2 x 22.23 | 80 | A 30 P-BF42 | 66252837275 | 25 |
| 125 x 3.2 x 22.23 | 80 | A 30 P-BF42 | 66252837276 | 25 |
| 230 x 3.2 x 22.23 | 80 | A 30 P-BF42 | 66252837278 | 25 |



| DIMENSIONS D x T x B (mm) | MAX SPEED (m/sec) | SPECIFICATION | ART. NO. | PK QTY |
|------------------------------|----------------------|---------------|-------------|-----------|
| 115 x 6.4 x 22.23 | 80 | A 24 Q-BF27 | 66252837263 | 10 |
| 125 x 6.4 x 22.23 | 80 | A 24 Q-BF27 | 66252837264 | 10 |
| 180 x 6.4 x 22.23 | 80 | A 24 Q-BF27 | 66252837268 | 10 |
| 230 x 6.4 x 22.23 | 80 | A 24 Q-BF27 | 66252837269 | 10 |



PNEUMATIC STRAIGHT CUT-OFF KIT

- Kit designed for quick cutting in collision repair applications
- The machine is delivered with a fixed safety guard and a soft grip to prevent discomfort. It is lightweight, only 0.8kg, and with low noise and low air consumption
- All included Norton Blue Fire wheels are 76mm to fit the 3" machine
- High-performance cutting disc 1.0mm, for more cuts and longer disc life
- Metal/inox 7.0mm grinding disc designed for rough applications

| DESCRIPTION | QTY IN KIT | ART. NO. |
|--------------------------------------------------------------|------------|-------------|
| Norton straight cut-off tool | 1 | |
| Norton Blue Fire inox cutting-off wheel for straight grinder | 50 | |
| Norton Blue Fire inox grinding wheel for straight grinder | 10 | 78072756398 |
| Norton standard glasses | 1 | |
| Norton tool bag | 1 | |

PANEL PREPARATION & WELD GRINDING

Weld grinding and stock removal is often required during major collision repair jobs. Norton offers a range of fibre discs and selfgrip discs for medium and heavy material removal from metal.

NORZON FIBRE DISCS F827



- Sharp NorZon grain provides fast cutting action and high-stock removal of old paint and rust, smoothing down welding beads, light deburring and blending
- The 0.8mm fibre backing and full resin bond system make the disc strong, flexible and long-lasting
- The fibre discs are impregnated with active cooling agents, which prevent the workpiece from burning

| GRIT | 115 x 22mm | 125 x 22mm | 180 x 22mm | QTY |
|------|-------------|-------------|-------------|-----|
| 36 | 63642539615 | 63642536483 | 63642533063 | 25 |
| 50 | 69957360053 | 63642539620 | 63642533064 | 25 |
| 60 | 63642539616 | 69957360057 | 63642533065 | 25 |
| 80 | 63642539617 | 63642539622 | 63642533066 | 25 |
| 120 | 63642533055 | 63642533056 | 63642533068 | 25 |
| | | | | |





DK

MOUNTING Use with a backing pad on an angle grinder and use a tightening nut to ensure correct fixing to the machine.



NORTON METAL F100

- Tough, aluminium oxide grain and additional grinding additives make F100 ideal for steel and metal alloys
- The 0.8mm/0.6mm thick fibre backing provides good product life in metal removal applications

| GRIT | 115 x 22mm | 125 x 22mm | 180 x 22mm | PK QTY |
|------|-------------|-------------|-------------|-----------|
| 36 | 66623385741 | 66623385768 | 66623385760 | 25 |
| 40 | 66623385745 | 66623385770 | 66623385752 | 25 |
| 50 | 66623385747 | 66623385773 | 66623385793 | 25 |
| 60 | 66623385748 | 66623385775 | 66623385749 | 25 |
| 80 | 66623385750 | 66623385776 | 66623385746 | 25 |
| 120 | 66623385757 | 66623385779 | 66623385739 | 25 |

MOUNTING

Use with a backing pad on an angle grinder and use a tightening nut to ensure correct fixing to the machine.

BACKING PADS

- Suitable for F827 & F100
- M14 nut medium hardness

| DIMENSIONS | DENSITY | ART NO. | PK QTY |
|------------|---------|-------------|-----------|
| 115 x 22mm | Medium | 69957382825 | 5 |
| 125 x 22mm | Medium | 69957382826 | 5 |
| 180 x 22mm | Medium | 69957382827 | 5 |
| | | | |

DEBURRING & RUST/PAINT REMOVAL

To help reduce processing time and lower costs, Norton flap discs are engineered for applications from light stock removal to blending, providing a high-quality finish every time.

SUPER BLEUE 4 FLAP DISCS



- Blended SG ceramic and NorZon abrasive grain provides the ultimate sharp cutting performance, even with less pressure applied to the machine
- Cloth backing provides strength and durability for aggressive applications
- Fibreglass back pad supports longer product life and a consistent finish

| GRIT | 115 x 22mm | 125 x 22mm | PK QTY |
|------|-------------|-------------|--------|
| 40 | 63642519005 | 63642519040 | 10 |
| 60 | 63642519006 | 63642519050 | 10 |
| 80 | 63642519025 | 63642519054 | 10 |





MOUNTING Fits directly on angle grinders which have a tightening nut.





MOUNTING Fits directly on angle grinders which have a tightening nut.

VULCAN FLAP DISCS /++++/



- Self-sharpening zirconia grain provides aggressive stock removal when needed and with lighter pressure, deburrs, blends and removes old paint layers and corrosion on the periphery or interior of doors and wheel arches
- Strong cotton cloth backing provides strength, flexibility and wear resistance
- Optimised flap configuration and increased abrasive density make this range ideal for all low and medium-pressure applications on all metal types

| GRIT | 115 x 22mm | 125 x 22mm | PK QTY |
|------|-------------|-------------|--------|
| 40 | 63642502311 | 63642502315 | 10 |
| 60 | 63642502312 | 63642502317 | 10 |
| 80 | 63642502313 | 63642502318 | 10 |
| 120 | 63642502314 | 63642502326 | 10 |





MOUNTING Fits directly on angle grinders which have a tightening nut.

VORTEX RAPID BLEND DISCS

- Combination of high-performance grain and unitised construction means finishing time is reduced and part quality is increased
- Thick nylon web resists loading, shedding and provides long product life
- 2-in-1 action; can cut like an 80 grit flap disc and finish like a finishing disc
- The undersized backing plate means the disc can be used for longer before being replaced, reducing the total abrasive cost

| DIMS | CAP CODE | MAX RPM | GRADE | ART. NO. | PK QTY |
|--------|----------|------------|------------|-------------|-----------|
| 115 mm | U2305 | 12000 | VORTEX 5AM | 66254429268 | 10 |
| 125 mm | U2305 | 12000 | VORTEX 5AM | 66254496323 | 10 |

CLEANING

Make light work of removing unwanted coatings and rust from metallic components with this range of products for stripping and cleaning.

This range of Rapid Strip discs have a strong open web structure that combines aggressive stock removal with a cool, conformable action that will not damage the workpiece.



- Nylon fibre composition, impregnated with high-performance ceramic abrasive grain provides flexibility, so the discs do not gouge the work surface, instead shaping to its contours
- The open structure between the fibres prevents clogging and reduces heat build-up for a great finish, first time
- Cut costs by replacing some processes; multiple applications can be carried out with only one disc
- Leaves the surface thoroughly cleaned to ensure excellent adhesion for the next stage of the process



BLAZE RAPID STRIP WHEELS

- For use on flexible shaft grinders, straight grinders and drills
- Ideal for corners and tight spaces
- Cut costs by replacing some processes; multiple applications can be carried out with only one disc
- Leaves the surface thoroughly cleaned to ensure excellent adhesion for the next stage of the process

| DIMENSIONS (mm) | GRADE | MAX RPM | ART. NO. | PK QTY |
|--------------------|--------------|------------|-------------|-----------|
| 100 x 13 x 12 | Extra coarse | 8000 | 66623304856 | 25 |
| 150 x 13 x 12 | Extra coarse | 8000 | 66261099378 | 15 |





MOUNTING Use with TR+ holder, order separately



BLAZE RAPID STRIP SPEEDLOK DISCS #++++

🕭 TR+

- For use on flexible grinders, straight grinders and drills
- Ideal for rust removal from small intricate areas

| DIMENSIONS (mm) | GRADE | MAX RPM | ART. NO. | PK QTY |
|--------------------|--------------|------------|-------------|-----------|
| 100 | Extra coarse | 8000 | 66623303921 | 5 |

BLAZE RAPID STRIP DISCS

• Depressed centre disc for use on an angle grinder to work on large surfaces

| DIMENSIONS (mm) | CAP CODE | GRADE | MAX RPM | ART. NO. | PK QTY |
|--------------------|-------------|--------------|------------|-------------|-----------|
| 115 x 22 | R9101 | Extra coarse | 12000 | 66623303783 | 10 |
| 125 x 22 | R9101 | Extra coarse | 11000 | 66623303916 | 10 |
| 178 x 22 | R9101 | Extra coarse | 8000 | 66623303920 | 10 |





WHEEL HOLDER

• Tool holders for Rapid Strip discs

| ART NO. | PK QTY |
|-------------|-------------|
| 07660707022 | 10 |
| 07660707023 | 12 |
| | 07660707022 |

BEARTEX HIGH STRENGTH DISCS

- Abrasive and nylon formulation won't tear when used on burrs and sharp edges
- Smear-proof resin binders help to produce a great finish every time without the need for rework

| DIMENSIONS (mm) | GRADE | ART. NO. | PK QTY |
|--------------------|--------|-------------|-----------|
| 100 x 10 x 8 | Medium | 66254429562 | 10 |





- The nylon fibre composition of the wheel, impregnated with abrasive, gives Rapid Strip wheels flexibility so they do not gouge the work surface, instead shaping to its contours
- The open structure between the fibres prevents clogging and reduces heat build-up for a great finish, first time
- Good material removal for applications where less pressure is required



RAPID STRIP SPEEDLOK DISCS



- For use on flexible shaft grinders, straight grinders and drills
- Ideal for corners and tight spaces
- Good material removal for applications where less pressure is required

| DIMENSIONS (mm) | GRADE | ART. NO. | PK QTY |
|--------------------|--------|--------------|-----------|
| 100 | Coarse | 63642585751* | 5 |

* Made-to-order

RAPID STRIP WHEELS RSF

• Depressed centre disc for use on an angle grinder to work on large surfaces

| DIMENSIONS (mm) | GRADE | MAX RPM | ART. NO. | PK QTY |
|--------------------|--------|------------|-------------|-----------|
| 115 x 22 | Coarse | 11000 | 63642585732 | 5 |
| 115 x 22 | Coarse | 12000 | 66261009649 | 10 |
| 125 x 22 | Coarse | 8500 | 63642585749 | 5 |
| 125 x 22 | Coarse | 12000 | 66261030655 | 10 |

RAPID STRIP WHEELS RST

- For use on flexible shaft grinders, straight grinders and drills
- Ideal for corners and tight spaces
- Good material removal for applications where less pressure is required

| DIMENSIONS (mm) | GRADE | ART. NO. | PK QTY |
|--------------------|--------|-------------|-----------|
| 100 x 13 x 6 | Coarse | 63642557742 | 10 |
| 100 x 25 x 6 | Coarse | 63642557745 | 5 |
| 150 x 13 x 8 | Coarse | 63642557743 | 10 |







QUICK CHANGE DISCS FOR SMALL AREAS

Known as 'Quick Change Discs' for their convenience and speed during disc changeover, these mini discs have a special fastening system, which enables discs to be changed quickly so no time is wasted during the application process. Designed for blending, breaking edges and removing parting lines and machine marks the discs are small in diameter, ideal for hard-to-reach areas and mild contours as well as small, flat surfaces.







MACHINES For use on pneumatic tools and pencil grinders.

MOUNTING

TR: Roll-on/roll-off system using a nylon threaded male button on a pad (TR) with spindle.

BLAZE X-TREME LIFE DISCS R980



- Premium ceramic grain delivers powerful cutting performance on stainless steel, inconels, chromium cobalt and titanium, even at medium pressure
- Premium ceramic alumina abrasive grain provides a cool, fast cut and long product life
- Supersize layer contains active filler, which promotes cool cutting and longer product life

| DIA (mm) | GRIT | ART. NO. | PK QTY |
|-------------|------|-------------|-----------|
| | 36 | 63642597039 | 50 |
| E0 | 50 | 63642597045 | 50 |
| 50 mm | 60 | 63642597050 | 50 |
| | 80 | 63642597052 | 50 |
| | 36 | 63642597053 | 50 |
| 75 | 50 | 63642597057 | 50 |
| 75 mm - | 60 | 63642597060 | 50 |
| | 80 | 63642597062 | 50 |



BLAZE F980 +++++



- Patented ceramic grain delivers an outstanding cut rate, which significantly outperforms similar competitor products
- The self-lubricating, advanced supersized treatment reduces heat build-up, loading and glazing on a stainless steel, titanium and super alloys. High-performance resins offer superior grain retention, which extends the product life and keeps the disc effective for longer

| DIA (mm) | GRIT | ART. NO. | PK QTY |
|-------------|------|-------------|-----------|
| | 36 | 66261058704 | 25 |
| E0 | 50 | 66261058705 | 25 |
| 50 mm | 60 | 66261058706 | 25 |
| | 80 | 66261058707 | 25 |
| | 36 | 66261058708 | 25 |
| 75 mm | 50 | 66261058709 | 25 |
| | 60 | 66261058711 | 25 |
| | 80 | 66261058712 | 25 |





- Premium self-sharpening NorZon grain delivers fast-cutting capability and high stock removal rates
- The SpeedLok fixing system makes changing the discs quick and easy, reducing process time
- Grinding, blending and finishing are all possible using the same tool, as NorZon discs are available in a wide range of grit sizes

| 36 63642560882 50 50 69957389455 50 50 mm 60 63642556396 50 80 63642560884 50 |)IA mm) | GRADE | ART. NO. | PK QTY |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------|-------------|-----------|
| 50 mm 60 63642556396 50 | | 36 | 63642560882 | 50 |
| | | 50 | 69957389455 | 50 |
| 80 63642560884 50 | 0 mm | 60 | 63642556396 | 50 |
| | | 80 | 63642560884 | 50 |
| 120 63642560885 50 | | 120 | 63642560885 | 50 |
| 36 63642560886 50 | | 36 | 63642560886 | 50 |
| 50 69957389465 50 | | 50 | 69957389465 | 50 |
| 75 mm 60 63642560887 50 | 5 mm | 60 | 63642560887 | 50 |
| 80 63642560888 50 | | 80 | 63642560888 | 50 |
| 120 66261137003 50 | | 120 | 66261137003 | 50 |





MACHINES

For use on pneumatic tools and mini angle grinders.

MOUNTING

TR: Roll-on/roll-off system using a nylon threaded male button on a pad (TR) with spindle.






MACHINES For use on pneumatic tools and mini angle grinders.





MACHINES For use on pneumatic tools and mini angle grinders.





MACHINES For use on pneumatic tools and mini angle grinders.

BLAZE MINI FLAP DISCS R980

🕭 TR

- A mini version of the flap disc, ideal for cleaning and removing metal from flanges, panels, and finishing prior to applying primer
- Extra heavy-duty plastic backing supports aggressive applications where more pressure is required
- Supersize layer contains active filler for cool cutting and long product life

| GRIT | 50mm | RECOMMENDED BACK UP PAD | PK QTY |
|------|-------------|----------------------------|-----------|
| 40 | 66261120104 | | 10 |
| 60 | 66261120109 | 63642556629 | 10 |
| 80 | 66261120110 | | 10 |

X-TREME MINI FLAP DISCS R828

- Ideal for cleaning, removing metal and finishing welds before applying primer
- NorZon grain provides high stock removal rates with medium to high pressure
- The backing system allows flexibility in blending and finishing operations and the small size can access hard-to-reach areas

| GRIT | 50 mm | 75 mm | RECOMMENDED BACK UP PAD | PK QTY |
|------|-------------|-------------|----------------------------|-----------|
| 40 | 66261180892 | 63642527476 | | 10 |
| 60 | 66261180893 | 66261180904 | 63642556629 | 10 |
| 80 | 66261180894 | 63642527482 | | 10 |



X-TREME MINI-FLEXI FLAP DISCS R828

A TR

TR 🖉

Grit

50

75

on soft metals

- Blend and finish small curved surfaces and contours with the flexible flap construction, which makes light work of small welds, rust and metal
- NorZon grain provides high stock removal rates with medium to high pressure
- The backing system allows flexibility in blending and finishing operations and the small size can access hard-to-reach areas

BLAZE RAPID STRIP +++++

• Heavily coated with super-sharp ceramic alumina grains,

The open structure will not shed on rusted surfaces or load

ART. NO.

66623303912

66261096557

which ensures this disc will last twice as long as competitor products
Use for multiple operations, including stripping, cleaning and finishing; provides a comparable finish to a medium surface conditioning disc

ΡK

QTY

25

25

| GRIT | 50 mm | PK QTY |
|------|-------------|-----------|
| 40 | 66261180889 | 10 |
| 60 | 66261180890 | 10 |
| 80 | 66261180891 | 10 |



MACHINES For use on pneumatic tools and mini angle grinders.





MOUNTING Roll-on/roll-off system using a nylon threaded male button on a pad

GRADE

Extra coarse

Extra coarse

RAPID STRIP / ++++/



- The flexibility of Rapid Strip wheels prevents them from causing damage to the work surface, allowing them to conform to its contours
- The open structure between the fibres prevents clogging and reduces heat build-up for a great finish, first time
- Good material removal for applications where less pressure is required

| DIMENSIONS (mm) | GRADE | ART. NO. | PK QTY |
|--------------------|--------------|-------------|-----------|
| 50 mm | Extra coarse | 63642588173 | 10 |
| 75 mm | Extra coarse | 63642588175 | 10 |

MOUNTING: TR: Roll-on/roll-off system using a nylon threaded male button on a pad









VORTEX RAPID BLEND OPEN

- An advanced grain technology delivers a controlled cut-rate, consistent finish to the workpiece and a long product life that results in fewer disc changes
- The open web structure allows the operator to blend in threedimensions; using the face, edge and back of the disc
- Open web structure avoids loading, even on soft metals

| GRIT | 50 mm | 75 mm | PK QTY |
|--------|-------------|-------------|--------|
| Medium | 66254497067 | 66254497068 | 25 |

MOUNTING: TR: Roll-on/roll-off system using a nylon threaded male button on a pad





MACHINES

For use on pneumatic tools and mini angle grinders.

MOUNTING

TR: Roll-on/roll-off system using a nylon threaded male button on a pad (TR) with spindle.

VORTEX RAPID PREP SCM /++++/

- Features a thick layer of specialised Vortex grain, which extends product life and eliminates grit sequences by combining the cutting speed of a coarse grit and the finishing qualities of a fine grit
- The advanced resin system and specialised Vortex grain imparts a superior smear-free finish and will not load on aluminium and other similar soft metals

| DIA (mm) | CAP CODE | GRADE | TR | PK QTY |
|----------|-------------|--------------|-------------|-----------|
| | S2103 | Extra coarse | 66623378336 | 50 |
| | S2203 | Coarse | 66623378340 | 50 |
| 50 mm | S2303 | Medium | 66623378342 | 50 |
| | 2403 | Fine | 66623378345 | 50 |
| | S2503 | Very fine | 66623378347 | 50 |
| | S2103 | Extra coarse | 66623378337 | 25 |
| | S2203 | Coarse | 66623378341 | 25 |
| 75 mm | S2303 | Medium | 66623378343 | 25 |
| | 2403 | Fine | 66623378346 | 25 |
| | S2503 | Very fine | 66623378348 | 25 |



RAPID PREP AO SCM /++++/



- The open structure resists loading on softer metals, so the disc can be used for longer before being changed, reducing down time and overall abrasive cost
- A high content of abrasive throughout the disc means the cut rate is consistently high throughout its life
- A flexible disc which conforms to contours

| DIA | CAP CODE | GRADE | TR | PK QTY |
|-------|----------|--------------|-------------|-----------|
| | S2108 | Extra coarse | 66623378355 | 50 |
| | S2208 | Coarse | 66623378359 | 50 |
| 50 mm | S2308 | Medium | 66623378363 | 50 |
| | S2408 | Fine | 66623378366 | 50 |
| | S2508 | Very fine | 66623378372 | 50 |
| | S2108 | Extra coarse | 66623378356 | 50 |
| | S2208 | Coarse | 66623378360 | 50 |
| 75 mm | S2308 | Medium | 66623378364 | 50 |
| | S2508 | Very fine | 66623378373 | 50 |
| | S2408 | Fine | 66623378382 | 50 |





MACHINES For use on pneumatic tools and mini angle grinders.

MINI ANGLE GRINDER

- Model: Norton Mini Angle grinder 50mm (2")
- 22.000 MAX RPM (0.45 HP)
- Designed for use with the quick-change back-up pad, SpeedLok and mini flap discs
- Use with 38mm and 50mm quick change sanding discs and spindle mounted sanding specialities only. The accessories must have a rated speed greater than the speed marked on the tool



6mm

0.742 kg

| 50mm (2") 22.000 MAX RPM (0.45 HP) mini angle grinder | 66261177765 | Rear | Level | 85 l/min |
|----------------------------------------------------------|-------------|------|-------|----------|
| | | | | |

ART NO.

EXHAUST

DIRECTION

APPLICATION TIPS:



DESCRIPTION

- Air tools require regular lubrication throughout the life of the tool. The air motor and bearing use compressed air to power the tool. As moisture in compressed, air will rust the air motor, therefore it must be lubricated daily. An inline oiling device is recommended.
- This is an UNGUARDED tool and should NEVER be used with cut-off discs or other bonded abrasive grinding wheels. Do not use any product with a maximum RPM rating lower than the tool's marked RPM.



MINI ANGLE GRINDER KIT

- Ideal for metal car bodywork; the kit contains an assortment of abrasive SpeedLok discs of the most popular grades for stripping, deburring and surface blending, and the Norton mini right-angle grinder
- The Norton mini grinder is compact, lightweight and ideal for use on small or awkward areas.
- The SpeedLok quick change system means discs can be changed quickly, reducing downtime and speeding up the job

| DESCRIPTION | QTY IN KIT | ART. NO. |
|-------------------------------------------|---------------|-------------|
| 50mm Quick Change Holder TR | 1 | |
| 50mm Vortex Rapid Prep SCM medium discs | 10 | |
| 50mm Blaze F980 P36 discs | 25 | 69957300298 |
| 50mm Blaze Rapid Strip extra coarse discs | 10 | 6995/300298 |
| Tool bag | 1 | |
| Norton mini right angle grinder | 1 | |



MINI ANGLE GRINDER KIT

STRIPPING TO BLENDING METAL INCLUDES MACHINE & ABRASIVES (50mm)

- The kit contains an assortment of abrasive SpeedLok discs of the most popular grades for stripping, deburring and surface blending, and the Norton mini right-angle grinder
- The Norton mini grinder is compact, lightweight and ideal for use on small or awkward areas
- The SpeedLok quick change system means discs can be changed quickly, reducing downtime and speeding up the job
- All products come in a handy Norton tool bag, which can be reused

| DESCRIPTION | QTY IN KIT | ART. NO. | |
|---------------------------------------------------------|------------|-------------|--|
| Mini angle grinder Ø 50mm (2") 22,000 MAX RPM (0.45 HP) | 1 | | |
| Speedlok Blaze Ø 50mm R980 P36 | 5 | | |
| Speedlok Blaze Ø 50mm R980 P50 | 5 | | |
| Speedlok Blaze Ø 50mm R980 P60 | 5 | | |
| Speedlok Blaze Ø 50mm R980 P80 | 5 | | |
| Speedlok Blaze Ø 50mm F980 P36 | 5 | | |
| Speedlok Blaze Ø 50mm F980 P50 | 5 | | |
| Speedlok Blaze Ø 50mm F980 P60 | 5 | 700707070/0 | |
| Speedlok Blaze Ø 50mm F980 P80 | 5 | 78072707340 | |
| Vortex Rapid Blend Ø 50mm | 5 | | |
| Rapid Strip Blaze Ø 50mm TR | 5 | | |
| High strength medium disc Ø 50mm | 5 | | |
| Pad for mini angle grinder Ø25 x 6mm - medium | 1 | | |
| Pad for mini angle grinder Ø50 x 6mm - hard | 1 | | |
| Safety glasses – standard | 1 | | |
| Norton bag | 1 | | |



QUICK CHANGE DISC HOLDER TR

• TR ATTACHMENT: Roll-on/roll-off system using a nylon threaded male button on a pad (TR) with spindle

| TR/TS | DIMS | Medium | Hard | PK QTY |
|-------|-------|-------------|-------------|-----------|
| TR | 50 mm | 07660717817 | 63642586931 | 1 |
| TR | 38 mm | 63642556629 | | 1 |
| | 75 mm | 63642556631 | 66254401460 | 1 |

QUICK CHANGE DISC HOLDER TR+

- Suitable for Rapid Strip discs
- For 100mm Speedlock TR+ discs

| DENSITY | ART. NO | PK QTY |
|---------|-------------|-----------|
| Hard | 63642586196 | 1 |
| | | |





FILE BELTS

Narrow width multi-purpose belts for sanding hard-to-reach areas. These belts are designed with ceramic grain to offer the best productivity and efficiency. File belts can be used for paint removal, cleaning, removing rust, sanding welding points and much more.

PNEUMATIC FILE BELT SANDER

- The Norton pneumatic file belt sander makes life easier when used in hard-to-reach and awkward applications and areas
- Use with Norton file belts for stock removal, deburring or surface preparation and defect removal on corners, contours and tight areas
- Small but powerful file belt sander with 0.5 hp motor, for a mighty output
- Ergonomic soft grip improves manoeuvrability and reduces operator fatigue



| DESCRIPTION | ART NO. | BELT SIZE | HORSEPOWER | FREE SPEED | RECOMMENDED OPERATING PRESSURE | TOOL WEIGHT |
|----------------------------|-------------|-----------|------------|---------------|-----------------------------------|----------------|
| Pneumatic file belt sander | 77696091766 | 10x330mm | 0.5 | 18,000rpm | 6.2 bar | 0.82 kg |



PNEUMATIC FILE BELT KIT

- The kit contains a wide assortment of premium ceramic and non-woven file belts, complete with pneumatic file belt sander
- The ultimate solution for all applications from removal of rust and corrosion, deburring, blending and finishing panels
- Machine is 10x330mm. All belts are 10x300mm to fit the machine

| DESCRIPTION | QTY IN KIT | ART. NO. |
|------------------------------------|---------------|-------------|
| File belt machine | 1 | |
| File belt R929 P60 | 20 | |
| File belt R929 P80 | 20 | |
| File belt 10x330mm BearTex: Coarse | 10 | 78072707299 |
| File belt 10x330mm BearTex: Medium | 10 | _ |
| File belt 10x330mm BearTex: Fine | 10 | |
| Norton tool bag | 1 | _ |





FILE BELTS R929 +++++

- Combined SG and aluminium oxide abrasive grain provides an outstanding cut-rate even at low to medium pressure and imparts an excellent surface finish
- Featuring a strong polyester cloth backing and phenolic bond with active fillers for a cool and fast cut

| GRIT | 20mm x 520mm | 10mm x 330mm | PK QTY |
|------|--------------|--------------|-----------|
| 40 | 66623303272 | 66623303110 | 10 |
| 60 | 66261029755 | 66261144369 | 10 |
| 80 | 66623303275 | 66623303270 | 10 |
| 120 | 66623303276 | 66623303271 | 10 |



RAPIDPREP SURFACE ++++ CONDITIONING FILE BELTS

- Strong synthetic mesh and aluminium oxide abrasive bonded together with a smear-resistant adhesive
- Open construction of non-woven material for tough cutting action without clogging or loading
- Ideal for removing paint, rust, adhesives, coatings and sealant corrosion in hard-to-access areas

| GRADE | 10mm x 300mm | PK QTY |
|-----------|--------------|-----------|
| Coarse | 69957360172 | 10 |
| Medium | 63642578004 | 10 |
| Very Fine | 69957360176 | 10 |



METAL WORKING

HANDY ROLLS

Great for manual sanding operations especially on curved surfaces thanks to the flexibility of the cloth backing. Available in grades from stripping to finishing.



HANDY ROLLS R222

- Aluminium oxide abrasive is sharp enough to remove material with manual pressure
- Cloth backing provides flexibility for sanding round pipes, contours and curves and can also be torn easily to size
- Resin bond system promotes excellent grain adhesion for applications from deburring to blending and finishing


| GRIT | 38mm x 25m | ΡΚ QTY |
|------|-------------|--------|
| 40 | 63642531828 | 1 |
| 50 | 63642531826 | 1 |
| 60 | 63642531824 | 1 |
| 80 | 63642531821 | 1 |
| 100 | 63642531817 | 1 |
| 120 | 63642531812 | 1 |
| 150 | 63642531809 | 1 |
| 180 | 63642531806 | 1 |
| 220 | 63642531803 | 1 |
| 240 | 63642531800 | 1 |
| 280 | 63642536425 | 1 |
| 320 | 63642531797 | 1 |
| 400 | 63642531794 | 1 |
| 600 | 63642539150 | 1 |
| | | |

STEP DRILLS, CARBIDE BURRS, WIRE BRUSHES

Drilling, cleaning and removing rust, paint, corrosion and weld spatters.

NEW STEP DRILLS HSSM2-TIN

- Ideal for drilling repetitive holes in metal sheets or tubes
- Fast penetration, centre and drill in one operation
- Works optimally on steel, cast iron, brass and plastics
- Also can be used on stainless steel and bronze
- Covers most common materials and hole dimensions





| $L_1 x D_1 x D_2 x D_3 (mm)$ | STEPS | HOLE DIAMETERS (mm) | MAX HOLE DEPTH (mm) | ΡΚ QTY | ITEM ART NO. | ART NO. |
|------------------------------|-------|----------------------------------------|------------------------|--------|--------------|------------|
| 65x4x12x6 | 9 | 4-5-6-7-8-9-10-11-12 | 3 | 1 | 78072765476 | |
| 75x4x20x8 | 9 | 4-6-8-10-12-14-16-18-20 | 4 | 1 | 5539553840 | 5539553847 |
| 100x4x30x10 | 14 | 4-6-8-10-12-14-16-18-20-22-24-26-28-30 | 4 | 1 | 5539553845 | - |

METAL WORKING



NEW X-TREM CUT 5 **++++** CARBIDE BURR KIT

- Longer life, faster stock removal and better finish than double-cut carbide burrs
- For use on steel, stainless steel, cast iron, nickel alloys, cobalt alloys and titanium
- Ideal for fast weld removal and cleaning

| SHAPE | $D_1 x L_1 x D_2 x L_2$ (mm) | ART NO. | PK QTY | ART NO. |
|-------|------------------------------|-------------|--------|-------------|
| А | 12x25x6x70 | 78072753479 | 1 | |
| С | 12x25x6x70 | 78072753481 | 1 | |
| D | 12,7x10,8x6x,56 | 78072756783 | 1 | 78072756854 |
| F | 12x25x6x70 | 78072753486 | 1 | |
| L | 12x30x6x75 | 78072756853 | 1 | |

S STATE

NEW BRUSHES **H**+++ WITH PLASTIC HANDLE

- Hand brush for cleaning works in hard-to-reach areas
- Ergonomic plastic grip for better comfort in use

| L ₁ xL ₂ xL (mm) | NUMBER OF ROWS | PK QTY | ART NO. | | |
|----------------------------------------|-------------------------------------------------|-----------------|-------------|--|--|
| PLASTIC HAND NORMA | PLASTIC HAND NORMAL STEEL STRAIGHT WIRE 0.30 mm | | | | |
| 265x140x25 | 1R | 12 | 66254405470 | | |
| PLASTIC HAND STAINL | ESS STEEL STRAIG | HT WIRE 0.30 mm | | | |
| 265x140x25 | 1R | 12 | 66254405471 | | |
| PLASTIC HAND BRASS | CRIMPED WIRE 0.3 | 0 mm NON SPARK | | | |
| 265x140x25 | 1R | 12 | 66254405473 | | |



NEW NON SPARK **++++** HAND BRUSH

• For precision cleaning operations in environments where 'traditional' wire brushes may create sparks

| L ₁ xL ₂ xL (mm) | WIRE | ROWS | PK QTY | ART NO. |
|----------------------------------------|------|------|-----------|-------------|
| SPB | | | | |
| 200x18x45 | 0.20 | 3x6R | 12 | 66254405474 |

MANUAL SANDING

| PRE-CUT ROLLS Cyclonic Multi-Air pre-cut rolls | - 42 |
|---------------------------------------------------|------|
| CUT SHEETS & SHEETS | - 43 |
| Cut sheets | _ 43 |
| Sheets | |
| ROLLS | - 47 |
| Self-grip rolls | _ 4/ |
| Paper rolls | |
| SANDING BLOCKS, KITS & HOSES | - 49 |
| Sanding blocks | _ 47 |
| Hoses | |
| Sanding block kits | |

MANUAL SANDING

PRE-CUT ROLLS

Norton Cyclonic pre-cut rolls are made using the latest technology to ensure that each stage of sanding provides the best finish for the next stage of the process, minimising sanding time, increasing productivity, and providing the perfect surface finish prior to painting.



As part of the Norton Cyclonic Sanding System, these rolls provide the best solution for panel preparation, from filler levelling to primer sanding.

FOR MORE INFORMATION ABOUT CYCLONIC, SEE PAGE 06.







CYCLONIC MULTI-AIR PRE-CUT ROLLS #++++

Dogo

- As part of Cyclonic sanding system, the colour-coded backing represents each application step for fast and easy product selection in panel preparation, from filler levelling to primer sanding, speeding up the process
- Self-sharpening ceramic grain delivers superior cutting performance and longer life than other abrasive grains. Ceramic grains also cut cooler, and wear more evenly, providing consistent sanding results and a distinctly uniform scratch pattern
- The No-Fil[®] formula prevents premature clogging of the abrasive, extending sanding time
- The self-grip backing is available in two dimensions that fit all sanding blocks for a fast and easy process from start to finish


| STEP | COLOUR | APPLICATION | 72mm x 12m | 115mm x 12m | PK QTY | BOX QTY |
|----------|--------|------------------------------------|-------------|-------------|--------|---------|
| Optional | Blue | Stripping & levelling (Heavy Duty) | 66261151791 | 69957305936 | 1 | 4 |
| 1 | Green | Stripping & filler levelling | 66261151792 | 69957305937 | 1 | 4 |
| 2 | Red | Filler finishing | 66261151793 | 69957305939 | 1 | 4 |
| 3 | Salmon | Primer sanding | 66261151794 | 69957305940 | 1 | 4 |

CUT SHEETS & SHEETS

Manufactured to the most exacting standards, Norton's range of sanding sheets are second to none. Each product within the portfolio is designed to deliver a high-quality, consistent finish at every stage of your process. Whether you are dry sanding primer, deburring, or removing scratches, Norton has a sanding sheet for your application.



Norton Multi-Air cut sheets are specially designed for dry sanding operations, to cut faster, run cooler, resist loading and last longer than conventional sandpaper.



MULTI-AIR WITH NORZON TECHNOLOGY H835 #++++



- Aggressive cutting performance for heavy-duty applications, including paint stripping and removal of body filler when sanding and flattening sharp edges, whilst imparting a consistent and uniform scratch pattern
- Heavy E-weight paper backing adds resistance to help this range withstand tough removal of filler on bare metal





| GRIT | 70 x 125 mm | 70 x 198 mm | 70 x 420 mm | 115 x 230 mm | ΡΚ QTY | BOX QTY |
|------|--------------|-------------|-------------|--------------|--------|---------|
| 40 | 69957394449* | 69957394363 | 69957394450 | 69957394452 | 50 | 200 |
| 60 | 69957394350* | 69957394367 | 69957394358 | 69957394453 | 50 | 200 |
| 80 | 69957394355* | 69957394369 | 69957394360 | 69957394454 | 50 | 200 |
| 120 | 69957394357* | 69957394451 | 69957394361 | 69957394455 | 50 | 200 |
| | | | | | | |

* Made-to-order

MANUAL SANDING



MULTI-AIR PLUS A975 +++++

20000

- The advanced No-Fil[®] coating both prevents build-up of dust and avoids premature clogging. In very fine grits, it can be used for final dry sanding before sprayin without the risk of developing runs
- Patented Norton ceramic grain is blended with premium heat-treated aluminium oxide to deliver a very high cut-rate that lasts up to twice as long as conventional abrasives and imparts a consistent, uniform scratch pattern
- A unique fibre-reinforced latex paper backing adds to the flexibility and makes the cut sheets tear-resistant in all the applications

.....

• Specifically designed for paint sanding from levelling filler to finishing primer



| | | | | | РК | вох |
|------|--------------|--------------|--------------|--------------|-----|-----|
| GRIT | 70 x 125 mm | 70 x 198 mm | 70 x 420 mm | 115 x 230 mm | QTY | QTY |
| 80 | 69957394456 | 69957394470 | 69957394463 | 69957394479 | 50 | 200 |
| 120 | 69957394457 | 69957394472 | 69957394464 | 69957394481 | 50 | 200 |
| 150 | 69957394458* | 69957394473 | 69957394465 | 69957394482 | 50 | 200 |
| 180 | 69957394459 | 69957394474 | 69957394466 | 69957394483 | 50 | 200 |
| 220 | 69957396408* | 69957396410 | 69957396406 | 69957396414 | 50 | 200 |
| 240 | 69957394460 | 69957394475 | 69957394467 | 69957394484 | 50 | 200 |
| 280 | | 69957396411* | 69957396407* | 69957396415* | 50 | 200 |
| 320 | 69957394461 | 69957394477 | 69957394468 | 69957394485 | 50 | 200 |
| 400 | 69957394462 | 69957394478 | 69957394469 | 69957394486 | 50 | 200 |
| | | | | | | |

* Made-to-order



MESH-POWER

Experience powerful dust extraction with Norton MeshPower. A significant upgrade on traditional perforated discs, this solution is truly multi-functional. Designed with thousands of holes that are created by a unique mesh matrix; the MeshPower structure provides excellent dust extraction in any application. A reduction in clean-up time is also a welcome benefit for any busy sander!

FOR MORE INFORMATION ON MESHPOWER SEE PAGE 08

MESH POWER CERAMIC M920

- Ceramic grain provides the highest performance thanks to its micro-fracturing properties, which means the abrasive stays sharper and lasts longer than the aluminium oxide version
- No-Fil[®] technology is applied to the abrasive grain for longer product life and a consistent cut for the entire life of the product
- Abrasive can be used wet or dry for the perfect results
- No defined hole pattern, saves time and effort aligning holes, just apply, and go



| GRIT | 70 x 125 mm | 70 x 198 mm | 70 x 420 mm | 115 x 230 mm | PK QTY | BOX QTY |
|------|-------------|-------------|-------------|--------------|--------|---------|
| 80 | 69957325770 | 69957325962 | 69957325986 | 69957326057 | 50 | 200 |
| 120 | 69957325772 | 69957325963 | 69957325987 | 69957326062 | 50 | 200 |
| 180 | 69957325773 | 69957325964 | 69957325988 | 69957326063 | 50 | 200 |
| 240 | 69957325774 | 69957325965 | 69957325990 | 69957326065 | 50 | 200 |
| 320 | 69957325775 | 69957325966 | 69957325991 | 69957326068 | 50 | 200 |

MESH POWER ALUMINIUM OXIDE M220

- Good performance on primer, filler, paint, lacquer, fibreglass, aluminium, gel coat and plastic in panel repair, spot repair and bumper repair on used or new panels. Use by hand or with a machine
- No-Fil® technology is applied to the abrasive grain for longer product life and a consistent cut for the entire life of the product
- Abrasive can be used wet or dry for the perfect results
- No defined hole pattern, saves time and effort aligning holes, just apply, and go

| GRIT | 70 x 198 mm | 70 x 420 mm | PK QTY | BOX QTY |
|------|-------------|-------------|--------|---------|
| 80 | 69957326280 | 69957326288 | 50 | 200 |
| 120 | 69957326281 | 69957326289 | 50 | 200 |
| 180 | 69957326283 | 69957326291 | 50 | 200 |
| 240 | 69957326285 | 69957326292 | 50 | 200 |
| 320 | 69957326286 | 69957326294 | 50 | 200 |
| | | | | |





 \sim

NORTON MULTI-AIR PAD SAVER

| ~ <i>000</i> 00 | | | |
|-----------------|------------|-------------|--------|
| DIMENSIONS | TYPE/GRADE | ART NO. | PK QTY |
| 70 x 198mm | Multi-Air | 69957328431 | 1 |
| 70 x 400mm | Multi-Air | 69957328432 | 1 |



NORTON PRO A275 /////

- Aluminium oxide abrasive grain for manual sanding of all paint layers and lacquer, until smoothing clear coat
- No-Fil[®] layer helps to prevent loading, meaning sheets can be used for longer
- Sheets can be used for manual sanding at size (230x280mm) or folded/ cut and used with an orbital machine or manual sanding block, pre-cut sheets (115x280mm) are also for use by hand or with an orbital sander



| GRIT | DIMENSION | ART. NO | PK QTY |
|------|---------------|--------------|-----------|
| 80 | | 63642588214* | 50 |
| 120 | | 63642588217* | 50 |
| 150 | | 63642588218* | 50 |
| 180 | 115 x 280mm - | 63642588221* | 50 |
| 240 | | 63642588223 | 50 |
| 280 | | 63642588224 | 50 |
| 320 | | 63642588225* | 50 |
| 400 | | 63642588226 | 50 |

| GRIT | DIMENSION | ART. NO | PK QTY |
|------|-------------|-------------|-----------|
| 80 | | 63642558015 | 50 |
| 100 | | 63642585256 | 50 |
| 120 | | 63642558016 | 100 |
| 150 | | 63642586145 | 100 |
| 180 | | 63642558017 | 100 |
| 220 | | 63642586139 | 100 |
| 240 | 230 x 280mm | 63642558018 | 100 |
| 280 | 230 X 280mm | 63642585742 | 100 |
| 320 | | 63642586132 | 100 |
| 360 | | 63642586133 | 100 |
| 400 | | 63642586134 | 100 |
| 500 | | 63642586136 | 100 |
| 600 | | 63642586137 | 100 |
| 800 | | 63642586138 | 100 |
| | | * 14 | |

* Made-to-order

ROLLS

A range of high-performance abrasive rolls for fairing, shaping, sanding and finishing pannels, boats, plugs and moulds. They are easy to use and compatible with any sanding block, file and fairing board.

MESH POWER ROLLS CERAMIC M920 +++++

- Ceramic grain provides the highest performance thanks to its microfracturing properties which mean the abrasive stays sharper and lasts longer than other rolls
- Ideal for a wide range of surfaces and applications including primer, filler, paint, lacquer, fibreglass, aluminium, gel coat and plastic in panel repair, spot repair and bumper repair on used or new panels
- The abrasive grain is impregnated with No-Fil® coating, which resists clogging and extends the product life
- Works perfectly wet or dry, by hand or with a machine

| _ | GRIT | 70mm x 10m | 115mm x 10m | PK QTY | BOX QTY |
|---|---------------|-------------|-------------|--------|---------|
| - | NEW 60 | 78072712625 | 78072712624 | 1 | 4 |
| | 80 | 69957326171 | 69957326269 | 1 | 4 |
| | 120 | 69957326176 | 69957326270 | 1 | 4 |
| | 180 | 69957326178 | 69957326271 | 1 | 4 |
| | 240 | 69957326179 | 69957326272 | 1 | 4 |
| | 320 | 69957326182 | 69957326273 | 1 | 4 |
| _ | | | | | |



MESH-POWER.

MANUAL SANDING





NORTON PRO PAPER ROLLS A275

- Aluminium oxide abrasive with No-Fil[®] layer cuts fast and helps prevent loading, meaning the sanding rolls can be used for longer
- Ideal for sanding filler, primer, gel-coat, aluminium, wood and composite materials

| GRIT | 100mm x 50m | 115mm x 50m | PK QTY |
|------|--------------|-------------|--------|
| 80 | 63642591122 | 69957380739 | 2 |
| 120 | 63642591123 | 69957380761 | 2 |
| 150 | 69957391073 | 69957380765 | 2 |
| 180 | 63642591124* | 69957380767 | 2 |
| 220 | 63642590924 | 69957380769 | 2 |
| 240 | 63642590927 | 69957380777 | 2 |
| 280 | | 69957380778 | 2 |
| 320 | 63642591649* | 69957380779 | 2 |
| 400 | 69957391077* | 69957380781 | 2 |
| 500 | | 69957396696 | 2 |
| | | | |

* Made-to-order



SELF-GRIP ROLLS H231

- Thanks to the E-weight paper backing combined with a premium resin bond, this aluminium oxide roll is designed for heavy-duty sanding on metal, filler, primer, wood and solid surfaces
- Anti-static No-Fil® treatment applied to the abrasive prevents clogging when in use

| GRIT | 115mm x 25m | PK QTY |
|------|-------------|--------|
| 40 | 69957391121 | 2 |
| 60 | 69957391123 | 2 |
| 80 | 69957391133 | 2 |





NORTON PRO SELF-GRIP ROLLS A275

- Aluminium oxide abrasive with No-Fil[®] layer cuts fast and helps prevent loading, meaning the sanding rolls can be used for longer
- Ideal for sanding filler, wood, fiberglass and composites

| GRIT | 115mm x 25m | PK QTY |
|------|-------------|--------|
| 120 | 69957391218 | 2 |
| 150 | 69957391219 | 2 |
| 180 | 69957391220 | 2 |
| 220 | 69957391221 | 2 |
| 240 | 69957391222 | 2 |
| 320 | 69957391224 | 2 |
| 400 | 69957391225 | 2 |

SANDING BLOCKS, KITS & HOSES

Multi-Air sanding blocks are ergonomic, resistant and built for the best dust extraction. The special rubber grip is ergonomic and easy to hold. All the Multi-Air blocks are provided with a regulating valve to regulate suction power and optimise air/dust flow.



MULTI-AIR SANDING BLOCKS

- The perfect partner for Norton abrasives for high-dust extraction, including Norton Cyclonic, Multi-Air or MeshPower, for cut sheets or rolls, available in a range of sizes for any product dimension
- An in-built air chamber keeps sanding dust-free and the workplace clean
- Robust, impact-resistant plastic body that has been built to last and stand up to the rigours of day-to-day use
- Comfortable rubber grip helps the user maintain control over the process





| * | \$ | 20. | <i>~</i> | |
|-------------|-------------|-------------|--------------|--------|
| 70 x 125 mm | 70 x 198 mm | 70 x 400 mm | 115 x 230 mm | PK QTY |
| 69957396645 | 69957396646 | 69957396648 | 69957396644 | 1 |

ATTACHABLE HOSE

- A 4 m long flexible tube
- Supplied together with a conical universal adapter

| DESCRIPTION | ART NO. | PK QTY |
|--------------|-------------|--------|
| 25/30mm x 4m | 07660767979 | 1 |



MANUAL SANDING



SANDING BLOCK STARTER KIT

00000

- Contains one sanding block in the following dimensions:
 - 70 x 125mm
 - 70 x 198mm
 - 70 x 400mm
 - 115 x 230mm
- Also contains valve and adaptor for fixing to the machine

| DESCRIPTION | QTY IN KIT | ART. NO. |
|-------------|---------------|-------------|
| Starter kit | 1 | 69957396649 |



MULTI-AIR SANDING BLOCK

- *Open*
- Manual sanding block with a set of three self-gripping interchangeable plates: straight, concave and convex
- For use with 150mm Multi-Air discs, in self-grip or Soft-Touch
- Kit contains an air valve

| | QTY IN | |
|-----------------------------|--------|-------------|
| DESCRIPTION | KIT | ART. NO. |
| Multi-Air sanding block kit | 1 | 77696024493 |



| | | _ | 00 | - |
|-----|------|------|----------|---|
| SAN | | ווחו | <u> </u> | |
| SAN | NU | | 2. | |
| | | | | |

| Cyclonic Multi-Air discs & starter kit | JZ |
|------------------------------------------|----------|
| Multi-Air discs | |
| Mesh power discs | |
| Multi-Air back-up pads & interfaces | |
| Blue Fire discs | |
| Norton Pro & Pro Plus discs | |
| Norton Pro & Pro Plus smart repair discs | |
| Norton Pro film discs | |
| Gold Reserve discs | |
| Self-grip back-up pads & interfaces | |
| MACHINES & ACCESSORIES | - 68 |
| DASP Machine | - 00 |
| Vacuum System | |
| Accessories | |
| CUT SHEETS | 72 |
| Multi-Air cut sheets | <u> </u> |
| Multi-air plus cut sheets | |
| | |

SANDING DISCS

Norton offers a comprehensive range of sanding discs tailored to various automotive refinishing tasks. From budget-friendly aluminium oxide options and the aggressive Norzon grain to top-tier ceramic sheets and discs, including the advanced Norton Cyclonic series, we provide the ultimate solutions for every step of the repair process. Our selection includes standard, self-gripping, perforated, and mesh-backed discs, making tasks like paint stripping, smoothing body filler, levelling sharp edges, and sanding door panels more effortless than ever before.



Norton Cyclonic is the ultimate all-in-one sanding system for car repair, colourcoded by application for quick and easy product selection. The next generation in sanding technology. The range includes: discs, rolls, dispenser and accessories.

NORTON CYCLONIC SANDING SYSTEM. SEE PAGE 06 FOR MORE INFORMATION



MULTI-AIR

CYCL🥯

CYCLONIC MULTI-AIR A975

- Made with super sharp ceramic A975 grain and No-Fil® technology for the ultimate cutting performance and a longer product life than conventional grain types. Ceramic grains also cut cooler and wear more evenly for a consistent finish
- For finishing applications, finer-grade discs have a thin foam backing which adapts to surface contours for a smooth, consistent finish. Use with a Multi-Air back-up pad for the best performance
- Ultra-precise laser cutting technology produces a flatter disc, increasing the abrasive surface area and optimising dust extraction
- Self-grip backing and easy-to-align hole configuration reduces downtime wasted between disc changes

| STEP | COLOUR | APPLICATION | BACKING | 150 mm | PK QTY | BOX QTY |
|----------|-----------|------------------------------------|------------------|-------------|-----------|------------|
| Optional | Blue | Stripping & levelling (heavy-duty) | Self-Grip | 66261151661 | 100 | 400 |
| 1 | Green | Stripping & filler levelling | Self-Grip | 66261151676 | 100 | 400 |
| 2 | Red | Filler finishing | Self-Grip | 66261151683 | 100 | 400 |
| 3 | Salmon | Primer sanding | Micro Soft-Touch | 66261151796 | 50 | 400 |
| 4 | Fuchsia | Primer finishing | Micro Soft-Touch | 66261151672 | 50 | 400 |
| Optional | Turquoise | Fadeout & blending | Micro Soft-Touch | 66261151684 | 50 | 400 |

MOUNTING: To be used on 150mm Multi-Air back-up pads on orbital sander.



CYCLONIC MULTI-AIR STARTER KIT

• This unique starter kit contains 30 Cyclonic Multi-Air sanding discs, five of each step and one back-up pad, providing everything you need to trial the new sanding system

| ART. NO. | PK QTY |
|-------------|-----------|
| 66261151852 | 1 |



NORTON CYCLONIC DISPENSER

- A handy storage unit for organising and dispensing the full range of Norton Cyclonic discs and rolls
- One dispenser fits two discs and two multiple units can be fixed together to store the whole range

| ART. NO. | PK QTY |
|-------------|--------|
| 66261151832 | 1 |







YouTube


Multi-Air is made with premium abrasive grain; Multi-Air discs provide substantially longer life thanks to excellent dust extraction, which reduces clogging, and provides a faster cut than conventional abrasives. Available with a Soft-Touch backing.

2003-2023





MOUNTING For use with a Multi-Air back-up pad on an orbital sander.



MOUNTING

For the best performance of Multi-Air Blaze, in the shop it's to be used with Multi-Air back-up pad HARD version (07660719198) see page 59

MULTI-AIR WITH NORZON TECHNOLOGY H835 +++++

20000

- Sharp NorZon grains cuts through old paint layers, body filler and smooth sharp edges with ease and the open coating helps to prevent cloaaina
- High-strength E-weight paper backing is tear resistant and significantly reduces common issues such as curling and edge chipping
- A full resin bond system maintains grain adhesion, ensuring the grain stays intact for longer for maximum productivity for the life of the disc
- Self-grip backing facilitates quick and easy disc changing

| | \bigcirc | | |
|------|-------------|--------|---------|
| GRIT | 150 mm | PK QTY | BOX QTY |
| 40 | 66261086898 | 50 | 200 |
| 60 | 66261086903 | 50 | 200 |
| 80 | 66254434876 | 50 | 200 |
| 120 | 66261086905 | 100 | 400 |



- Ultra-premium ceramic aluminium oxide grain boosts performance with extremely sharp edges and removes over 30% more material with considerably less dust
- An all-new exclusive backing design provides extraordinary strength with tear resistance well beyond any flexible paper in the market
- Unique Norton Multi-Air[®] hole configuration provides a consistent cut throughout the product's life and maximum dust extraction for a cleaner work environment and less potential for contamination
- Norton No-Fil[®] water-based stearate coating ensures you get the superior finish you need without user fatigue, rework and endless consumption of discs through changeovers

| GRIT | 150 mm | ΡΚ QTY | BOX QTY | GRIT | 150 mm | PK QTY | BOX QTY |
|------|-------------|--------|---------|----------------|----------------------|--------|---------|
| 40* | 78072756399 | 50 | 200 | 180 | 78072756405 | 50 | 200 |
| 60* | 78072756400 | 50 | 200 | 220 | 78072756406 | 50 | 200 |
| 80 | 78072756402 | 50 | 200 | 320 | 78072756407 | 50 | 200 |
| 120 | 78072756403 | 50 | 200 | 400 | 78072756408 | 50 | 200 |
| 150 | 78072756404 | 50 | 200 | * Discs P40 ar | nd P60 have 33 holes | | |
| | | | | | | | |



MULTI-AIR PLUS A975 +++++

- SG ceramic blended with heat-treated aluminium oxide grains provides a high, fast cut-rate on primer, paint, composites, marine gelcoat and non-ferrous metals
- The blend of grain provides a consistent and uniform scratch pattern, maintaining the desired surface finish and excellent wear resistance
- In P80 P120 discs, the backing is thicker for more aggressive use, P150 - P800 is thinner for better flexibility in finer applications
- The unique hole configuration and No-Fil[®] coating resists loading to extend disc life by up to two times longer than conventional discs when sanding dry or wet. Disc colour will not transfer to the surface of the working area

| GRIT | 125 mm | 150 mm | ΡΚ QTY | BOX QTY |
|------|-------------|-------------|--------|---------|
| 80 | 63642563535 | 63642565916 | 100 | 400 |
| 120 | 63642563536 | 63642523429 | 100 | 400 |
| 150 | 63642563537 | 63642523430 | 100 | 400 |
| 180 | 63642563538 | 63642565920 | 100 | 400 |
| 220 | | 63642523434 | 100 | 400 |
| 240 | 63642563540 | 63642523435 | 100 | 400 |
| 280 | | 63642523436 | 100 | 400 |
| 320 | 63642563542 | 63642523437 | 100 | 400 |
| 400 | 63642563543 | 63642565925 | 100 | 400 |
| 500 | 66254477930 | 66254477924 | 100 | 400 |
| 600 | | 63642532657 | 100 | 400 |
| 800 | 66254477934 | 66254477926 | 100 | 400 |
| | | | | |

MOUNTING

For use with a 125mm and 150mm medium or hard Multi-Air back-up pad on an orbital sander.





Premium SG ceramic grain blended with heat-treated aluminium oxide grains, provide excellent cutting action for a very high-level finish The foam backing is colour-coded to aid in quick product identification for each stage of sanding

• Fibre-reinforced latex paper creates a flexible and tear-resistant backing

MULTI-AIR PLUS SOFT-TOUCH A975

• Unique hole configuration and No-Fil® coating significantly improves load resistance with no risk of colour transfer thanks to the pigment-free layer

| COLOUR | GRIT | APPLICATION | 150 mm | QTY | QTY |
|-----------|------|-------------------------------------------|-------------|-----|-----|
| Red | 220 | Sanding filler before primer | 66261110863 | 20 | 120 |
| Salmon | 320 | Sanding cataphoretic coats and primer | 63642595575 | 20 | 120 |
| Yellow | 400 | Sanding polyurethane primer | 63642595577 | 20 | 120 |
| Blue dark | 500 | Sanding polyurethane primer | 66254477927 | 20 | 120 |
| Blue | 800 | Cutting back lacquer before a flush joint | 66254477932 | 20 | 120 |
| White | 1000 | Blending on clear coat | 63642536301 | 20 | 120 |
| Green | 1500 | Before polishing and buffing | 66261110864 | 20 | 120 |

MOUNTING For use with a Multi-Air back-up pad on an orbital sander.

+++++

ΡK

BUX





MULTI-AIR PLUS STARTER KIT A975

 Contains a Multi-Air back-up pad and a variety of discs with the Multi-Air hole configuration, providing all you need to trial the Multi-Air Process system

| GRIT | DESCRIPTION | QTY IN KIT | ART. NO. | PK QTY |
|------|---------------------------|---------------|-------------|-----------|
| | Medium Multi-Air Pad | 1 | | |
| P80 | Multi-Air Plus | 5 | | |
| P120 | Multi-Air Plus | 5 | | |
| P240 | Multi-Air Plus | 5 | | |
| P320 | Multi-Air Plus | 5 | 69957395370 | 1 |
| P400 | Multi-Air Plus | 5 | | |
| P400 | Multi-Air Plus Soft-Touch | 5 | | |
| P500 | Multi-Air Plus Soft-Touch | 5 | | |
| P800 | Multi-Air Plus Soft-Touch | 5 | | |
| | | | | |






MULTI-AIR A275 /++++



- Premium, heat-treated aluminium oxide grains provide a fast cutrate in the final sanding stages
- Fibre-reinforced latex paper creates a flexible and tear-resistant backing
- Unique hole configuration and No-Fil® coating significantly improves load resistance and eliminates the risk of colour transfer thanks to the pigment free layer

| | Ø | | |
|------|--------------|--------|---------|
| GRIT | 150 mm | ΡΚ QTY | BOX QTY |
| P80 | 63642560561* | 100 | 400 |
| P120 | 63642560562* | 100 | 400 |
| P150 | 63642560563* | 100 | 400 |
| P180 | 63642560564* | 100 | 400 |
| P220 | 63642560565* | 100 | 400 |
| P240 | 63642560566* | 100 | 400 |
| P280 | 63642560567* | 100 | 400 |
| P320 | 63642560568* | 100 | 400 |
| P360 | 63642560569* | 100 | 400 |
| P400 | 63642560570* | 100 | 400 |
| P500 | 63642560571* | 100 | 400 |
| P600 | 63642560572* | 100 | 400 |
| P800 | 63642560573* | 100 | 400 |
| | | | |





* Made-to-order

MULTI-AIR SOFT TOUCH A275

- Premium, heat-treated aluminium oxide grains provide excellent cutting action for a very high-level finish
- The foam backing is colour-coded to aid in quick product identification for each stage of sanding
- Fibre-reinforced latex paper creates a flexible and tear-resistant backing
- No-Fil® coating is both water-based and pigment-free to significantly improve load resistance and eliminate the risk of colour transfer



| COLOUR | GRIT | APPLICATION | 150 mm | PK QTY | BOX QTY |
|---------------------------------------------------------------------------|------|-------------------------------------------|--------------|-----------|------------|
| Red | 220 | Sanding filler before primer | 66261032770* | 20 | 120 |
| Salmon | 320 | Sanding cataphoretic coats and primer | 66261032772* | 20 | 120 |
| Yellow | 400 | Sanding polyurethane primer | 66261032773* | 20 | 120 |
| Blue dark | 500 | Sanding polyurethane primer | 66261032774* | 20 | 120 |
| Blue | 800 | Cutting back lacquer before a flush joint | 66261032775* | 20 | 120 |
| White | 1000 | Blending on clear coat | 66261034247* | 20 | 120 |
| Green | 1500 | Before polishing and buffing | 66261034248* | 20 | 120 |
| MOUNTING: To be used on Ø150mm Multi-Air back-up pads on orbital sanders. | | | | | -to-order |



Experience powerful dust extraction with Norton MeshPower. A significant upgrade on traditional perforated discs, this solution is truly multi-functional.

FOR MORE INFORMATION ON MULTI-AIR SEE PAGE 08

APPLICATION GUIDE

| GRIT | APPLICATION | BACK-UP PAD | DA SANDER | RPM |
|------|---------------------------------------------|----------------|--------------|-----|
| P80 | Heavy stripping, reinforced filler leveling | Multi-Air | | |
| P120 | Paint stripping, filler leveling | HARD | Orbit | |
| P180 | Filler sanding, plastic sanding (bumpers) | | 5mm | |
| P240 | Filler sanding, plastic finishing (bumpers) | Multi-Air | | |
| P320 | Panel sanding, primer sanding | MEDIUM | Orbit | |
| P400 | Primer finishing | | 2,5mm | |





MESHPOWER CERAMIC M920

- Ceramic grain provides the highest cutting performance thanks to its microfracturing properties, meaning the abrasive stays sharper and lasts longer than the aluminium oxide version
- For use on primer, filler, paint, lacquer, fibreglass, aluminium, gel coat and plastic in panel repair, spot repair and bumper repair on used or new panels
- No-Fil® technology is applied to the abrasive grain for longer product life and a consistent cut for the entire life of the disc
- Abrasive can be used wet or dry for the perfect result

| GRIT | 150 mm | 203 mm | PK QTY | BOX QTY |
|---------------|-------------|--------------|-----------|------------|
| NEW 60 | 78072712627 | 78072712626* | 50 | 400 |
| 80 | 69957325723 | 69957326072 | 50 | 400 |
| 120 | 69957325730 | 69957326073 | 50 | 400 |
| 180 | 69957325731 | 69957326075 | 50 | 400 |
| 240 | 69957325732 | 69957326076 | 50 | 400 |
| 320 | 69957325733 | 69957326077 | 50 | 400 |
| 400 | 69957325736 | 69957326078 | 50 | 400 |
| | _ | | * Made | -to-order |

MOUNTING


For best performance, use with Multi-Air back-up pad, and for longer pad life, use with the pad saver



MESHPOWER ALUMINIUM OXIDE M220 ++++

- A good choice for sanding primer, filler, paint, lacquer, fibreglass, aluminium, gelcoat and plastic in panel repair
- No-Fil® coating resists loading and provides consistent sanding for the entire life of the disc
- Ideal for wet or dry processes
- The self-gripping mesh backing not only provides unbeatable dust extraction, but saves time when changing over; just apply, and carry on

| | | PK | вох |
|------|-------------|-----|-----|
| GRIT | 150 mm | QTY | QTY |
| 80 | 69957326274 | 50 | 400 |
| 120 | 69957326275 | 50 | 400 |
| 180 | 69957326276 | 50 | 400 |
| 240 | 69957326277 | 50 | 400 |
| 320 | 69957326278 | 50 | 400 |
| 400 | 69957326279 | 50 | 400 |





MOUNTING

* Made-to-order

For best performance, use with Multi-Air back-up pad, and for longer pad life, use with the pad saver

MULTI-AIR BACK-UP PADS

- The Multi-Air back-up pad draws dust into a collection chamber for optimal airflow and powerful dust extraction
- The innovative design delivers high-performance and a smoother, unblemished work surface. This is alongside the additional benefit of a clean working environment.
- Multi-Air back-up pad 150mm is available in three densities (125mm in medium and soft).
- Packed in individual boxes with Festool and Rupes adapters, M8 and 5/16" bolts, one metal and three fibre ring spacers to fit all the most common sanders in the market



** High Temperature DENSITY **APPLICATIONS** Hard Heavy-duty sanding, best for flat surfaces or dimensions Medium Scuffing, shaping, sanding and finishing, for use on filler, primer, paint, clear coat, wood, plaster, composites and metal Soft Final sanding, to obtain the best finishes PK SIZES TYPE ART NO. QTY Soft 63642563534 1 125mm Medium (Suitable for Festool) 63642563533 1 Medium HT** (Compatible with most common brands such as Dynabrade, Rupes, except Festool) 66261067436 1 Soft 63642560605 1 Medium HT** (Suitable for Festool and Rupes) 63642585872 1 Medium HT** - Fixed screw (Compatible with most common brands such as Dynabrade, 150mm 63642582245 1 Rupes, except Festool. No Adapters & spacers) Hard 07660719198 1 Adapter for Rupes SK2 66261131280 1




MULTI-AIR INTERFACE PADS

| DIAMETER | ART NO. | ΡΚ QTY |
|----------|-------------|--------|
| 125 mm | 63642585864 | 16 |
| 150 mm | 07660719359 | 12 |



PAD SAVER

| ***** | | | |
|----------|--------------|-------------|--------|
| DIAMETER | TYPE / GRADE | ART NO. | ΡΚ QTY |
| 150 mm | Multi-Air | 69957328425 | 1 |
| 150 mm | 14+1 holes | 69957328430 | 1 |



BLUE FIRE H835 *+++++*

- Sharp Norzon grains cut through old paint layers, body filler, and smooth sharp edges with ease and the open coating helps to prevent clogging
- High-strength E-weight paper backing is tear resistant and significantly reduces common issues, such as curling and edge chipping
- A full resin bond system maintains grain adhesion, ensuring the grain stays intact for longer for maximum productivity for the life of the disc
- Self-grip backing facilitates quick and easy disc changing







| | | U | 1.1.1 | | | |
|------|--------------------|-------------------|--------------------|-------------------|-----------|--|
| GRIT | NO HOLES 150 mm | 7 HOLES 150 mm | 15 HOLES 150 mm | 8 HOLES 203 mm | PK QTY | |
| 40 | 69957390933 | 69957391250 | | 69957391263 | 25 | |
| 40 | | | 66254444904 | | 50 | |
| 60 | 69957390940 | 69957391255 | | 69957391268 | 25 | |
| 60 | | | 66254444905 | | 50 | |
| 80 | 69957391248 | 69957391256 | 66254444908 | 69957391269 | 50 | |
| 120 | 69957391249 | 69957391257 | | 69957391272 | 50 | |
| 120 | | | 66254444909 | | 100 | |

* Made-to-order



NORTON PRO PLUS A975 ++++

- Using a combination of SG and premium heat-treated aluminium oxide grains, Norton Pro Plus provides excellent cutting with a uniform scratch pattern on primer, paint, composites, marine gel coat, non-ferrous metals and ceramic coatings
- Thanks to the combination of premium grain, Pro Plus has the most aggressive yet cool cut with excellent wear resistance, lasting up to twice as long as conventional discs
- In P80 P120 discs, the backing is thicker for more aggressive use, P150 - P80 has a thinner paper backing for better flexibility in finer applications
- The No-Fil® coating resists loading to extend disc life when sanding dry or wet. Disc colour will not transfer to the surface of the working area





| GRIT | 7 HOLES 150 mm | 15 HOLES 150 mm | PK QTY | ΒΟΧ ΩΤΥ |
|------|-------------------|--------------------|--------|---------------|
| 80 | 63642527655 | 66254477881 | 100 | 400 |
| 120 | 63642527659 | 66254477879 | 100 | 400 |
| 150 | 63642527657 | 66254477882 | 100 | 400 |
| 180 | 63642527661 | 66254477883 | 100 | 400 |
| 220 | 63642527662* | 66254477884 | 100 | 400 |
| 240 | 63642527666* | 66254477885 | 100 | 400 |
| 280 | | 66254477886 | 100 | 400 |
| 320 | 63642527669 | 66254477887 | 100 | 400 |
| 400 | 63642527670* | 66254477888 | 100 | 400 |
| 500 | 66254476604 | 66254476601 | 100 | 400 |
| 600 | | 63642532659 | 100 | 400 |
| 800 | | 66254479091 | 100 | 400 |
| | | | | * Made-to-ord |

-

MOUNTING

For use with a 150mm Norton back-up pad on an orbital sander.



NORTON PRO PLUS SOFT TOUCH A975

- Premium, SG ceramic grain blended with heat-treated aluminium oxide grains provide excellent cutting action for a very high-level finish
- The foam backing is colour-coded to aid in quick product identification for each stage of sanding and increasing the quality of surface finish by conforming to curves, edges and contours
- Fibre-reinforced latex paper creates a flexible and tear-resistant backing
- No-Fil[®] coating is both water-based and pigment-free to significantly improve load resistance and eliminate the risk of colour transfer

MOUNTING: For use with a medium 150mm Norton self-grip back-up pad on an orbital sander



| | | | 15 HOLES | | |
|-----------|------|-------------------------------------------|--------------|--------|---------|
| COLOUR | GRIT | APPLICATION | 150 x 14 mm | PK QTY | BOX QTY |
| Salmon | 320 | Sanding polyurethane primer | 66261108763* | 20 | 80 |
| Yellow | 400 | Sanding polyurethane primer | 66261108817* | 20 | 80 |
| Blue Dark | 500 | Sanding polyurethane primer | 66261108819 | 20 | 80 |
| Blue | 800 | Cutting back lacquer before a flush joint | 66261108820* | 20 | 80 |
| White | 1000 | Retouching clear coat | 66261108822* | 20 | 80 |
| Green | 1500 | Before polishing and buffing | 66261110861* | 20 | 80 |

* Made-to-order



MOUNTING To be used on 76mm pad. Use interface pad with finer grits. See page 66.

NORTON PRO PLUS SMART REPAIR A975



- When an operation calls for more precision or is in a small area, the Norton Smart repair system offers a premium sanding solution in small disc size
- Using a combination of SG and premium heat-treated aluminium oxide grains, Norton Pro Plus provides excellent cutting performance
- The self-grip fixing system allows quick, easy disc changing, reducing downtime and increasing productivity
- Reinforced B-weight latex paper provides better tear resistance and flexibility

| GRIT | NO HOLES 76 mm | PK QTY | BOX QTY | | GRIT | NO HOLES 76 mm | PK QTY | BOX QTY |
|------|-------------------|-----------|------------|---|------|-------------------|-----------|------------|
| 80 | 63642575308 | 50 | 200 | | 320 | 63642575531 | 50 | 200 |
| 120 | 63642575521 | 50 | 200 | _ | 400 | 63642575532 | 50 | 200 |
| 150 | 63642575526 | 50 | 200 | | 500 | 63642575533 | 50 | 200 |
| 180 | 63642575527 | 50 | 200 | | 800 | 63642575534 | 50 | 200 |
| 220 | 63642575528 | 50 | 200 | | 1000 | 63642575535 | 50 | 200 |
| 240 | 63642575529 | 50 | 200 | | | | | |



NORTON PRO A275 /++++/



- Heat-treated high-performance aluminium oxide grain provides Norton Pro with a fast cut-rate and a consistent, uniform scratch pattern
- Discs are flexible and tear-resistant due to their fibre-reinforced latex paper backing, which is heavier in grits P80 to P120 for more aggressive applications and lighter weight in finer grits for more flexibility
- The No-Fil[®] layer is added to resist loading and is pigment-free, which eliminates the risk of colour transfer to the surface
- MOUNTING: Norton Pro discs are for use on orbital sanders with 150mm and 203mm back-up pads. For detailed information see page 66-67





| | | | 8 | | |
|---------|-------------------|--------------------|-------------------|--------------------|-------------------|
| GRIT | NO HOLES 76 mm | NO HOLES 150 mm | 7 HOLES 150 mm | 15 HOLES 150 mm | 8 HOLES 203 mm |
| 80 | 63642585133 | 63642585184 | 63642557950 | 66254405540 | 63642585236 |
| 100 | | 63642585186 | 63642586135 | 66254405542 | |
| 120 | 63642585145 | 63642569701 | 63642557954 | 66254405528 | 63642585243 |
| 150 | 63642585148 | 63642569702 | 63642586141 | 66254405530 | 63642585244 |
| 180 | 63642585150 | 63642585190 | 63642586142 | 66254405546 | 63642585245 |
| 220 | 63642585153 | 63642585194 | 63642586143 | 66254405548 | |
| 240 | 63642585156 | 63642585197 | 63642557955 | 66254405549 | 63642585248 |
| 280 | | 63642585199 | 63642586144 | 66254405550 | |
| 320 | 63642569699 | 63642569704 | 63642557959 | 66254405539 | 63642585250 |
| 360 | | 63642585205* | 63642586148 | 66254405551 | |
| 400 | 63642585169 | 63642585214 | 63642557962 | 66254405552 | 63642585252 |
| 500 | 69957391303 | 63642585217 | 63642586150 | 66254405553 | |
| 600 | | 63642585220 | 63642557964 | 66254405554 | |
| 800 | 63642585172 | 63642585223 | 63642584990 | 66254405555 | |
| 1000 | 63642585180 | | | | |
| PK QTY | 50 | 100 | 100 | 100 | 100 |
| BOX QTY | 100 | 100 | 400 | 400 | 100 |

MOUNTING

For use with 76mm, 150mm, and 203mm Norton back-up pad on an orbital machine







SOFT TOUCH

NORTON PRO SOFT TOUCH A275 ++++

- Soft-Touch discs have a colour-coded foam backing designed to make sanding curves and contours easy and product identification instant
- Premium, heat-treated aluminium oxide grain delivers a rapid cut rate and outstanding performance with a fluid and linear sanding result without cutting through to the paint layer
- The No-Fil® layer resists dust build-up on the disc, maintaining excellent cutting action throughout the disc life
- Fibre-reinforced latex paper backing makes discs tear-resistant and flexible, supporting applications from sanding to finishing

| COLOUR | GRIT | APPLICATION | 15 HOLES 150 x 14 mm | PK QTY | BOX QTY |
|-----------|------|-------------------------------------------|-------------------------|-----------|------------|
| Salmon | 320 | | 66623382800 | 20 | 80 |
| Yellow | 400 | Sanding polyurethane primer | 66623382802 | 20 | 80 |
| Blue dark | 500 | | 66623382803 | 20 | 80 |
| Turquoise | 600 | | 66623382804 | 20 | 80 |
| Turquoise | 800 | Cutting back lacquer before a flush joint | 66623382805 | 20 | 80 |
| White | 1000 | Retouching clear coat | 66623382806 | 20 | 80 |
| Green | 1500 | Before polishing & buffing | 66623382808 | 20 | 80 |

MOUNTING

For use with a medium 150mm Norton self-grip back-up pad on an orbital sander



NORTON PRO FILM Q275 /++++/

20000

- Flexible film backing is resistant to tearing and provides a consistent scratch pattern, which reduces rework
- No-Fil[®] layer on the abrasive prevents dust build-up during sanding for significantly longer disc life
- Heat-treated aluminium oxide grain for fast material removal and excellent performance on paint, varnish and fillers



| ACHINE ANDING |
|------------------|
| SA SA |

| GRIT | 15 HOLES 150 mm | ΡΚ QTY | BOX QTY | GRIT | 15 HOLES 150 mm | ΡΚ QTY | BOX QTY |
|------|--------------------|--------|---------|------|--------------------|--------|---------|
| 80 | 77696085879 | 100 | 400 | 400 | 77696088151 | 100 | 400 |
| 120 | 77696088028 | 100 | 400 | 500 | 77696088152 | 100 | 400 |
| 150 | 77696088145 | 100 | 400 | 600 | 77696088153 | 100 | 400 |
| 180 | 77696088146 | 100 | 400 | 800 | 77696088154 | 100 | 400 |
| 220 | 77696088147 | 100 | 400 | 1000 | 77696088155 | 100 | 400 |
| 240 | 77696088149 | 100 | 400 | 1200 | 77696088156 | 100 | 400 |
| 320 | 77696088150 | 100 | 400 | 1500 | 77696088388 | 100 | 400 |

MOUNTING

For use with a 150mm Norton self-grip back-up pad on an orbital sander





- With sharp aluminium oxide grains, Gold Reserve is ideal for feather edging, stripping old paint and dry sanding filler
- Durable latex paper backing supports tougher applications whilst maintaining flexibility and is resistant to tearing
- The No-Fil® water-based stearate layer prevents dust build-up on the disc, meaning it can be used for longer until being changed



| GRIT | 15 HOLES 150 mm | PK QTY | BOX QTY | GRIT | 15 HOLES 150 mm | PK QTY | BOX QTY |
|------|--------------------|--------|---------|------|--------------------|--------|---------|
| 80 | 66261097523 | 100 | 400 | 280 | 66261097537 | 100 | 400 |
| 120 | 66261097529 | 100 | 400 | 320 | 66261097538 | 100 | 400 |
| 150 | 66261097531 | 100 | 400 | 400 | 66261097539 | 100 | 400 |
| 180 | 66261097532 | 100 | 400 | 500 | 66261097540 | 100 | 400 |
| 220 | 66261097533 | 100 | 400 | 600 | 66261097542 | 100 | 400 |
| 240 | 66261097534 | 100 | 400 | 800 | 66261097543 | 100 | 400 |



NORTON A293 +++

00000

- No-Fil[®] stearate treatment on top of high-performance aluminium oxide abrasive reduces clogging and dust build-up in all sanding applications for a smooth finish
- Light and flexible paper backing provides a consistent scratch pattern, with a smooth surface finish in fine applications.
- Durable and performing disc for sanding applications on paint and solid surfaces

| GRIT | 15 HOLES 150 mm | PK QTY | BOX QTY | GRIT | 15 HOLES 150 mm | PK QTY | BOX QTY |
|------|--------------------|--------|---------|------|--------------------|--------|---------|
| 40 | 78072710207 | 100 | 400 | 240 | 78072710216 | 100 | 400 |
| 60 | 78072710208 | 100 | 400 | 280 | 78072710219 | 100 | 400 |
| 80 | 78072710209 | 100 | 400 | 320 | 78072710221 | 100 | 400 |
| 120 | 78072710197 | 100 | 400 | 400 | 78072710222 | 100 | 400 |
| 150 | 78072710210 | 100 | 400 | 500 | 78072710224 | 100 | 400 |
| 180 | 78072710211 | 100 | 400 | 600 | 78072710226 | 100 | 400 |
| 220 | 78072710212 | 100 | 400 | 800 | 78072710227 | 100 | 400 |



SELF-GRIP BACK-UP PAD

- Spindle mounted back-up pad
- Ideal for all self-grip discs

| DIAMETER | PERFORATIONS | TYPE | SOFT | MEDIUM | HARD | QTY |
|----------|-----------------------|------------|--------------|--------------|-------------|------------|
| | No perforations | 5/16" & M8 | | 66623338436 | | 1 |
| 150 mm | 6+1 holes | 5/16" & M8 | 66623338441* | 66623338445 | 66623338446 | 1 |
| 150 1111 | 8+1 holes | 5/16" & M8 | 66623338447* | 66623338448* | | 1 |
| | 15 holes | 5/16" & M8 | 66623338452 | 66623338450 | 66623338451 | 1 |
| 203 mm | 8 holes | M5 | | 69957371442 | | 3 |
| DIAMETER | TYPE | ART NO. | PK QTY | | * Mad | e-to-order |
| 150mm | Adapter for Rupes SK2 | 662611312 | 280 1 | | | |
| | | | | | | |



NORTON PRO SELF-GRIP FOAM INTERFACES

• Super soft interfaces with 10mm foam thickness for the best finish even on curved surfaces

| DIAMETER | PERFORATIONS | ART NO. | PK QTY |
|----------|-----------------|-------------|--------|
| 76 mm | No perforations | 69957394589 | 10 |
| 150 mm | 6+1 holes | 07660707383 | 10 |
| | 15 holes | 07660719360 | 10 |



NORTON SELF-GRIP DUO FOAM INTERFACES

• Soft flat interfaces for finishing operations to reduce the risk of scratches thanks to the natural rubber and the gripping system, which features the 'flat-top mushroom' shape

| PERFORATIONS | ART NO. | PK QTY |
|-----------------|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| No perforations | 63642567831 | 12 |
| No perforations | 63642567836* | 6 |
| 6 holes | 63642567837 | 6 |
| 14+1 holes | 63642567840 | 6 |
| | No perforations No perforations 6 holes | No perforations 63642567831 No perforations 63642567836* 6 holes 63642567837 |

* Made-to-order



DUAL ACTION SANDER PNEUMATIC DASP

- This sander is compact, lightweight, and ergonomically designed to minimise vibration and reduce hand and arm fatigue during extended use, enhancing control for more effective sanding
- Available in two rotational orbit sizes; 5mm for faster sanding and 2.5mm for an excellent finish
- Includes a 360° adjustable muffler-cap to reduce sharp noise and a metal-muffler inside to reduce oil accumulation, designed to ensure smooth running and extend machine life
- The included Multi-Air back-up pad, used in conjunction with the adjustable speed of 12,000 RPM, yield the best sanding results



| | | | | | | | 🕨 YouTube |
|---------|------------|------------|----------------|--------|-------------|---|------------------|
| MODEL | PAD SIZE | DIA. ORBIT | VACUUM | WEIGHT | ART NO. | | 112-22 10 |
| 150/5.0 | 6" / 152mm | 5 mm | Central vacuum | 750g | 78072723478 | _ | |
| 150/2.5 | 6" / 152mm | 2.5 mm | Central vacuum | 710g | 78072723484 | - | |
| | | | | | | - | |



NORTON VACUUM SYSTEM CV4E

- A reliable, mobile and effective vacuum, that can be used with or without power tools
- Powerful vacuum technology with automatic filter cleaning system ideal for moderate dust levels in bodyshops and workshops
- User-friendly control panel and NONSTOPVAC! system ensures constant vacuuming significantly reducing downtime and maintaining high suction performance
- The vacuum features a convenient accessory organisation system with holders, supports, and compartments, making it highly practical in day-today use

| DESCRIPTION | VOLUME | FILTER CLASS | DIMENSIONS | WEIGHT | ART NO. |
|-------------|--------|--------------------|-------------------|--------|-------------|
| CV4E 40:L | 40 L | L (low hazard) | 625 x 385 x 545mm | 21 kg | 78072755382 |
| CV4E 40:M | 40 L | M (medium hazard) | 625 x 385 x 545mm | 21 kg | 78072755386 |

PNEUMATIC MODULE KIT

- Allows the connection of pneumatic tools to the vacuum
- Easy to install directly under the control panel
- Use a co-axial pneumatic hose to complete the system

| | QTY IN | |
|----------------------|--------|-------------|
| DESCRIPTION | KIT | ART. NO. |
| Pneumatic module kit | 1 | 78072755387 |





ANTISTATIC CLEANER KIT

- Kit includes a floor brush, handle, crevice tool and a metal extension kit 0.5m (2 pieces)
- The antistatic accessories are designed to protect against any electric shock that may occur during use

| DESCRIPTION | QTY IN KIT | ART. NO. | |
|-----------------------------|---------------|-------------|--|
| Chrome extension tubes 0.5m | 2 | | |
| Transport handle | 1 | 78072756753 | |
| Dry floor tool | 1 | | |
| Vacuum crevice tool | 1 | | |
| | | | |



VACUUM SYSTEM ACCESSORIES

- Accessories for Norton Vacuum System CV4
- Suitable for electric and pneumatic option
- All hoses are suitable for most common vacuums
- Antistatic accessories protect against any static-shocks that may occur during use



| DESCRIPTION | APPLICATION | TYPE/DIMENSIONS | PK QTY | ART NO. |
|-------------------------|--------------------------------------|----------------------------------|-----------|-------------|
| Flat filter | For vacuum CV4E/P | Class L/M | 1 | 78072756714 |
| Fleece filter bags | For vacuum CV4E/P | | 10 | 78072756715 |
| PE bag | For vacuum CV4E/P | | 1 | 78072756716 |
| Transport handle kit | For vacuum CV4E/P | | 1 | 78072756754 |
| Box adapator kit | For vacuum CV4E/P | Suitable for most common systems | 2 | 78072756755 |
| Remote control kit | For vacuum CV4E/P | | 1 | 78072756756 |
| Aspiration hose | For vacuum, antistatic | Lenght: 5m, Dia: 29mm | 1 | 78072757323 |
| Aspiration hose | For vacuum, antistatic | Lenght: 7m, Dia: 29mm | 1 | 78072757449 |
| Aspiration hose | For vacuum, antistatic | Lenght: 10m, Dia: 29mm | 1 | 78072757450 |
| Co-axial pneumatic hose | For vacuum | Lenght: 5m, Dia: 29mm | 1 | 78072757452 |
| Co-axial pneumatic hose | For vacuum | Lenght: 7m, Dia: 29mm | 1 | 78072757454 |
| Co-axial pneumatic hose | For vacuum | Lenght: 10m, Dia: 29mm | 1 | 78072757455 |
| "Y" connector | For connecting two tools to a vacuum | Suitable for hoses Dia 29mm | 1 | 78072757457 |

DEFECT GUIDE COAT

- Quickly identifies pinholes and deep scratches in primer to ensure the total primed area is sanded prior to top coating
- Does not require masking and takes no time to dry
- Does not contain solvents and can be used for both wet and dry sanding

| VOLUME | ART NO. | PK QTY |
|--------|-------------|--------|
| 100g | 77696072696 | 6 |



ORGANISE YOUR WORKSPACE EFFECTIVELY



- 1x trolley
- 2x machine holder
- 1x phone holder

Other accessories are sold separately THE CYCLONIC DISPENSER IS SOLD SEPARATELY.

PLEASE REFER TO PAGE 53.



NEW NORTON WORKING STATION

- This is a versatile, double-sided work station designed for bodyshops to conveniently store products near the repair area
- Spacious storage shelves and drawers
- Durable metal construction
- Front wheels that swivel for easy manoeuvrability
- Compact dimensions and effortless assembly and disassembly
- Fully customisable design allowing the operator to have a setup that works for their needs
- Compatible with all Norton tools and abrasives, including Norton Vacuum System CV4E
- Capability for simultaneous use by two operators

| ART NO. | PK QTY |
|-------------|--------|
| 66254427951 | 1 |

NEW NORTON SMART STATION

- Compatible with Norton Vacuum System CV4E for less dust and a cleaner working environment
- Portable, featuring compact and durable construction
- Promotes increased operator mobility, reducing time spent searching for tools and supplies
- Highly customisable with a variety of complementary accessories
- Includes the exclusive Cyclonic Dispenser, offering a comprehensive sanding solution

| ART NO. | ΡΚ QΤΥ |
|-------------|--------|
| 66254427986 | 1 |

INCLUDES:


- 1 machine and 1 hose holder
- Fixing corners for Vacuum System CV4E
- Set of shelves
- Cyclonic Dispenser

Other accessories are sold separately



WORKING STATION & SMART STATION ACCESSORIES

| DF | SCRIPTION | ART NO. | WORKING STATION | SMART STATION |
|----|----------------------------------------|-------------|-----------------|---------------|
| 1 | Vertical panel | 66254427953 | | |
| 2 | Paper roller | 66254427966 | Ø | |
| 3 | Machine holder | 66254427968 | Ø | |
| 4 | Sanding block holder | 66254427971 | Ø | Ø |
| 5 | Tape holder (3 units) | 66254427972 | Ø | 0 |
| 6 | Spray holder | 66254427973 | Ø | |
| 7 | Mobile phone holder | 66254427977 | Ø | 0 |
| 8 | Waste bag holders | 66254427978 | Ø | |
| 9 | Set of four fixing holders to VAC CV4E | 66254434791 | | 0 |
| 10 | Set machine holder & hose holder | 66254435609 | 0 | 0 |
| 11 | Set of shelves | 63642598433 | 0 | Ø |



BODY SHOP TROLLEY

- A practical work station for use in a body shop to store products close to the repair area
- Metal trolley is portable for moving to different areas
- Three shelves are included for maximum product storage

| ART NO. | ΡΚ QTY | |
|-------------|--------|--|
| 66254425276 | 1 | |

THE CYCLONIC DISPENSER IS SOLD SEPARATELY. PLEASE REFER TO PAGE 53.



FINISHING

| ROTOLO FOAM | 7/ |
|------------------------------------|------|
| Norton Pro Plus | _ /4 |
| Norton MAX | |
| Norton Pro | _ |
| Gold Reserve | |
| BEARTEX NON-WOVEN | - 77 |
| Rotolo rolls | |
| BearTex hand pads | _ |
| BearTex discs | _ |
| Scuff Gel | _ |
| Back-up pads | |
| WATERPROOF SHEETS | - 80 |
| Waterproof sheets | |
| Sanding block for waterproof paper | |
| Rossette discs & blocks | |
| SANDING SPONGES | |
| Soft touch sanding sponges | 02 |

FINISHING

ROTOLO FOAM

Rotolo Foam pre-cut sheets are ideal for fine sanding on round edges, contours and curves, providing a smooth finish on primers and top coats. The secret of Rotolo Foam lies in the combination of premium abrasive sanding paper and special foam backing. Rotolo is pre-cut to guarantee a straight edge when a piece is torn and prevents scratches from an unevenly torn edge.



NORTON PRO PLUS A975 +++++

- The best of the best Norton SG ceramic grain combined with heattreated aluminium oxide gives an outstanding cut rate
- Fibre reinforced paper combined with flexible foam backing is ideal for use on round edges, contours and curves without breaking through the paint
- No-Fil[®] treatment prevents clogging, increasing performance and lifetime
- Units are packed in a handy dispenser box and have colour-coded labels that show the grit size for quick product selection and easy storage

| LABEL | GRIT | APPLICATION | 115mm x 25m | PK QTY | BOX QTY |
|---------------|------|-----------------------------------------------------------|-------------|-----------|------------|
| Apple Green | 120 | Conding of hody filler | 66261108905 | 1 | 2 |
| Orange | 150 | Sanding of body filler | 66261108906 | 1 | 2 |
| Purple | 180 | | 66261108984 | 1 | 2 |
| Red | 220 | Sanding of finishing filler | 66261108986 | 1 | 2 |
| Electric Blue | 240 | - | 66261108989 | 1 | 2 |
| Grey | 280 | Condina estado estis estado en desina en | 66261108990 | 1 | 2 |
| | 320 | Sanding cataphoretic coats and primer | 66261108991 | 1 | 2 |
| | 400 | | 66261108993 | 1 | 2 |
| Blue dark | 500 | Sanding polyurethane primer | 66261108994 | 1 | 2 |
| Fuchsia | 600 | - | 66261108995 | 1 | 2 |
| Turquoise | 800 | Cutting back lacquer before a flush joint | 66261108996 | 1 | 2 |
| White | 1000 | Retouching clear coat | 66261108997 | 1 | 2 |
| Green | 1500 | Before polishing & buffing | 66261108998 | 1 | 2 |



NORTON MAX A295 *++++*

- White aluminium oxide grain is specially selected for finer sanding and finishing applications due to the quality of the surface finish and the No-Fil® layer reduces clogging and improves product life
- A light and flexible paper backing gives a smooth and consistent finish throughout the whole process
- The flexible foam is ideal for use on round edges, contours and curves without breaking through the paint
- Units are packed in a handy dispenser box and have colour-coded labels that show the grit size for quick product selection and easy storage



| LABEL | GRIT | APPLICATION | 115mm x 25m | PK QTY | BOX QTY |
|---------------|------|-------------------------------------------|-------------|-----------|------------|
| Purple | 180 | Sanding of body filler | 66261032478 | 1 | 2 |
| Red | 220 | Sanding of finishing filler | 66261032479 | 1 | 2 |
| Electric Blue | 240 | Sanding of finishing filler | 63642533809 | 1 | 2 |
| Grey | 280 | Sanding cataphoretic coats and primer | 63642533808 | 1 | 2 |
| Salmon | 320 | Sanding cataphoretic coats and primer | 63642533807 | 1 | 2 |
| Yellow | 400 | Sanding polyurethane primer | 63642533806 | 1 | 2 |
| Blue dark | 500 | Sanding polyurethane primer | 63642533805 | 1 | 2 |
| Fuchsia | 600 | Sanding polyurethane primer | 63642534524 | 1 | 2 |
| Turquoise | 800 | Cutting back lacquer before a flush joint | 63642533848 | 1 | 2 |
| White | 1000 | Retouching clear coat | 63642557616 | 1 | 2 |
| White | 1000 | Retouching clear coat | 63642557616 | 1 | 2 |







NORTON PRO A275 ++++/

- Norton Pro A275 is a premium abrasive available in the full grit range for all common sanding and finishing applications
- Flexible foam backing is ideal for use on round edges, contours and curves without breaking through the paint
- Rolls are washable, meaning dust is removed and each section can be reused
- Rolls are packed in a handy dispenser box and have colour-coded • labels that show the grit size for quick product selection and easy storage

DOV

| LABEL | GRIT | APPLICATION | 115mm x 25m | PK QTY | BOX QTY |
|---------------|------|----------------------------------------------|-------------|-----------|------------|
| Apple Green | 120 | | 63642535316 | 1 | 2 |
| Orange | 150 | Sanding of body filler | 63642557584 | 1 | 2 |
| Purple | 180 | | 63642557599 | 1 | 2 |
| Red | 220 | Sanding of finishing | 63642557600 | 1 | 2 |
| Electric Blue | 240 | filler | 63642557602 | 1 | 2 |
| Grey | 280 | Sanding cataphoretic | 63642557604 | 1 | 2 |
| | 320 | coats and primer | 63642557606 | 1 | 2 |
| | 360 | | 63642557607 | 1 | 2 |
| | 400 | Sanding polyurethane | 63642557608 | 1 | 2 |
| Blue dark | 500 | primer | 63642557611 | 1 | 2 |
| Fuchsia | 600 | | 63642557612 | 1 | 2 |
| Turquoise | 800 | Cutting back lacquer before a flush joint | 63642557613 | 1 | 2 |
| White | 1000 | Retouching clear coat | 63642557616 | 1 | 2 |
| Green | 1500 | Before polishing & buffing | 63642557617 | 1 | 2 |





GOLD RESERVE A296

- With sharp aluminium oxide grains, Gold Reserve is available in coarser grades, ideal for feather edging, stripping old paint and dry sanding of filler by hand
- Durable B-weight latex paper backing supports tougher applications while maintaining flexibility and is resistant to tearing
- The No-Fil® water-based stearate layer prevents dust build-up on the disc, meaning it can be used for longer until being changed

| GRIT | APPLICATION | 115mm x 25m | PK QTY | BOX QTY |
|------|----------------------------------------------|-------------|-----------|------------|
| 240 | Sanding or finishing filler | 66261097596 | 1 | 2 |
| 320 | Sanding cataphoretic coats and primer | 66261097598 | 1 | 2 |
| 400 | | 66261097599 | 1 | 2 |
| 500 | Sanding polyurethane primer | 66261097600 | 1 | 2 |
| 600 | | 66261097601 | 1 | 2 |
| 800 | Cutting back lacquer before a flush joint | 66261097602 | 1 | 2 |

BEARTEX NON-WOVEN

BearTex is made from abrasive grain bonded to synthetic nylon to provide a pliable, long-lasting solution for cleaning, finishing and blending applications on curved or flat surfaces. The open mesh construction does not load with dust and shapes itself to contours for a uniform finish.

NON-WOVEN APPLICATION GUIDE



- BearTex is made from silicon carbide and aluminium oxide grains bonded to synthetic resins to provide a cushioned, 3D material which is pliable, long-lasting and provides an excellent finish without cutting through the undercoat/paint layer
- The open mesh construction is both flexible and waterproof, meaning that it will not load, shapes itself to the contours of any surface and is washable and reusable
- From cleaning to finishing, BearTex can be used in many bodyshop applications as it is available in pads, rolls, and discs in very fine to micro fine grades

| COLOUR | GRADE | GRIT GENERATED | FEATURES | APPLICATIONS |
|--------|--------------|-------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| RED | Very fine | P320/400 | Quick and aggressive cut. Tear-resistant. | Cutting back surface inside a brand new part. |
| GREY | Ultra fine | P600/800 | Quick cut, uniform finish. Incredibly flexible, yet tear-resistant. | Finishing a primer on sharp edges. Gentle cutting back before flush joint. Can be used with Scuff Gel. |
| GOLD | Micro fine | P1000 | Ideal for pearls and metallics. | Cleaning of clear coat or lacquer. Can be used with Scuff Gel. |
| WHITE | Non-abrasive | - | Use on all surfaces. | For final cleaning. |

ROTOLO BEARTEX PRE-CUT ROLLS

- Flexible, durable and perfect for use on contoured surfaces or hard-to-reach areas. Comes in a roll dispenser for easy storage and access to the product
- Available in silicon carbide (S) or aluminium oxide (A)

| COLOUR | GRADE | DIMENSION | ART. NO | PK QTY | | |
|-------------------|--------------|-------------|-------------|-----------|--|--|
| BEARTEX THIN FLEX | | | | | | |
| Red | Very fine A | 115mm x 25m | 77696042073 | 1 | | |
| Grey | Ultra fine S | 115mm x 25m | 77696042075 | 1 | | |
| BEARTEX STANDARD | | | | | | |
| Red | Very fine A | 115mm x 25m | 77696009598 | 1 | | |
| Grey | Ultra fine S | 115mm x 25m | 77696042071 | 1 | | |
| Gold | Micro fine A | 115mm x 25m | 66261124481 | 1 | | |
| White | Non-abrasive | 115mm x 25m | 66261124480 | 1 | | |
| | | | | | | |



UIISHING



CLEAN, BLEND AND FINISH ROLLS BEARTEX

- Flexible 3D non-woven hand pad material in roll form for hand and machine use
- Conforms to contours of work surface and provides a uniform finish
- Long life with resilient construction
- Ideal for blending and finishing applications on a variety of substrates

| COLOUR | GRADE | 100mm x 10m | 115mm x 10m | 115mm x 25m | 150mm x 10m | PK QTY |
|--------|--------------|-------------|-------------|-------------|-------------|-----------|
| Red | Very fine A | 66261018301 | | 63642587694 | | 2 |
| Grey | Ultra fine S | 66254470984 | | 66623301430 | | 2 |
| Maroon | Very Fine A | 63642571050 | 63642548949 | | 63642571056 | 2 |
| Green | Very Fine A | 63642571095 | 63642571200 | | 63642571201 | 2 |
| Grey | Ultra Fine S | 63642571202 | 63642549115 | | 63642571203 | 2 |



PRE-CUT HAND PADS BEARTEX

• Excellent flexibility, easy to tear, for dry or wet use. Combine the grey and gold pads with Norton Scuff Gel to clean, degrease and abrade in one step

| COLOUR | GRADE | 152 x 229mm | PK QTY |
|--------|--------------|-------------|-----------|
| Red | Very fine A | 66261058000 | 60 (20x3) |
| White | Non-abrasive | 66261058001 | 60 (20x3) |
| Grey | Ultra fine S | 66261058002 | 60 (20x3) |
| Gold | Micro fine A | 66261058005 | 30 (10x3) |



THIN-FLEX HAND PADS BEARTEX

• Thinner than standard BearTex, when greater precision is needed. Flexible and durable, for use on contoured surfaces and hard-toreach areas

| COLOUR GR | RADE | APPLICATION | 115 x 230mm | PK QTY |
|-----------|------|--------------------------------------------------------------------------------------|-------------|----------------|
| Red Vei | | For use before primer and on primer surfaces. Removes rust and cleans off metal. | 63642506166 | 100 (25x4) |
| White Ult | | Ideal for blending applications. Final scuffing of primer. Flexible. Non loading. | 63642506167 | 100 (25x4) |
| Gold Mi | | Use for fine finishing and clear blend prep. Ideal for pearls and metallics. | 66261113519 | 100 (10x10) |



PLAIN DISCS BEARTEX +++

• Three-dimensional discs that conform to panels and uneven surfaces thanks to the nylon fibre impregnated with abrasive

| COLOUR | GRADE | 150 mm | PK QTY |
|--------|--------------|-------------|-----------|
| Red | Very fine A | 63642557497 | 10 |
| Grey | Ultra fine S | 63642557498 | 10 |



- Contra

- Three-dimensional discs that conform to panels and uneven surfaces thanks to the nylon fibre impregnated with abrasive
- Hole configuration designed to extract dust from the surface for a cleaner working environment and better surface finish

| | • | | |
|--------|--------------|-------------------|-----------|
| COLOUR | GRADE | 7 HOLES 150 mm | PK QTY |
| Red | Very fine A | 69957383151 | 10 |
| Grey | Ultra fine S | 69957383158 | 10 |
| Gold | Micro fine A | 69957383162 | 10 |





SCUFF GEL

- Norton Scuff Gel is formulated to clean, degrease and abrade in one step
- Designed for use with grey and gold BearTex pads, using Scuff Gel gives better paint adhesion
- The water-based formula with very low in V.O.C (Volatile Organic Compounds, rinses easily and leaves no mess

| APPLICATIONS | ART NO. | WEIGHT | PK QTY |
|----------------------------------------|-------------|-----------|-----------|
| Use with grey and gold BearTex pads | 63642574653 | 700 grams | 6 bottles |

BACK-UP PADS

| DIAMETER | DENSITY | ART NO. | PK QTY |
|----------|---------|--------------|------------|
| 150 mm | Medium | 69957382843* | 1 |
| | | * Mad | e-to-order |




FINISHING

FINISHING

WATERPROOF SHEETS

When hand sanding in wet applications, waterproof sandpaper is the product of choice. Offering flexibility, cleaner sanding and a consistent finish; choose from silicon carbide or aluminium oxide abrasive.







BLACK ICE T417 ++++

- Premium silicon carbide grain delivers a fast initial cut and imparts a consistent finish across the surface
- Its synthetic bond provides flexibility to the sandpaper, preventing cracking or curling, making it particularly suitable for shaping vehicle contours
- Whether utilised with a sanding block on flat surfaces or by hand, this sandpaper's extended grit range, reaching higher grades, is perfect for achieving finer finishing results
- For tasks such as sanding polyurethane primer and smoothing old surfaces before spraying, it can be used wet. It is also effective for cutting back flush joints

| GRIT | 230 x 280mm | PK QTY | GRIT | 230 x 280mm | PK QTY |
|------|-------------|-----------|------|-------------|-----------|
| 80 | 66261021180 | 50 | 500 | 66261021192 | 50 |
| 120 | 66261021183 | 50 | 600 | 66261021193 | 50 |
| 180 | 66261021185 | 50 | 800 | 66261021195 | 50 |
| 220 | 66261021186 | 50 | 1000 | 66261021196 | 50 |
| 240 | 66261021187 | 50 | 1200 | 66261021197 | 50 |
| 280 | 66261021188 | 50 | 1500 | 63642534713 | 50 |
| 320 | 66261021189 | 50 | 2000 | 63642534719 | 50 |
| 360 | 66261021190 | 50 | 2500 | 63642565497 | 50 |
| | | | | | |

SANDING BLOCK FOR WATERPROOF PAPER

70 x 120mm 07660717789

PK QTY

12





NEW NORTON T419 /++++/

- Improved product design and premium silicon carbide grain delivers a fast initial cut and imparts a consistent finish across the surface
- The synthetic bond combined with blue latex paper adds extra flexibility to the sandpaper and prevents cracking or curling, making it an ideal choice for sanding contours
- Higher grits are ideal for finer finishing applications
- Use with a sanding block on flat surfaces or by hand
- Use wet for sanding polyurethane primer and cutting back an old surface before spraying, can also be used for cutting back flush joints

| GRIT | 230 x 280 mm | PK QTY | BOX QTY |
|------|--------------|-----------|------------|
| 80 | 78072771886 | 50 | 200 |
| 120 | 78072771890 | 50 | 200 |
| 180 | 78072771895 | 50 | 200 |
| 240 | 69957365874 | 50 | 200 |
| 320 | 69957365876 | 50 | 200 |
| 400 | 69957365878 | 50 | 200 |
| 500 | 69957365879 | 50 | 200 |
| 600 | 69957365880 | 50 | 200 |
| 800 | 69957365881 | 50 | 200 |
| 1000 | 69957365868 | 50 | 200 |
| 1200 | 69957365870 | 50 | 200 |

NORTON T489 /++++/

- Sharp silicon carbide grain cuts through rust and corrosion fast
- Flexible backing conforms to curves and contours, making T489 ideal for use on panels, wings, wheel arches and bumpers
- Can be used on lacquer, paint, metal, glass and composites
- Can be used wet or dry

| GRIT | 230 x 280mm | PK QTY | GRIT | 230 x 280mm | PK QTY |
|------|-------------|-----------|------|-------------|-----------|
| 60 | 63642532956 | 25 | 320 | 63642532995 | 50 |
| 80 | 63642532988 | 50 | 360 | 63642532996 | 50 |
| 100 | 63642532989 | 50 | 400 | 63642532997 | 50 |
| 120 | 63642532990 | 50 | 500 | 63642532998 | 50 |
| 150 | 63642532991 | 50 | 600 | 63642532999 | 50 |
| 180 | 63642532957 | 50 | 800 | 63642533000 | 50 |
| 220 | 63642532992 | 50 | 1000 | 63642533001 | 50 |
| 240 | 63642532993 | 50 | 1200 | 63642533002 | 50 |
| 280 | 63642532994 | 50 | | | |



FINISHING

FINISHING

SANDING SPONGES

Available in various grades tailored to accommodate a wide array of applications, all aimed at achieving a flawless finish and end result.



SOFT TOUCH SANDING SPONGES

- Thanks to the soft foam sponge backing, these sponges conform to the most complex shapes
- They generate a finer finish than conventional coated abrasives and when used wet, have a very long life

| GRADE | GRIT | APPLICATION | 140 x 115 x 6mm | ΡΚ QTY |
|------------|------|-------------------------------------------------------------|-----------------|--------|
| Medium | 60 | Scuffing, shaping filler | 63642550599 | 20 |
| Fine | 100 | Feather edging, scuffing primer & new parts before painting | 63642550601 | 20 |
| Super fine | 180 | Preparing panel for base coat | 63642550602 | 20 |
| Ultra fine | 220 | Sanding base coat, removing clear coat defects | 63642550603 | 20 |
| Micro fine | 280 | Clear coat sanding, removing minor defects | 63642550604 | 20 |

MASKING SOLUTIONS

| MASKING TAPES Gold tape | 84 |
|-----------------------------------|----|
| Challenger tape | |
| Masking tape | |
| Premium perforated tape | |
| Foam tape | |
| Fine line tape | |
| Double-sided attachment foam tape | |
| Rubber cleaning wheel | |
| MASKING FILM | 00 |
| Plastifilm | 07 |
| Accessories | |
| KRAFT PAPER | 01 |
| Premium kraft paper | 71 |

MASKING SOLUTIONS

MASKING TAPES

Norton offers a range of masking tapes suitable for several bodyshop applications. All tapes readily conform to contours and adhere to most surfaces and irregular shapes. Our masking tapes are also resistant to a broad range of temperatures.



ORANGE TAPE ++++

- Professional masking tape, excellent for curves, contours and irregular surfaces
- Excellent adhesion to all surface types (paints, plastic films etc.) thanks to the solvent-based rubber adhesive, which offers good stretchability
- Resists baking temperatures up to 120°C for 30 minutes or 90°C for 1 hour
- UV protection withstands indoor and outdoor use for three days without leaving any residue on the surface

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 18mm x 55m | 78072709627 | 48 |
| 24mm x 55m | 78072709628 | 36 |
| 36mm x 55m | 78072709629 | 24 |
| 48mm x 55m | 78072709630 | 20 |



GOLD TAPE ++++

- Gold tape is designed for fine-line paint masking on many substrates
- Resists baking temperatures of up to 120°C for one hour without leaving residue on the surface
- Thin and resistant (rice) paper tape will not peel paint off when removed and provides excellent masking line sharpness

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 19mm x 50m | 66261067434 | 24 |
| 25mm x 50m | 66254490982 | 36 |
| 38mm x 50m | 66261067435 | 12 |
| 50mm x 50m | 66254490986 | 18 |



CHALLENGER TAPE ++++

- Excellent resistance to paint, solvents, lacquer thinners, Challenger Tape shows outstanding tape-to-tape adhesion
- Saturated semi-crepe paper-based masking tape makes Challenger Tape particularly suited to oven baking painting operations up to 100°C for 30 minutes
- Optimised for most surfaces and well suited to both metallic and plastic alike

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 18mm x 45m | 66261133208 | 48 |
| 24mm x 45m | 66261133211 | 36 |
| 36mm x 45m | 66261133214 | 24 |
| 48mm x 45m | 66261133216 | 18 |

PREMIUM MASKING TAPE +++++

- For demanding applications, contours and irregular surfaces, Norton premium tape does not bleed through, seep or leave residue when removed
- Excellent adhesion on all surface types thanks to the rubber solvent-based adhesive, which resists baking temperatures of up to 100°C for 30 minutes
- Compatible with most common paints and lacquers used in the bodyshop



| DIMENSIONS | ART NO. | ΡΚ QTY | BOX/PALLET |
|------------|-------------|--------|------------|
| 19mm x 50m | 69957394601 | 48 | 48 |
| 25mm x 50m | 69957394602 | 36 | 48 |
| 30mm x 50m | 66261193492 | 32 | 32 |
| 38mm x 50m | 69957394603 | 24 | 48 |
| 50mm x 50m | 69957394604 | 24 | 48 |

NEW QUALITY TAPE /++++/

- Resists temperatures up to 100°C for 30 minutes
- Excellent edge definition, with natural rubber adhesive for immediate adhesion
- Leaves no residue upon removal
- Not UV resistant, not suitable for IR drying

| DIMENSIONS | ART NO. | ΡΚ QTY | BOX/PALLET |
|------------|-------------|--------|------------|
| 18mm x 50m | 78072760581 | 48 | 48 |
| 24mm x 50m | 78072760587 | 36 | 50 |
| 30mm x 50m | 78072760598 | 32 | 20 |
| 36mm x 50m | 78072760600 | 24 | 48 |
| 48mm x 50m | 78072760601 | 24 | 42 |



MASKING SOLUTIONS



MEDIUM MASKING TAPE

- Ideal for use in oven dry cycles with resistance up to 80°C
- Easy to remove without tearing and will not leave any residue on the surface
- Highly flexible with a good level of adhesion, which easily conforms to contours or irregular shapes and surfaces
- Can be used universally as the tape is compatible with the most common types of paints and lacquers

| DIMENSIONS | ART NO. | ΡΚ QTY | BOX/PALLET |
|------------|-------------|--------|------------|
| 19mm x 50m | 69957394605 | 48 | 48 |
| 25mm x 50m | 69957394609 | 36 | 48 |
| 38mm x 50m | 69957394611 | 24 | 48 |
| 50mm x 50m | 69957394614 | 24 | 48 |





PREMIUM PERFORATED TRIM TAPE

- For protecting rubber trims and body side mouldings during spraying
- The tape is pre-perforated for easy tear-off and is flexible to follow contours and tight curves
- Only one size and thickness: plastic strip fits all types of rubber trim
- High-quality adhesive with no residue upon removal

| DIMENSIONS | ART NO. | ΡΚ QTY |
|------------|-------------|--------|
| 50mm x 10m | 66261194743 | 10 |

PREMIUM FOAM TAPE ++++

- With highly absorbent foam to avoid leaks or paint runs, this foam tape is one continuous length which fits all gaps without rolling and will not distort when torn
- Recessed adhesive reduces defects or rework after spraying
- Can be used on fixed or moving parts to ensure a smooth paint edge
- Use in all car door apertures before spraying

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 20mm x 50m | 66254470746 | 1 |



STANDARD FOAM TAPE

 Recessed adhesive causes no paint edge or rubbing down, and provides reliable protection of painted edges quickly, and is easy to apply

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 13mm x 50m | 66254470735 | 1 |
| 19mm x 35m | 66254470744 | 1 |



POLYETHYLENE TAPE - 357

- Excellent adhesion to all surfaces for edge protection and wrapping
- Water and heat resistant

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 50mm x 50m | 07660717720 | 24 |

FINE LINE TAPE ++++

- Used for the demarcation of the most delicate paintwork, Fine Line Tape conforms easily to the tightest contours without wrinkling
- Vinyl backing does not leave adhesive residue when the tape is removed, even after baking at 150°C for 30 minutes
- 0.13mm thickness allows exact demarcation of the area to be painted
- Elongation of 150% provides excellent flexibility

| DIMENSIONS | ART NO. | ΡΚ QTY |
|------------|-------------|--------|
| 3mm x 55m | 66261194993 | 10 |
| 6mm x 55m | 66261194994 | 10 |
| 9mm x 55m | 66261194995 | 10 |
| 12mm x 55m | 66261194996 | 10 |
| 19mm x 55m | 66261194997 | 10 |

DOUBLE-SIDED ATTACHMENT FOAM TAPE #++++

- High-density foam tape is coated with high-strength acrylic adhesive on both sides, with a red polyethylene release liner, for bonding medium to large mouldings and accessories
- High-strength acrylic adhesive provides superior adhesion to plastics, metal, glass, and painted vehicle surfaces
- Used for many applications including attaching body side mouldings, cladding, door edges, emblems, fascia rub strips, garnish mouldings, interior trim panels, rocker panel mouldings and pillar covers

| DIMENSIONS | ART NO. | ΡΚ QTY |
|--------------------|-------------|--------|
| 6mm x 18m x 1.1mm | 63642505620 | 12 |
| 12mm x 18m x 1.1mm | 63642505621 | 12 |
| 22mm x 18m x 1.1mm | 63642505622 | 12 |







MASKING SOLUTIONS



RUBBER CLEANING WHEEL

- For pinstripe and adhesive tape removal without surface damage
- Specially designed with a ventilated structure, which helps to prevent meltdown or marking of the paint coating

| DESCRIPTION | DIMENSION | ART NO. | PK QTY |
|----------------|----------------|-------------|-----------|
| Cleaning Wheel | 100 x 15 x 6mm | 07660707987 | 8 |
| Spindle | 6mm | 07660718162 | 8 |

MASKING FILM

Norton Plastifilm provides the perfect solution for protecting car bodywork when spraying primer, paint or varnish. Available in three qualities: Standard, Premium and Ultra.

PLASTIFILM ULTRA +++++

- Made from a tough, water-resistant, and tear-resistant highdensity polyethylene+ prevents sweating and leaves no marks when used on damp cars
- Impregnated with an anti-paint-flaking treatment for excellent paint absorption and no bleed-through of water/solvent-based products
- Heat resistant up to 110°C, making it safe to use in the spray booth
- The material is also fully recyclable

| DIMENSIONS | ART NO. | ΡΚ QTY |
|------------|-------------|--------|
| 4m x 150m | 63642504273 | 1 |
| 5m x 120m | 63642504393 | 1 |
| 6m x 100m | 63642504396 | 1 |

PLASTIFILM PREMIUM

- High-density polyethylene resistant to water and solvent-based paint
- Heat resistant up to 110°C, making it safe to use in the spray booth and infra-red drying
- Static treatment applied to the film means it moulds instantly to the car for faster throughput with better precision and saving time
- Corona treatment prevents imprinting and marking on damp vehicles and eliminates humidity between the film and coating
- The thickness of Plastifilm Premium is 11 microns

| DIMENSIONS | ART NO. | ΡΚ QTY |
|------------|-------------|--------|
| 4m x 150m | 66623341457 | 1 |
| 5m x 120m | 66623341458 | 1 |







MASKING SOLUTIONS





PLASTIFILM STANDARD +++

- Made from transparent polyethylene, which can be easily trimmed to size and gives excellent visibility throughout the process
- Closed surface structure prevents paint leaking through and avoids the requirement for rework
- Can be compressed to minimum dimensions, making it easy to store and producing less waste overall
- The thickness of Plastifilm Standard is 9 microns

| DIMENSIONS | ART NO. | PK QTY |
|------------|-------------|--------|
| 4m x 150m | 66623341451 | 1 |
| 4m x 300m | 66623341454 | 1 |
| 5m x 120m | 66623341455 | 1 |

ACCESSORIES

| DESCRIPTION | ART No. | PK QTY |
|--------------------------|-------------|-----------|
| Dispenser for Plastifilm | 66623341459 | 1 |
| Cutter for Plastifilm | 07660708055 | 50 |





KRAFT PAPER

Norton Kraft paper is ideal for masking panel sections and parts before painting. It's thickness (50g/m²) means no paint will leak through whilst still easy to cut to size.

PREMIUM KRAFT PAPER #++++

- Thick paper prevents paint from leaking through
- Can be used for water and solvent-based paints
- Recycled paper for a more environmentally friendly solution

| DIMENSIONS | ART NO. | ΡΚ QTY |
|---------------|--------------|--------|
| 200mm x 300m | 66261133230 | 1 |
| 400mm x 300m | 66261127558 | 1 |
| 450mm x 300m | 66261133231 | 1 |
| 600mm x 300m | 66261133232 | 1 |
| 800mm x 300m | 66261133233 | 1 |
| 900mm x 300m | 66261127561 | 1 |
| 1000mm x 300m | 66261133304* | 1 |
| 1200mm x 300m | 66261127562 | 1 |
| 1500mm x 300m | 66261133306 | 1 |
| | | |

* Made-to-order



NORTON PAINT SYSTEM

IMPROVED VERSION

| Disposable kits | 0/ |
|-------------------|----|
| Refill kits | 74 |
| Reusable hard cup | |
| Starter kit | |
| Mixing cups | |
| Paint strainer | |
| Accessories | |
| Dispensers | |
| Adapters | |

VORT

NORTON PAINT SYSTEM

NORTON PAINT SYSTEM

The most effective and productive solution for preparing, mixing and spraying paints, the Norton Paint System provides a faster and cleaner solution and saves on cleaning time and solvent usage, allowing the paint to be stored and reused.

The Norton Paint System also enables the operator to paint in all positions, without any risk of the paint leaking.

The easy-to-assemble system ensures a consistent spray pattern, convenient storage of paint as well as easy and clean disposal of the entire unit.

A complete range of products and accessories are also available.



DISPOSABLE KIT

- Two different kits are available with different mesh weights built in to the filter inside the lids: 190 μ , 125 μ and 80 μ mesh
- Refer to the paint manufacturer's recommendation for the correct filter mesh. Each kit comes complete with lids with membranes, liners, rings, plugs and a mixing bar

| VOLUME (ml) | FILTER 80µ | FILTER 125µ | FILTER 190µ | ΡΚ QTY |
|----------------|-------------|-------------|-------------|--------|
| 250 | | 63642504727 | 63642504734 | 48 |
| 750 | 63642504739 | 63642504742 | 63642504744 | 48 |



REPLACEMENT FILTERS

| VOLUME (ml) | FILTER 80µ | FILTER 125µ | FILTER 190µ | PK QTY |
|----------------|--------------|--------------|--------------|--------|
| 250 | · | 66261103841* | 66261103842* | 24 |
| 750 | 66261112807* | 63642504747 | 63642504748* | 24 |

* Made-to-order



• The reusable mixing cup has pre-printed mixing ratio scales for greater convenience

| VOLUME (ml) | ART NO. | PK QTY |
|----------------|-------------|-----------|
| 250 | 07660721650 | 8 |
| 750 | 07660721651 | 8 |



STARTER KIT

• An ideal starter kit to introduce the use of Norton Paint System complete with 1 Hard Cup, 12 Lids, 12 Liners, 12 Rings, 12 Caps, 4 Paint Strainers and 1 Mixing bar (adapter not included)

| VOLUME (ml) | FILTER 125µ | PK QTY |
|----------------|----------------|--------|
| 750 | 66261136686* | 1 |
| | * 14 | |

* Made-to-order



MIXING CUPS

- Disposable plastic mixing cups for paint preparation and storage
- Printed with seven different mixing ratios for accurate measuring, and base feet which protect against cold transfer during mixing

C17E

| DESCRIPTION | SIZE (ml) | ART NO. | PK QTY | BOX QTY |
|---------------------------|--------------|-------------|--------|---------|
| Mixing cup | 400 | 66261140644 | 25 | 200 |
| Lid for 400ml mixing cup | | 66261140652 | 50 | 400 |
| Mixing cup | 650 | 66261140653 | 25 | 200 |
| Lid for 650ml mixing cup | | 66261140655 | 50 | 400 |
| Mixing cup | 1300 | 66261140659 | 25 | 200 |
| Lid for 1300ml mixing cup | | 66261140665 | 50 | 400 |
| Mixing cup | 2240 | 66261140668 | 25 | 100 |
| Lid for 2240ml mixing cup | | 66261140670 | 50 | 200 |



www.nortonabrasives.com



PAINT STRAINER

- Disposable paint-strainer, which filter paint before spraying
- High quality paper and mesh, gives the highest purity in the preparation of water-based, basecoat and clear-coat paints

| DESCRIPTION | BLUE FILTER 125µ | WHITE FILTER 190µ | PK QTY |
|----------------|------------------|-------------------|-------------|
| Paint Strainer | 63642530324 | 63642530358 | 4 x 250 pcs |



ACCESSORIES

| DESCRIPTION | SIZE | ART NO. | PK QTY |
|---------------------------------|------|--------------|----------------|
| Cleaning brush for NPS adapters | | 63642506317* | 6 |
| Gun & adapter wash attachment | | 63642506281* | 4 |
| Mixing bar | | 66254405711 | 250 |
| | М | 66254428976 | 10 |
| Painting Overall | L | 66254428977 | 10 |
| | XL | 66254428978 | 10 |
| | | | * Made-to-orde |



DISPENSERS

- Suitable for storage of liners and rings
- Available in small and medium/large size

| DESCRIPTION | SIZE | ART NO. | QTY PER DISPENSER | BOX QTY |
|---------------------------|----------------|--------------|---------------------------------------------------------------|------------|
| Liner dispenser | Small | 07660721654* | 50 liners | 1 |
| Liner dispenser | Medium / Large | 07660721655* | 50 liners | 1 |
| Lid and ring dispenser | All Sizes | 07660721656 | Holds 25 M/L lids or rings or 50 small lids or rings | 1 |

* Made-to-order

ADAPTER MITH & MEMBRANE

The new actuator inside the adapter, has been specially designed to pierce the membrane inside the lid, allowing the aint to flow through when the cup is attached to the spray gun.



ADAPTERS









• The new improved Norton Paint System can only be used with the new adapter series A.1

Adapter 2A

Adapter 5A

Adapter 9A

Quick Connect (QCC)

| BRAND | MODELS | | ADAPTER | ART NO. | PK QT\ |
|-----------|------------------------------------------------------------------------------------------------------------------|------|----------------------------------------|-------------|-----------|
| Accuspray | lssac | 7A | 3/8 Female, 18 Thread (BSP) | - | 4 |
| | 10, 12s, 19, 19c | 18A | 3/8 Female, 18 Thread (NSP) | - | 4 |
| | PerfoMax 05-300 mini | 21A | 14mm Female, 1,0mm Thread | - | 4 |
| Airgunsa | AZ3, AZ5, AZ30 HTE, AZ40 HTE | 6A | 1/4 Male, 19 Thread (BSP) | 7660721661 | 4 |
| Asturo | OM Green | 6A | 1/4 Male, 19 Thread (BSP) | 7660721661 | 4 |
| | EC0/SSP | 18A | 3/8 Female, 18 Thread (NSP) | - | 4 |
| Binks | Mach 1, 1SL, 95, 95SL, 95SLV, M.Featherlite, | 18A | 3/8 Female, 18 Thread (NSP) | - | 4 |
| | 2001, 2001SS, 2001V, Model 7, SV-100 Siphon | 18A | 3/8 Female, 18 Thread (NSP) | - | 4 |
| DeVilbiss | PRI, GTI, GTI Pro, GFG, GFV,GFHV 510, FLG4 | 15A | 3/8 Male, 19 Thread (BSP) | 7660721669 | 4 |
| | SRI Minigun | 14A | 7/16 Male, 14 Thread (UNC) | - | 4 |
| | TGHV-635, JGX-501, 502, FUN Gravity | 10A | Elbow Swive Nut 1/4 Fe19 Thread (BSP | - | 4 |
| | 506, 507, 510, EXL 520S, FLG 606, 626, 693, 694, VTX | 18A | 3/8 Female, 18 Thread (NSP) | - | 4 |
| | EGA-503 Mini Siphon Feed, EGHV 531 Mini | 23A | 1/4 Female, 1/8 Thread (NPS) | - | 4 |
| | FUN Siphon | 25A | 1/4 Female, 19 Thread (BSP) | - | 4 |
| Eminent | E13 | 6A | 1/4 Male, 19 Thread (BSP) | 7660721661 | 4 |
| Graco | 600 Side Cup Mount | 10A | Elbow Swive Nut 1/4 Fe19 Thread (BSP) | - | 4 |
| IWATA | W 400, WR 400, LPA 94, VXL Primer Gun, LPH 400, LPH 440 | 2A | 16mm Female, 1,5mm Thread | 7660721658 | 4 |
| | W300, LPH300 | 6A | 1/4 Male, 19 Thread (BSP) | 7660721661 | L |
| | Supernova WS400, LS400 | 43A | 1/4 Male, 19 Thread | 7660721882 | Z |
| | LPH-80 Mini Spray Gun | 31A | 1/8 Male 28 Thread (BSP) | 7660721883 | Z |
| | LPH-50 Mini, LPH-100, W-100G, RG3L, W-71 | 10A | Elbow Swive Nut 1/4, Fe19 Thread (BSP) | - | L |
| | Mini Siphon Feed Guns, Europe | 17A | 1/4 Female, 19Thread (BSP) | - | 4 |
| | W-200 Siphon, LPSI, W101 Siphon, W200 Siphon | 19A | 3/8 Female, 19 Thread | - | L |
| | W-100, Siphon | 25A | 1/4 Female, 19 Thread (BSP) | - | 4 |
| Kremlin | M 21 G | 6A | 1/4 Male, 19 Thread (BSP) | 7660721661 | 4 |
| Sagola | 475 Mini-Gun | 12A | 10mm Male, 1,0mm Thread | 7660721667 | L |
| | 403 G, 433 G, 434 G, 444 G, 450 G, 4100 G, 4200 G, 4300 | 5A | 12mm Male, 1,5mm Thread | 7660721660 | 4 |
| | 4400 Xtreme, 4500 Xtreme | 32A | 18mm x 1,5mm Female Thread | - | 4 |
| SATA | SATAjet 2000 HVLP w/o QCC, SATAjet RP w/o QCC, SATA LM 2000 HVLP/RRP, SATA KLC HVLP/RRP, KLC P, SATAjet 90 | 9A | 16mm Male, 1,5mm Thread | 7660721664 | 4 |
| | SATA Jet 3000/4000/5000 | 40A | 12mm Male, 1,5mm Thread | 66261110559 | 4 |
| | SATAjet B NR 92,NR 95 HVLP | 2A | 16mm Female, 1,5mm Thread | 7660721658 | Z |
| | SATA LM B 92 | 5A | 12mm Male, 1,5mm Thread | 7660721660 | L |
| | SATA Mini-Jet 1, 2, 3 | 12A | 10mm Male, 1,0mm Thread | 7660721667 | L |
| Sharpe | GT1,Platinum, Titanium, Cobalt, SGF 98 | 11A | Male 3/8 Net.18 (NPS) | - | L |
| | MFG, MPF Mini-Gun HVLP | 20A | 1/8 Male, 27 Thread | - | L |
| Snap-On | BF515 R-Angle Mini | 24A | El Sw Nut, 1/4Fe, 18 Thread | - | L |
| Tekna | Tekna Cooper, Prolite, Quick Clean | 15A | 3/8 Male, 18 Thread (NSP) | 7660721669 | 1 |
| Walcom | FX GEO, FX HVLP | 8A | 12mm Male, 1,0mm Thread | 7660721663 | |
| | Touch-up STM | 22 A | 8mm Male, 0,75mm Thread | - | L |
| | Suction gun | 16A | 3/8 Female, 19 Thread (BSP) | - | L |

MICRO FINISHING

| NORTON ICE RANGE | 100 |
|-------------------------|--------------|
| Discs | <u> </u> |
| Foam interfaces | |
| Rossette discs & blocks | |
| Norton Ice starter kit | |
| LIQUID ICE | — 105 |
| Liquid Ice Compounds | 105 |
| POLISHING HEADS | — 107 |
| Foam heads & lambswool | |
| Back-up pads | |
| CLOTHS & TACK RAGS | — 108 |
| Micro fibre cloths | |
| Tack rags | |
| CLAY RANGE | <u> </u> |
| Clay discs | |
| Clay glove | |
| Clay starter kit | |
| HEADLIGHT KIT | 110 |
| Headlight repair kit | |

MICROFINISHING

NORTON ICE RANGE

The Ice range is a complete solution of abrasive discs, compounds, polishing heads, cloths and accessories designed to provide the ultimate finish. Combine Liquid Ice polishing compounds with Pure Ice Q175 or Norton Ice discs to remove defects quicker, more effectively and thereby reduce polishing time.





PURE ICE FILM DISCS Q175



- The ultra-thin film backing provides multiple benefits, including excellent flexibility, allowing conformity to contours in the car body and it helps the discs to remain flat and prevent curling
- Patented resin technology promotes excellent grain adhesion that keeps the disc effective for longer and imparts a consistent finish that's easier to buff out
- Water-based No-Fil[®] stearate coating resists loading, eliminates pigtails and further extends the life of the product
- Colour-coded grits provide an at-a-glance identification of the correct product across all hole configurations, including the dust reducing Multi-Air disc

| COLOUR | GRIT | NO HOLES 76 mm | PK QTY | BOX QTY | 7 HOLES 150 mm | 15 HOLES 150 mm | MULTI-AIR 150 mm | PK QTY | BOX QTY |
|--------|------|-------------------|-----------|------------|-------------------|--------------------|---------------------|-----------|------------|
| Black | 800 | | 50 | 300 | 66261110841* | 66261110837 | | 50 | 300 |
| Red | 1000 | 66261110859 | 50 | 100 | 66261110852* | 66261110838 | 66261113819 | 50 | 300 |
| Green | 1200 | | 50 | 300 | 66261110853* | 66261110839 | | 50 | 300 |
| Blue | 1500 | 66261110860 | 50 | 100 | 66261110854* | 66261110840 | 66261113821 | 50 | 300 |

MOUNTING

For better results, use with the Norton Self-Grip Duo Foam Interfaces.

* Made-to-order



NEW SUPERFLEXIBLE Q775 FILM +++++

- The resilient and highly flexible film backing conforms exceptionally well to surfaces
- Offers superior fine-grit abrasion for achieving an outstanding finish
- Maintains a consistent scratch pattern and ensures an even finish, making blending effortless

| | | | 15 HOLES | | |
|-----------|------|-------------|-------------|--------|---------|
| COLOUR | GRIT | 76mm | 150 mm | ΡΚ QTY | BOX QTY |
| Turquoise | 600 | 77696083755 | 78072723111 | 25 | 100 |
| | 800 | 77696083757 | 78072723112 | 25 | 100 |
| Amber | 1200 | 77696083761 | 78072723115 | 25 | 100 |
| | 1500 | 77696083762 | 78072723116 | 25 | 100 |
| Jade | 2000 | 77696083763 | 78072723117 | 25 | 100 |
| Meteorite | 3000 | 77696083764 | 78072723118 | 25 | 100 |





MOUNTING

To be used with pad Page 102

NEW SUPERFLEXIBLE Q775 FILM #++++

- The resilient and highly flexible film backing conforms exceptionally well to surfaces
- Offers superior fine-grit abrasion for achieving an outstanding finish
- Maintains a consistent scratch pattern and ensures an even finish, making blending effortless



| COLOUR | Grit | 170 x 130mm | ΡΚ ΩΤΥ | ΒΟΧ ΩΤΥ |
|-----------|------|-------------|--------|---------|
| COLOOK | GIIL | | | BUX GIT |
| Turquoise | 600 | 66623390551 | 25 | 100 |
| Citrine | 800 | 66623390552 | 25 | 100 |
| Amber | 1200 | 66623390554 | 25 | 100 |
| Rose | 1500 | 66623390555 | 25 | 100 |
| Jade | 2000 | 78072723119 | 25 | 100 |
| Meteorite | 3000 | 78072723120 | 25 | 100 |



- Super soft foam sanding pad moulds to curves and contours of all surfaces
- Norgrip-Duo attaches to abrasive quickly and easily for quick product change over
- Helps to provide an even finish and prevent scratches in the surface

| ΡΚ QTY |
|--------|
| 8 |
| |



MICROFINISHING

DUAL SANDING BLOCK - RIGID/SOFT

- Double sided block with soft and rigid foam to support abrasive during sanding
- Norgrip Duo fixing allows the abrasive to be changed quickly and easily and prevents surface scratches

| ART NO. | PK QTY |
|-------------|--------|
| 78072742355 | 4 |

FOAM INTERFACES

• Soft flat interfaces for finishing operations to reduce the risk of scratches thanks to the natural rubber and the gripping system, which features the 'flat-top mushroom' shape

| | | A | | |
|------------------|--------------|-------------|-------------|-----------|
| DIAMETER (mm) | NO HOLES | 6 HOLES | 15 HOLES | PK QTY |
| 76 mm | 63642567831 | | | 12 |
| 150 mm | 63642567836* | 63642567837 | 63642567840 | 6 |

* Made-to-order





NORTON ICE DISCS Q255 +++++

- Enhance the speed of spot repair polishing with uniform cutting, achieving a smooth finish and reducing scratch depth
- The open-mesh foam backing adapts to the surface, ensuring even pressure distribution for a consistent finish
- The waterproof mesh foam means the disc can be washed and reused, and it can also be used manually.
- Colour-coded discs enable easy grit identification at a glance

| COLOUR | GRADE | DIA (mm) | ART NO. | PK QTY | BOX QTY |
|---------|-------|----------|-------------|-----------|------------|
| Blue | 1500 | | 66623324958 | 12 | 24 |
| Fuchsia | 2000 | 80 mm | 66623324955 | 12 | 24 |
| Green | 3000 | | 66623324956 | 12 | 24 |
| Blue | 1500 | | 66623324933 | 15 | 60 |
| Fuchsia | 2000 | 150 mm | 66623324952 | 15 | 60 |
| Green | 3000 | | 66623324954 | 15 | 60 |





NEW NORAX U458 - MICROFINISHING DISC #++++

- Effectively removes nibs and defects, easy to polish out
- Long life thanks to the micro 3D structure
- Colour-coded for fast grit identification
- Use wet for better performance
- Use with a sanding block or suitable machine pad
- Self-adhesive waterproof film backing for quick and easy disc change

LAUNCHING SUMMER 2024



| GRIT | GRIT GENERATED | COLOUR CODE DISCS/ LABEL | 32 mm | PK QTY | BOX QTY |
|------|-------------------|--------------------------------|-------------|-----------|-------------------|
| Х3 | 3000-3500 | OLIVE | 66254431739 | 100 | 5 rolls x 100 pcs |
| X5 | 2500-3000 | KHAKI | 66254431740 | 100 | 5 rolls x 100 pcs |
| X7 | 2000-2500 | PURPLE | 66254431741 | 100 | 5 rolls x 100 pcs |
| Х9 | 1500-2000 | GREEN | 66254431742 | 100 | 5 rolls x 100 pcs |

*U458 is authorized for sale only in the EU, Turkey, UK, Morocco and South Africa.

MOUNTING

To be used with a specific sanding block, or on the dedicated pad of the denibbing sanding machine

NEW DOUBLE SIDE SANDING BLOCK - NORGRIP DUO

LAUNCHING SUMMER 2024

- A dual-sided block featuring both hard and medium densities to provide robust support for abrasives during sanding
- This versatile manual sanding block is ideal for various applications
- The Norgrip Duo design enables precise defect removal
- Equipped with PSA/self-adhesive backing for convenient and speedy attachment

| DESCRIPTION | ART. NO. | ΡΚ QTY |
|--------------------------------------------|-------------|--------|
| 30mm sanding block - hard & medium density | 66254431890 | 1 |

LAUNCHING SUMMER 2024



NEW DEFECT REMOVAL KIT

• Spot repair system for all paint types

| DESCRIPTION | ART. NO. | QTY IN KIT | ART. NO. |
|--------------------------------------|-------------|---------------|-------------|
| NORAX U458 discs 32mm - X5 | 66254431740 | 100 | |
| NORAX U458 discs 32mm - X7 | 66254431741 | 100 | |
| NORAX U458 discs 32mm - X9 | 66254431742 | 100 | |
| Cordless denibber machine* | 66254431892 | 1 | 66254431897 |
| Sanding block 30mm- Hard & Medium | 66254431890 | 1 | |
| Blue Magnet microfibre cloth | 63642504402 | 1 | |

*The machine comes with two batteries, a charger, one hard and one medium pad.

| DENIBBER MACHINE ACCESSORIES | ART. NO. | ΡΚ QTY |
|------------------------------|-------------|--------|
| Battery | 66254431893 | 1 |
| Charger | 66254431894 | 1 |
| Hard density pad | 66254431895 | 5 |
| Medium density pad | 66254431896 | 5 |



NORTON ICE STARTER KIT

- This kit serves as a perfect entry point to the Norton Ice range, encompassing discs, polishing compounds, foams, pads, and a finishing spray
- It provides a preview of Norton's technologically advanced products designed to assist in achieving impeccable finishes

| DESCRIPTION | QTY IN KIT | ART. NO. |
|-----------------------------------------|---------------|--------------|
| Liquid Ice Detailer Spray | 1 | |
| Blue Magnet microfibre cloth | 2 | |
| Liquid Ice OEM - 250ml | 1 | |
| Liquid Ice Quick Cut - 250ml | 1 | _ |
| Soft black foam 80mm | 2 | _ |
| Hard white foam 80mm | 2 | _ |
| One box Norton Ice Grit 3000 80mm | 6 | |
| One box Norton Ice Grit 2000 80mm | 6 | 66254488515* |
| One box Norton Ice Grit 1500 80mm | 6 | _ |
| Foam interface 76mm | 2 | _ |
| Pad 76mm | 2 | _ |
| Norwool 76mm | 2 | |
| One box Pure Ice Q175- P1000 76mm | 50 | |
| Norton Ice Starter Kit | 1 | _ |
| 1 process chart "how to use Liquid Ice" | 1 | _ |
| | | * |

* Made-to-order



When only the perfect finish is acceptable, use Liquid Ice polishing compounds and accessories. By reducing the number of polishing steps required, Liquid Ice XtraCut, Quickcut and OEM are practical solutions to improve productivity and quality of work.

Reduce polishing time and overall bodyshop costs with Liquid Ice, which reduces the number of steps required to get that showroom shine. Compounds are 0% silicon and water-based so are contamination-free.



A polished finish can be achieved on common clear coats using only Liquid Ice Xtra Cut, single step process. Use the single-step process for quick applications and good results. If holograms appear or if a higher gloss finish is required (on black, metallic or pearl coating), use Liquid Ice Quick Cut and OEM, dual-step process. The dual-step process gives accurate results and an exceptional finish.



LIQUID ICE - XTRA CUT

+ CUT INDICATOR - GLOSS INDICATOR

- Remove scratches in a single step after grade 2 and finer
- For best results, use with hard foam or lambswool polishing heads
- Only one step is required for the most common clear coat applications, for high gloss finishing and fast application

| VOLUME | ART NO. | PK QTY |
|---------|-------------|-----------|
| 1 Litre | 66623339742 | 6 bottles |



MICROFINISHING





LIQUID ICE - QUICK CUT

- Polish after grade 15, use with hard foam or lambswool for best results
- Follow with OEM and black backed finishing foam to achieve a perfect gloss finish

| VOLUME | ART NO. | ΡΚ QTY |
|---------|-------------|-----------|
| 1 Litre | 66254429419 | 6 bottles |



LIQUID ICE - OEM

+ CUT INDICATOR - GLOSS INDICATOR +

• To remove holograms and clouds and improve gloss for a final finish

| VOLUME | ART NO. | ΡΚ QΤΥ |
|---------|-------------|-----------|
| 1 Litre | 66261191537 | 6 bottles |



LIQUID ICE DETAILER SPRAY

- Liquid Ice Detailer Spray cleans up excess buffing residue and provides paint protection
- Simply spray on and wipe off with a Blue Magnet microfibre cloth for the perfect shorwoom shine

| VOLUME | ART NO. | ΡΚ QTY |
|---------|-------------|-----------|
| 1 Litre | 63642574651 | 4 bottles |



FOAM POLISHING HEADS

- An excellent combination of density and softness for polishing and creating shine
- The open cell design allows the compound to flow through and is held in the foam during use with little or no splattering



| DESCRIPTION | BACKING COLOUR | DIMENSIONS (mm) | DENSITY / SHAPE | ART NO. | ΡΚ QTY |
|---------------------------------------|-------------------|--------------------|--------------------|-------------|-------------|
| Cutting form white flat | Ded | 80 x 25 | Hard / flat | 63642537215 | 4 x 5 pcs |
| Cutting foam - white flat | Red | 150 x 30 | Hard / Ital | 63642537212 | 10 x 2 pcs |
| | \A(_:+_ | 80 x 25 | 11 - mai / | 63642541544 | 4 x 5 pcs |
| Cutting foam - white waffle | white | White Hard / | Hard / waffle | 63642541644 | 10 x 2 pcs |
| | Black | 80 x 25 | Soft / flat | 66254441987 | 4 x 5 pcs |
| Finishing foam - black flat | | 150 x 30 | | 66254441985 | 10 x 2 pcs |
| | | 80 x 25 | | 66623339749 | 4 x 5 pcs |
| General purpose foam - orange flat | | 150 x 30 | Firm / flat | 77696068719 | 10 x 2 pcs |
| ordinge nat | | 150 x 50 | | 66623339748 | 10 x 50 pcs |
| Support pad - super comfort | | 125 - M14 | Soft | 63642541545 | 10 pcs |

NORWOOL LAMBSWOOL POLISHING HEADS

- Norwool polishing heads are made from lambswool natural fibres for cool cutting and immediate shine
- Available in small and large sizes for all polishing needs

| DIAMETER | ART NO. | PK QTY |
|----------|-------------|--------|
| 150 mm | 63642567955 | 6 |
| 76 mm | 63642567956 | 12 |



BACK-UP PAD

- Made from neoprene rubber for optimal pressure dissipation
- Chamfered edges allow the pads to adhere to the contours of bodywork and reduce the risk of edge-cut
- Specially designed for microfinishing

| DIMENSIONS | 200 2000 | a second | ΡΚ QTY | |
|--------------|--------------|-------------|--------|---|
| 76mm - 5/16" | 63642567810 | | 6 | |
| 33mm - 5/16" | 63642567811* | | 6 | |
| 150mm - M14 | | 63642567812 | 3 | * |
| | | | | |



MICROFINISHING



MICROFIBRE CLOTHS

- High-quality micro-fibres are lint-free for streak-free cleaning and won't scratch paint or clear coat, leaving a high gloss shine
- To eliminate any possibility of scratching the surface, each cloth is laser cut and the care sticker is removable
- Each cloth absorbs eight times its weight in water and dries in half the time of a standard towel
- Perfect for polishing applications, washing, cleaning and detailing cars, trucks, boats, motorcycles and delicate surfaces and can be washed and reused, saving money

| COLOUR | DIMENSIONS (mm) | ART NO. | PK QTY |
|--------|-----------------|-------------|--------|
| Red | | 66261108196 | 20 |
| White | 400 x 400 | 66261108197 | 20 |
| Black | | 66261108200 | 20 |



BLUE MAGNET MICROFIBRE CLOTH

- Blue Magnet is the ultimate performance cleaning cloth for general purpose applications such as dusting, drying, polishing and waxing
- Absorbs eight times its weight in water, dries faster than chamois material and is ultra-soft, reusable and machine-washable
- Blue Magnet can be used dry or slightly damp to easily remove dirt, grease and dust from most surfaces, including metal, paint, glass, plastic and leather

| DIMENSIONS (mm) | ART NO. | PK QTY |
|-----------------|-------------|--------|
| 400 x 400 | 63642504402 | 5 |



COTTON TACK RAG

- The 100% bleached cotton (15 threads per sq inch) is coated with an adhesive resin, which picks up and retains particles effectively
- Solvent and silicon-free, so it won't cause surface contamination

| DIMENSIONS (mm) | ART NO. | PK QTY |
|-----------------|-------------|------------|
| 420 x 750 | 07660708050 | 20 x 10pcs |



NON-WOVEN TACK RAG

- Polyester fabric infused with resin to capture tiny particles and imperceptible dust, effectively prepping the surface before painting
- The non-woven structure provides durability and resistance to tearing

| DIMENSIONS (mm) | ART NO. | PK QTY |
|-----------------|-------------|------------|
| 320 x 400 | 07660708051 | 10 x 10pcs |



CLAY FINISHING SOLUTIONS

- For best results, use with the Norton Detailer Spray to give flawless showroom finish
- Clay Disc for finishing large surface areas by machine. With a soft foam backing, the disc is ideal for curved and contoured surfaces during fine surface preparation
- Clay Glove ideal for manual finishing of difficult to reach areas such as edge of panels

| DESCRIPTION | | GRADE | ART NO. | PK QTY |
|------------------|--------------------------|-------|-------------|-----------|
| Ø150mm Clay Disc | Surface Preparation | Fine | 66261140440 | 1 |
| Clay Glove | Fine Surface Preparation | Fine | 66261140439 | 1 |



CLAY STARTER KIT

• The Norton Clay Starter Kit contains 1 clay disc, 1 clay glove, 1 Liquid Ice detailer spray and 1 Blue Magnet microfibre cloth

| DESCRIPTION | QTY IN KIT | ART. NO. |
|-------------------------------------------|---------------|-------------|
| ø150mm Clay Disc Fine Surface Preparation | 1 | |
| Clay Glove Fine Surface Preparation | 1 | |
| Liquid ICE - Detailer Spray 1 litre | 1 | 66261140442 |
| Blue Magnet Microfibre cloth (400x400mm) | 1 | _ |
| Instruction sheet | 1 | _ |





MICROFINISHING



NEW HEADLIGHT REPAIR KIT

- The NEW Norton Headlight Repair Kit helps you achieve crystal-clear surfaces and stunning results easily in less than 15 minutes
- Restores discoloured or chipped headlights

| DESCRIPTION | QTY IN KIT | ART. NO. |
|-------------------------------------------------------------|---------------|-------------|
| Mini Orbital Sander 76mm (pneum) | 1 | |
| Mini Rotary Polisher 76mm (pneum) | 1 | |
| Orange Tape | 1 | |
| Foam interface 76mm | 1 | |
| Norton A975 discs 76mm P500 | 50 | - |
| Norton SuperFlexible discs 76mm Q775 P800 | 25 | - |
| Norton SuperFlexible discs 76mm Q775 P1500 | 25 | |
| Norton SuperFlexible discs 76mm Q775 P3000 | 25 | |
| Farécla G360 Super Fast Compound 500g | 1 | 78072769407 |
| Farécla G3 Wax Premium Liquid 500ml | 1 | - |
| Farécla G Mop 3" Yellow Compounding Foam | 2 | - |
| Farécla G Pro applicator waffle pads (1 white + 1 black) | 1 | - |
| Norton Liquid Ice Detailer Spray - 1l | 1 | |
| Norton Blue microfibre cloths - 400x400mm | 2 | |
| Norton Polybag 600D 38x23x28cm | 1 | |
| Process chart | 1 | |



ND

| ADHESIVES FOR WINDSCREEN REPLACEMENT | 114 |
|-----------------------------------------|-----|
| ONEBOND PU EXPRESS 30 | |
| ONEBOND PU FAST 120 | |
| ONEBOND PU POWER 180 | _ |
| ONEBOND MS RAPID 60 | |
| ONEBOND PU PRIMER | |
| ONEBOND PU DAUBER | |
| ADHESIVES & SEALANTS | 110 |
| FOR BODY REPAIR | 118 |
| ONEBOND PU SEAL 50 | _ |
| ONEBOND MS SEAL 50 | _ |
| ONEBOND MS SEAL 45 SPRAY | _ |
| ONEBOND EP POWER METAL 60MIN | _ |
| ONEBOND PU PLASTIC EXPRESS 30SEC | _ |
| ONEBOND PU PLASTIC FAST 90SEC | _ |
| ONEBOND PU PLASTIC EXPRESS 5MIN | |
| MIX 8.7/24PP2K-200ML BLK | |
| MIXER TQ 2K-50ML GREEN | |
| ONEBOND PU PLASTIC TAPE | |
| ONEBOND PLASTIC PRIMER PE PP | |

| APPLICATOR GUNS | -125 |
|-----------------------------------------------------|----------|
| ONEBOND PNEUMATIC GUNS | |
| ONEBOND MANUAL GUNS | |
| ONEBOND CHEMICALS, WIPES, TAPES, SAFETY AND CARE | 129 |
| DEGREASER & PROTECTIVE SPRAY | <u> </u> |
| PROTECTIVE OILS & CUTTING OILS | <u> </u> |
| CARE & SAFETY | |
| TECHNICAL WIPES & TACK WIPES | |
| MIXERS & NOZZLES | 137 |
| ACCESSORIES | 139 |

THE COMPLETE AUTOMOTIVE AFTERMARKET SOLUTION

BOND



OneBond PU Fast 120

Polyurethane adhesive for windscreen bonding. 120 min.



PU Power 180 Polyurethane adhesive for windscreen bonding. 180 min.

OneBond

OneBond MS 60 Rapid Hybrid windscreen adhesive. 60 min.

OneBond PU Primer Adhesion promoter for windscreen bonding.

Par and



OneBond **PU Plastic**

Two-component polyurethane adhesive for plastic repair. Available in three versions: 30 sec, 90 sec, 5 min.



OneBond PU Express 30 Polyurethane adhesive

for windscreen quick. 30 min.



OneBond EP Power Metal

Two-component structural epoxy adhesive for bonding metal parts.



OneBond MS Seal 50

Hybrid adhesive sealant for repairing body parts.



OneBond MS Spray Sprayable Hybrid Sealant Adhesive.

OneBond PU Seal 50

Polyurethane sealing adhesive for repairing car body parts.

ADHESIVES FOR WINDSCREEN REPLACEMENT

Glass bonding adhesives are widely used in the installation and replacement of automotive windscreens, back-lights, quarter glass and other automotive glass, including sun and panoramic roofs. They are usually one-part polyurethane-based and one-part MS hybrid adhesives.

They can also be used to bond other parts of the vehicle body, such as trims, spoilers and plastic profiles, as well as plastic brackets and sensors to glass.





ADHESIVES FOR WINDSCREEN REPLACEMENT EASY SELECTION

| | PRODUCT | OneBond PU Express 30 | OneBond PU Fast 120 | OneBond PU Power 180 | OneBond MS Rapid 60 |
|----------|-------------------------|--------------------------|------------------------|-------------------------|------------------------|
| | KEY FEATURE | FAST CURING | HIGH FLEXIBILITY | LONG OPEN TIME | PRIMERLESS |
| | NON HAZARDOUS | Yes | Yes | Yes | Yes |
| 8 | HIGH MODULUS | Premium | Yes | Yes | Yes |
| | SKIN-TIME | 15 minutes | 25 minutes | 35 minutes | 15 minutes |
| @ | DRIVE AWAY TIME | 30 minutes | 2 hours | 3 hour | 1 hour |
| | CRASH TEST FMVSS 212 | Certified | Compliant | Compliant | Certified |
| G | CONDUCTIVITY | Non conductive | Very low | Very low | Non conductive |
| 0 | REQUIRE GLASS PRIMER | Yes | Yes | Yes | No |



ONEBOND PU EXPRESS 30

OneBond PU Express 30 is the fastest-curing polyurethane adhesive in the portfolio. It is non-conductive and has the highest modulus strength of all the glass-bonding products in the OneBond range. OneBond PU Express is recommended for windscreen replacement in high-end cars. Certified by TÜV.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 310ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765568 |
| 400ml | EN, FR, NL, IT | 20 | 69210492911 |



ONEBOND PU FAST 120

OneBond PU Fast 120 has a two-hour drive-away time and a skin time of 25 minutes. It is recommended for car windscreen replacement and to structurally bond thin metal panels in commercial vehicles due to its high elasticity. Available in black in 310ml aluminium cartridges.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 310ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765565 |



ONEBOND PU POWER 180

OneBond PU Power 180 has a three-hour drive-away time and an open time of 35 minutes, making it ideal for applications that require long cycle times (stationary windscreen replacement is common for buses, trucks and vans).

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 310ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765564 |
| 400ml | EN FR NL IT | 20 | 66254427434 |
| 600ml | FR NL EN PL | 20 | 66254427439 |



ONEBOND MS RAPID 60

OneBond MS Rapid 60, has a one-hour drive-away time and does not require a primer. It has an open time of 15 minutes, making it ideal for small, quick applications. Certified by TÜV.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 290ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765570 |
| 400ml | EN, FR, NL, IT | 20 | 66254427435 |



ONEBOND PU PRIMER

OneBond PU Primer can be used to improve the adhesion of painted plastics and metals, GFR plastics and metals. If the body is damaged during the glass removal step, and the epoxy layer or even the bare metal is exposed, the application of a layer of primer will be required to prevent the metal from rusting and also to prevent compatibility issues between the original glass bonding adhesive and the new layer.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 30ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765569 |
| 10ml | EN, FR, NL | 12 | 66254427440 |



ONEBOND PU DAUBER

OneBond Daubers are designed for the application of OneBond Primer and does not leave fibres on the glass surface.

| SIZE | BOX QUANTITY | ART NO. |
|--------------|--------------|-------------|
| 20mm x 125mm | 10 per bag | 78072767002 |



ADHESIVES & SEALANTS FOR BODY REPAIR

The main difference between adhesives and sealants is that sealants exhibit higher elasticity and lower tear resistance than adhesives. Higher elasticity is required for sealing applications in cars and commercial vehicles for a better distribution of stress and to reduce noise. Sealants can join dissimilar materials with different thermal expansion coefficients and with different galvanic potential, protecting the metal from corrosion.

OneBond sealants exhibit outstanding UV resistance for exterior applications and can be sanded and painted when cured.





ADHESIVES & SEALANTS FOR BODY REPAIR EASY SELECTION

| | | OneBond | OneBond | OneBond |
|----------|--------------------------------------------|--------------------------------|----------------------------------|--------------------------------------|
| | PRODUCT | PU Seal 50 | MS Seal 50 | MS Seal 45 Spray |
| | KEY FEATURE | HIGH MECHANICAL STRENGTH | FAST REPAIR NON- HAZARDOUS | SPRAYABLE NON- HAZARDOUS |
| | SKIN TIME 10°C / 30% RH | 90 minutes | 40 minutes | 90 minutes |
| | SKIN TIME 23°C / 50% RH | 20 minutes | 20 minutes | 30 minutes |
| | SKIN TIME 40°C / 80% RH | 10 minutes | 5 minutes | 20 minutes |
| | TOOLED, BRUSHED WITHIN THE OPEN TIME | Yes | Yes | Yes, when is applied as a bead |
| 1 | PAINTING TIME (min / max) | From 2 hours to 24 hours | Wet-to-wet to 24 hours | Wet-to-wet to 24 hours |
| 8 | SANDING TIME | 24 hours | 24 hours | 24 hours |
| | UV RESISTANT | Yes | Yes | Yes |
| G | CONDUCTIVITY | Very low | Very low | Very low |
| | | | | |

ADHESIVES & SEALANTS FOR BODY REPAIR EASY SELECTION

PLASTIC REPAIR ADHESIVES SELECTION GUIDE

| PRODUCT | OneBond EP Power Metal 60 minutes | OneBond PU Plastic Express 30 seconds | | OneBond PU Plastic Fast We believe this is | |
|-----------------------------------------------|-----------------------------------------|------------------------------------------------|------------|------------------------------------------------------------|--|
| KEY FEATURE | METAL PANEL BONDER | ULTRA-RAPID REPAIR | | tested, so can thi to see if it is corr AND ASSEMBLY | |
| STRUCTURAL | Yes | No | No | No | |
| CRASH RESISTANT | No | - | - | - | |
| OPEN TIME | 60 minutes | 30 seconds | 90 seconds | 5 minutes | |
| TOOLED, BRUSHED WITHIN THE OPEN TIME | Yes | - | - | - | |
| FIXTURE TIME | 4 hours | 2 minutes | 10 minutes | 15 minutes | |
| CURING ACCELERATED BY HEAT | Yes | - | - | - | |
| SANDING TIME | - | 5 minutes | 10 minutes | 30 minutes | |
| MAX SERVICE TEMPERATURE RESISTANCE | 180°C | 100°C | 100°C | 100°C | |
| SHELF LIFE | 24 months | - | - | | |

B

M



ONEBOND PU SEAL 50

OneBond PU Seal 50 is a moisture-cured, UV stable solvent-free polyurethane-based sealant and medium strength adhesive, suitable for interior and exterior applications. It has excellent adhesion to glass fibre reinforced plastics thermoplastics (ABS, PC, PVC), metals, coated metals, concrete, wood and glass, even without primer. OneBond PU Seal 50 has outstanding mechanical properties and durability, is non-conductive and provides corrosion protection. Available in black, white and grey.

| SIZE | BOX QUANTITY | COLOUR | ART NO. | |
|-------|-----------------|--------|-------------|--|
| 310ml | 12 | Black | 78072768750 | |
| 310ml | 12 | White | 78072765586 | |
| 310ml | 12 | Grey | 78072765574 | |



ONEBOND MS SEAL 50

OneBond MS Seal 50 is a moisture-cured, UV-stable, hybrid sealant suitable for horizontal and vertical applications. It is a multi-purpose product that can also be used for medium-strength bonding of internal panel areas in trucks and buses, and fixing and sealing caravans door and window frames. OneBond MS Seal 50 has excellent adhesion to glass fibre reinforced plastics, thermoplastics (ABS, PC, PVC), metals, coated metals, concrete, wood and glass, even without primer. It is non-conductive and provides corrosion protection.

| BOTTLE SIZE | BOX QUANTITY | COLOUR | ART NO. |
|----------------|-----------------|--------|-------------|
| 290ml | 12 | Grey | 78072765575 |
| 290ml | 12 | White | 66254427408 |



ONEBOND MS SEAL 45 SPRAY

OneBond MS Seal 45 is a moisture-cured, UV-stable, hybrid sealant suitable for replacing OEM spray seams. It can be applied as a bead or as a coating by adjusting the air pressure, the product dosage, the distance from the substrate and the nozzle design. OneBond MS Seal 45 Spray has excellent adhesion to glass fibre reinforced plastics, thermoplastics (ABS, PC, PVC), metals, coated metals, concrete, wood and glass, even without primer. It is non-conductive and provides corrosion protection. Available in grey and ochre.

| BOTTLE SIZE | BOX QUANTITY | COLOUR | ART NO. |
|----------------|-----------------|--------|-------------|
| 290ml | 12 | Grey | 78072765578 |
| 290ml | 12 | Ochre | 78072768763 |
| | | | |





ONEBOND EP POWER METAL 60min

OneBond EP Power Metal 60 is a two-part toughened structural epoxy adhesive for use on metal. It offers higher rigidity, strength, environmental and temperature resistance than OneBond PU Flex 12 for bonding and weld-bonding fenders, rear body panels, roofs, door reinforcements, door skins, bonnet skins and floor pans. It is also suitable to bond the bed panels and metal and composite side panels of vans, trucks and buses. It is non-conductive and provides corrosion protection. OEM approved and certified by TÜV.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | COLOUR | ART NO. |
|----------------|--------------------------------------------------------------|-----------------|--------|-------------|
| 195ml | EN, PL, FI, DK, SE, NO, GR, IT, ES, PT, TK NL, FR, PL, DE | 12 | Black | 78072765579 |
| 220ml | EN, IT, ES, PT, TK NL, FR, PL, DE | 12 | Black | 66254427415 |



ONEBOND PU PLASTIC EXPRESS 30sec

OneBond PU Plastic Express 30 seconds. is a polyurethane adhesive two-component, EC1 low-emission certified, suitable for repairing cracks, scratches and holes in the exterior plastic parts of cars, including bumpers, spoilers, tailgates and side mirrors. It is suitable for metals, coated metals and plastics (except polyethylene polypropylene and Teflon). It can be sanded and painted quickly, has good impact resistance. It can also be used for small assemblies, for gluing window brackets, trim parts and for mounting brackets on headlights and taillights.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|-----------------------------------------------------|-----------------|-------------|
| 50ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 20 | 66623341009 |
| 50ml | EN, PL, FI, DK, SE, NO, HU, CZ, RO & CRO/SRB/BiH | 20 | 66254427413 |

ONEBOND PU PLASTIC FAST 90sec

OneBond PU Plastic Fast 90 seconds is a polyurethane adhesive twocomponent, EC1 low-emission certified, suitable for repairing cracks, scratches and holes in the exterior plastic parts of cars, including bumpers, spoilers, tailgates and side mirrors. It is suitable for metals, coated metals and plastics (except polyethylene polypropylene and Teflon). It can be sanded and painted quickly, has good impact resistance. It can also be used for small assemblies, for gluing window brackets, trim parts and for mounting brackets on headlights and taillights.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 50ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 20 | 66254426446 |



ONEBOND PU PLASTIC EXPRESS 5min

OneBond PU plastic Rapid 5 minutes is a polyurethane adhesive twocomponent, EC1 low-emission certified, suitable for repairing cracks, scratches and holes in exterior plastic parts of cars, including bumpers, spoilers, tailgates and side mirrors. It is suitable for metals, coated metals and plastics (except polyethylene polypropylene and Teflon). It can be sanded and painted quickly, has good impact resistance. OneBond PU Plastic Rapid 5 minutes can be also used for small bonding of window brackets, decorative parts and mounting brackets on front and rear lights.

| BOTTLE SIZE | BOTTLE | | ART NO. |
|----------------|------------------------------------|----|-------------|
| 50ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 20 | 66254426449 |



MIX 8.7/24PP2K-200ml BLK

Mixers to be used as recharge for additional applications of 2K products from 200ml up to 400ml as PU FLEX 12 (280ml) and EP Power metal (195 ml), EP POWER METAL 60.



| COLOUR |
|--------|
| Black |

BOX QUANTITY


ART NO. 78072767766



ONEBOND PU PLASTIC TAPE

OneBond PU Plastic Tape is a glass fibre reinforced with PVC film that provides better impact resistance to the repaired area. It is applied in the outer side and helps to repair broad areas. Available also in the reinforced version to be applied in the inner side.

| SIZE | TYPE | BOX QUANTITY | ART NO. |
|--------------|--------------------|--------------|-------------|
| 13cm x 150cm | Plastic | 12 | 78072765590 |
| 10cm x 150cm | Reinforced Plastic | 12 | 78072765591 |



ONEBOND PLASTIC PRIMER PE PP

OneBond PU Plastic Primer is a solvent-based adhesion promoter solvent-based adhesion promoter used to improve adhesion in plastic repair applications such as PMMA, ABS, PP, PA, TPU, rigid PVC. Compatible with Onebond PU Plastic, low emission 30sec, 90sec and 5 min.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 200ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 6 | 78072767700 |





OneBond applicators range specially designed to achieve the best performance of OneBond adhesives.

ONEBOND PNEUMATIC GUNS

AS01-PNEUM GUN CART&BAG 1K 0P34A

A pneumatic gun without a piston for or 300/310ml cartridges and 300/400ml soft pack

- Use with: PU Seal 50, MS Seal 50, EP Power Metal 12, PU Flex 12
- Pneumatic gun without piston
- Recommended for applying medium viscosity sealants
- Connection: ¹/₄ male gas
- Weight: 1.072g
- Working pressure: 4-8 bar

| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|----------------------------------------------------------|--------|-----------------|-------------|
| PU Seal 50, MS Seal 50, EP Power Metal 12, PU Flex 12 | Black | 1 | 63642599995 |





AS01-PNEUM GUN CART&BAG 1K 0P34PI

Pneumatic gun with piston for for 300/310ml cartridges and 300/400ml soft pack(ideal for glass bonding).

- Use with: PU Power 180, PU Fast 120, PU Express 30, MS Rapid 60
- Recommended for applying medium viscosity sealants and high viscosity glass-bonding adhesives
- Also suitable for dispensing two-part epoxy and polyurethane-based structural adhesives packed in coaxial cartridges by changing the ring nut (the static mixer is not centred)
- Connection: ¼ male gas
- Working pressure: 4-8 bar
- Weight: 1.416g

| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|-----------------------------------------------------------|--------|-----------------|-------------|
| PU Power 180, PU Fast 120, PU Express 30, MS Rapid 60, | Black | 1 | 63642599990 |

AS01-PNEUM SPRAY GUN CART 1K OSP310

Pneumatic gun for sprayable sealant 310ml cartridge.

- Use with: MS Seal 45 Spray
- Sealants can be extruded and sprayed
- Includes a kit of nozzles to achieve the desired bead shape (Ø 1.6 – 2.5 mm)
- Includes an anti-clogging nozzle (metal pin)
- The spraying cap is made of anti-adherent material (POM)
- Includes an anti-clogging nozzle (metal pin)
- Working pressure 3-5 bar (maximum pressure of 8 bar)
- Nozzle: Ø 1.6 or 2.5 mm
- Connection: ¼ male gas
- Weight: 1330g

| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|------------------|--------|-----------------|-------------|
| MS Seal 45 Spray | Black | 1 | 77696097057 |

SPARE PART KIT FOR OSP310 ONEBOND SPRAY GUN

- Plastic nozzle flat shape female thread 15 x 1.5
- Plastic nozzle round shape female 15 x 1.5
- Plastic nozzle half-round shape female thread 15 x 1.5 with adjustable tongues.
- Cap for plastic nozzle

| FOR USE WITH | BOX QUANTITY | ART NO. |
|-----------------------------------|-----------------|-------------|
| Pneum Spray Gun Cart 1K OSP310 | 1 KIT | 66254427383 |

- Brush for OSP310 cleaning
- 0-ring 15.00 x 4.00
- Nozzle in PE type arm with blade cut, M15 x 1.5



ONEBOND MANUAL GUNS

AS01-MAN GUN CART&BAG 1K 0M340-18 ONB

Manual gun for use with 300ml cartridges and with 400ml soft bags.

- Ring nut made of aluminium
- Suitable for 290/310ml cartridges and 400ml sachets
- Recommended for applying medium viscosity sealants and high viscosity glass-bonding adhesives
- Maximum force: 450Kgf 4.412 N
- Progress/Stroke: 4.5mm
- Weight: 840g



| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|-----------------------------------------------------------------------------------------------|--------------------------|-----------------|-------------|
| PU Power 180, PU Fast 120, PU Express 30, MS Rapid 60, EP Power Metal 60, PU Flex 12 | Black & Brushed steel | 1 | 77696097769 |

AS01-MAN GUN 2K METAL (1:1&2:1) 0M21

Manual gun for 2K PU adhesives (50ml) for Plastic Repair – Metal body.

- Use with: PU Plastic Express 1 Min, PU Plastic Fast 5 Min
- High power for easy application of adhesives
- Durable product because of the complete metal frame
- Designed to guarantee accurate and sustainable application
- Ergonomic moulded grip

| FOR USE WITH | MIXING RATIO | BOX QUANTITY | ART NO. |
|----------------------------------------------------|-----------------|-----------------|-------------|
| PU Plastic Express 1 Min, PU Plastic Fast 5 Min | 1:1 & 2:1 | 1 | 77696097231 |





AS01-MAN GUN CART&BAG 1K OM346JL-20 ONB

Manual gun specially designed for the extrusion of one component sealants and adhesives from low to medium viscosity. To be used with products contained in 300ml / 400ml / 600ml soft bags and in standard 300ml / 310ml cartridges.

- Thrust ratio: 20:1
- Weight 690g
- Material-holding tube: Aluminum to control the extrusion of the product.
- Clutch: Forged steel
- Push rod: Galvanized carbon steel
- Lever: Stamped steel

| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|--------------------------------------------------------------------------------------------------------------|--------------------------|-----------------|-------------|
| PU Power 180, PU Fast 120, PU Express 30, MS Rapid 60, EP Power Metal 60, PU Flex 12 and many other | Black & Brushed steel | 1 | 78072773587 |



MAN GUN 2K (1:1&2&4&10) 04IN1JL

4-IN-1 APPLICATOR

- Two plunges and one body enable to operate most two part 50ml epoxy and resin cartridges with ratios of 1:1, 2:1, 4:1 and 10:1
- Lightweight portability and durable construction for many assembly operations
- Easy to dispenser the adhesive with a very controlled flow

| FOR USE WITH | MIXING RATIO | BOX QUANTITY | ART NO. |
|-----------------------------------------------------------------------|----------------------|-----------------|-------------|
| PU Plastic Express1 Min, PU Plastic Fast 5 Min and many others. | 1:1,2:1, 4:1,10:1 | 1 | 78072774869 |



MAN GUN 2K (1-1-1-2) 0M220

- High power for effortless adhesive dispensing
- Enhanced durability due to the robust all-metal frame
- Designed to ensure precise and long-lasting application
- Features an ergonomic molded grip for comfortable use
- Fully black dispenser that conceals grease and dirt stains effectively

| FOR USE WITH | COLOUR | BOX QUANTITY | ART NO. |
|-----------------------------------|--------|-----------------|-------------|
| 0B EP Power Metal 60 min 220ml | Black | 1 | 66254422401 |

ONEBOND CHEMICALS, WIPES, TAPES, SAFETY AND CARE

750m

Welcome to the exciting world of OneBond from Saint-Gobain Surface Solutions. As a world-leading supplier to maintenance, repair and assembly customers, it's our mission to deliver performance-based sustainable solutions to effectively help build and restore your equipment, whilst saving you time, effort and cost.

OneBond products are specifically designed to be safe, efficient, application-focussed and easy-to-use in the wide range of repair and maintenance challenges you face every day. And this is just the start; our ongoing commitment to innovation means we are continually developing new results-based products to make your life easier.





DEGREASER & PROTECTIVE SPRAY

Clean, degrease and protect all types of surfaces quickly and easily with OneBond cleaning products.



ONEBOND DG 500 BIODEGRADABLE NEUTRAL DEGREASER

OneBond DG 500 degreaser is free of caustic soda and solvents. It is non-alkaline and biodegradable. Ideal for removing grease from all surfaces, including steel, stainless steel, aluminium, cast iron, wood, PVC, glass, ceramic and painted surfaces.

- Removes even encrusted grease and dirt without the need for more aggressive cleaners
- Ideal for cleaning surfaces before and after glueing, stripping, grinding and cutting operations
- Compatible with aluminium
- Recommended use within 24 months of opening

| DENSITY (Min/Max) | SIZE (liters) | ΡΚ QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|--------|-------------|
| 0.99/1.03 | 0.75 | 12 | Yellow | 78072763665 |



ONEBOND PS 500 PROTECTIVE SPRAY

OneBond PS 500 is a cleaner, rinse aid and protective spray which provides an invisible coating over the surface to clean and preserve it. It can be used on stainless steel, glass, tiles, chrome and vinyl. It can also be used as a rinse aid for stainless steel after polishing and finishing. Using PS 500 can reduce cleaning and maintenance costs.

- Odourless.
- Kind to treated surfaces
- Helps to repell dust and dirt
- Anti-static when used on electrically charged surfaces
- Recommended use within 24 months of opening

| DENSITY (Min/Max) | SIZE (liters) | ΡΚ QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|-------------|-------------|
| 0.99/1.03 | 0.75 | 12 | Transparent | 78072763666 |



ONEBOND TP 500 PROFESSIONAL THERMAL PROTECTOR

This product is specially formulated for the protection of surfaces close to welding or grinding areas. It dissipates heat, avoiding burns, deformations and other undesirable effects of a high heat point. It absorbs heat by evaporating.

- Its special molecular structure means that the product can be sprayable and a gel at the same time. Adheres well to vertical surfaces
- Should be used pure, without dilutions
- Ideal product for plumbing, heating and cooling, air conditioning and for industry in general. For soft, hard, autogenous, argon welding processes, etc.
- Protects sensitive materials such as wood, tiles, aluminium, glass, synthetic materials, rubbers, and seat gaskets

| DENSITY (Min/Max) | SIZE (liters) | ΡΚ QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|-------------|-------------|
| 1.008/1.029 | 0.75 | 12 | Transparent | 78072767573 |

ONEBOND RT 500 RUST TRANSFORMER; ACID-BASED FORMULATION

OneBond RT 500 is a highly effective rust converter with high covering power that can be used as a primer before painting.

HOW TO USE:

- Remove any grease, oil and soot.
- Remove calamine scale, chipped paint and unadhered rust.
- Apply RT 500 with a stiff brush for good penetration.
- RT 500 can be applied even on wet surfaces.
- If it's applied with on spray or roller, it's important to apply a second coat after 30 minutes
- RT 500 will dry in 20 minutes, but full reaction will take 12 hours.
- After 12 hours surface will be ready to be painted. If surface is left unpainted more than 48 hours, then RT 500 will need to be reapplied before painting

| DENSITY (Min/Max) | SIZE (liters) | PK QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|--------|-------------|
| 1.008/1.029 | 1 | 6 | White | 66254423518 |



BOND

TP 500



ONEBOND DG 550 NEUTRAL BIODEGRADABLE DEGREASER

Professional/industrial users only. Apply to the surface to be cleaned and rub with OneBond SA 200 or XP 200 wipes. Rinse with water if needed.

- 5 Litres carafe- best value packaging.
- Easily eliminate grease and grime from a variety of surfaces, including steel, stainless steel, aluminum, cast-iron, wood, PVC, glass, ceramic, and painted surfaces
- Thanks to its neutral pH, it won't harm paint, glass, plastic, aluminum, and other surfaces
- Suitable for use with water jet cleaner machines at a 10% dilution

| DENSITY (Min/Max) | SIZE (liters) | ΡΚ QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|-----------|-------------|
| 1.03 | 5 | 4 | Yellowish | 78072768733 |



ONEBOND ONE CLEANER

The surface must be free of dust and contaminants as these can lead to partial or complete adhesion loss. OneBond One Cleaner is a multi-purpose solution for removing all contaminants from glass, plastic and metal. A water-based spray, it shows and removes marks, hand prints and particles for a clean, shiny finish.

The active formula is aggressive on contaminants.

- Foaming action identifies contaminant areas.
- Spray-on/wipe-off foam.
- Does not run, fast drying and residue-free action.
- Efficient as a glass cut out lubricant.
- Can be used as a dry cleaner for external parts and internal upholstery and cockpit.

| BOTTLE SIZE | LANGUAGES | BOX QUANTITY | ART NO. |
|----------------|------------------------------------|-----------------|-------------|
| 400ml | EN, IT, ES, PT, TK, NL, FR, PL, DE | 12 | 78072765571 |



PROTECTIVE OILS & CUTTING OILS

High performance oils for lubricating and cutting and for protecting metal from rust and corrosion.



ONEBOND PO 500 ANTICORROSIVE PROTECTIVE OIL

OneBond PO 500 is an anti-corrosive protective oil spray for use on metallic elements when they are stored or in transit. It is ideal for when paint and rust has been removed, to prevent corrosion. It can be easily removed with OneBond DG 500 degreaser and a OneBond SA 200 wipe.

- Low toxicity, can be used in ambient temperatures
- Penetrates elements well due to its fluidity
- Maximum efficiency for medium exposure periods
- Recommended use within 24 months of opening

| DENSITY (Min/Max) | SIZE (liters) | PK QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|-----------|-------------|
| 0.87/0.91 | 1 | 12 | Rubin Red | 78072763667 |



ONEBOND CO 500 SYNTHETIC CUTTING OIL

OneBond CO 500 is a powerful, synthetic lubricant and cutting oil. For professional use on ferrous and non-ferrous materials, it is also highly effective on carbon steel, stainless steel and aluminium.

- Non-irritant, safe to use
- Specifically designed for drilling with a high degree of lubrication
- Specially developed for use with Norton HSSM2 and HSS-E (cobalt) core drill
- Transparent oil for full surface visibility
- Recommended use within 24 months of opening

| DENSITY (Min/Max) | SIZE (liters) | PK QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|-----------|-------------|
| 0.87/0.91 | 1 | 12 | Rubin Red | 78072763659 |





CARE & SAFETY

Emphasising care and safety for professionals, our hand wash is a dermatologically tested and neutral pH.



ONEBOND HC 150 HAND WASHER DEGREASER WITH DISPENSER


- Easily and quickly eliminate grease, oils, and stubborn dirt with HC150. This formula includes friction agents to simplify the degreasing process
- Simply apply a small amount of HC150 to dry hands, rub, and then add a little water
- Once the grime is dissolved, rinse thoroughly with water

| DENSITY (Min/Max) | SIZE (litres) | ΡΚ QTY | COLOUR | ART NO. |
|----------------------|------------------|--------|--------------|-------------|
| 0.89 | 5 | 4 | Light yellow | 78072767827 |



TECHNICAL WIPES & TACK WIPES

Highly-resistant and reinforced technical wipes with fast absorption and extra cleaning power. Tack wipes are the perfect solution.



ONEBOND SA 200 SUPER FAST ABSORPTION

OneBond SA 200 super absorbent wipes are ideal for maintenance and cleaning. The polyester backing provides structure and resistance, and the front is made from lint-free pulp for excellent absorption of all types of particles.

- Extremely hard-wearing, resistant to tearing and compatible with the most aggressive solvents
- Highly absorbent, ensures the surface dries fast with no lint
- Can be used on plastic, metal and composite parts
- Washable and re-usable

| PK QTY | PACK QTY | ART NO. |
|--------|-------------------------------------|------------|
| 1 Roll | Pre-cut wipes 400 Wipes(32x40mm) | 7660782170 |



ONEBOND XP 200 EXTRA CLEANING POWER

OneBond XP 200 are extra powerful, robust, non-woven wipes which combine high absorption, cleaning efficiency and abrasion resistance, whether used wet or dry. They are an excellent alternative to all classic rags.

- Specially created for maintenance cleaning of oil, grime and solvents
- High absorption and resistance for cleaning contaminated tools, machines and absorbing oil, grease and heavy liquids
- The 'beehive' pattern provides extra scrubbing power

| PK QTY | PACK QTY | ART NO. |
|--------|------------------------|------------|
| 1 Box | 200 Wipes (32x40mm) | 7660782171 |





ONEBOND GP 200 GENERAL PURPOSE

- OneBond GP 200 features a distinctive waffled structure designed to guarantee effective particle capture and high tackiness, without any transfer.
- Crafted from 100% cotton with a 13-yarn gauze
- Its unique formulation maintains tackiness over extended periods
- Perfect for use in dusty environments such as woodwork, composite work, primer application, and windmill maintenance
- The larger-sized cloths (90x95cm) are particularly well-suited for capturing more dust

| PK QTY | ΡΑCΚ QTY | ART NO. | |
|--------|-----------------------|------------|--|
| 1 Box | 25 Wipes (90x95cm) | 7660782173 | |



ONEBOND XP 250 EXTRA POWERFUL

OneBond XP 250 extra powerful wipes are made from polyester and viscose with a medium non-woven aperture. They have a unique formulation designed to catch medium to small sanding dust and particles.

- Better tear and abrasion resistance with no fibre loss due the acrylic binder
- Removes twice as much dust as a traditional cotton tack rag
- Black colour wipes makes dust particles easily visible
- Provides a perfect finish before applying paint or clear coat
- Larger cloths (90x95cm) are ideal for catching more dust

| PK QTY | PACK QTY | ART NO. | |
|--------|-----------------------|------------|--|
| 1 Box | 10 Wipes (32X40cm) | 7660700766 | |

MIXERS & NOZZLES

AS01-MIXER TQ 2K-50ML GREEN 10 PCS.

Mixers to be used with PU PLASTIC FAST and PU PLASTIC EXPRESS.

| BOX QTY (pcs) | PACK QTY (pcs) | ART NO. |
|---------------|----------------|-------------|
| 1 Bag | 10 pcs./Bag | 77696083788 |

AS01-MIX 8.7/24PP2K-200ML BLK 10 PCS.

Mixers to be used with PU FLEX 12.

| BOX QTY (pcs) | PACK QTY (pcs) | ART NO. |
|---------------|----------------|-------------|
| 1 Bag | 10 pcs./Bag | 78072767766 |

AS01-ST MIXER 77MM-R10:1 FOR 7790

Mixers to be used with 7790.

| BOX QTY (pcs) | PACK QTY (pcs) | ART NO. |
|---------------|----------------|-------------|
| 1 Bag | 10 pcs./Bag | 78072773549 |



AS01-ST MIXER 103mm NO PEDESTAL-8422

Mixers to be used with 8422.

| _ | BOX QTY (pcs) |
|---|---------------|
| | 1 Bag |

PACK QTY (pcs)

ART NO. 78072773554

AS01-ST MIXER 112mm-R1:1 FOR 8740

Mixers to be used with 8740.

| BOX QTY (pcs) | PACK QTY (pcs) | ART NO. |
|---------------|----------------|-------------|
| 1 Bag | 10 pcs./Bag | 78072773553 |



AS01-50GN0ZZLE-160-116-042-070&074

Nozzle to be used for additional applications of anaerobic OneBond range; 160, 116, 042, 070 and 074.

| BOX QTY (pcs) | PACK QTY (pcs) | ART NO. |
|---------------|----------------|-------------|
| 1 Bag | 10 pcs./Bag | 78072772776 |



NOZZLES FOR CATRIDGES AND SOFT PACK

| PRODUCT | PACK Q.TY (pcs) | ART NO. |
|-------------------------------------------------------------------|--------------------|-------------|
| Soft pack nozzle | 48 pcs./Bag | 66623390640 |
| Cartridge nozzle | 48 pcs./Bag | 66623390642 |
| Kit (2 cartridge nozzle x2, cap x3, spatula x1, silicone scraper) | 48 pcs./Bag | 66623390643 |











To be applied on the outer side of the repaired part.

| BOX Q.TY (pcs) | PACK Q.TY (pcs) | ART NO. |
|----------------|-----------------|-------------|
| 12 Bags | 1 pc/Bag | 78072765590 |

AS02- REINFORCED FILM 13 x 150 cm

To be applied on the inner side of the repaired part.

| BOX Q.TY (pcs) | PACK Q.TY (pcs) | ART NO. |
|----------------|-----------------|-------------|
| 12 Bags | 1 pc/Bag | 78072765591 |



AS03- WOOL DAUBERS-125 x 20 x 1.6 -10 PCS

Designed for the application of OneBond Primer.

| BOX Q.TY (pcs) | PACK Q.TY (pcs) | ART NO. |
|----------------|-----------------|-------------|
| 12 Bags | 1 pc/Bag | 78072767002 |







PERSONAL PROTECTION EQUIPMENT

| MASKS | - 142 |
|------------------------------------|-------|
| Dual cartridge respirator mask | _ 142 |
| Particulate filter pad replacement | |
| SAFETY GLASSES | - 144 |
| Safety glasses | 44 |
| Glasses safety information | |
| GLOVES | - 146 |
| Non-sterile nitrile gloves | - 140 |
| Non-sterile latex gloves | |
| OVERALLS | - 147 |
| Painting overall | - 147 |
| Body shop overall | |



PERSONAL PROTECTION EQUIPMENT

MASKS

The Norton range of personal protection equipment is designed to provide the highest standard of protection in the workplace. All products adhere to the most stringent European directives and regulations. Our approach to safety in the workplace is taken very seriously and products are designed to the most rigorous standards to guarantee optimum personal safety and user comfort.



DUAL CARTRIDGE RESPIRATOR MASK EN405:2001+A1:2009 CE 2834

- Soft, non-allergenic material is smooth and comfortable to wear on the face
- Patented hygienic form guard maintains the shape of the mask and its cleanliness after use
- Low profile cartridge provides unimpeded vision to the user
- Cradle suspension and adjustable head straps give the user a secure and comfortable fit
- Filter replacement pads are low maintenance and can be frequently replaced to prevent replacing the mask itself

| MODEL | PRODUCT DESCRIPTION | PROTECTION LEVEL | ART NO. | PK QTY |
|-------|------------------------------------|------------------|-------------|--------|
| 2016 | Dual cartridge respirator mask | FFA A2P2 | 66254482016 | 1 |
| 2017 | Particulate filter pad replacement | P2 | 66254482017 | 12 |



Hygienic form guard to maintain shape and cleanliness



Low profile cartridge for improved vision



USAGE ADVICE



Place the respirator over the mouth and nose, then pull the head harness over the crown of the head.



Attach the bottom straps behind the neck.



Tighten top strap by pulling on ends to obtain a secure and comfortable fit. Tighten bottom straps by pulling on ends or loosen by pushing out on buckle tab.



Check respirators each time you enter a contaminated area.

NORTON UPHOLDS THE FOLLOWING EUROPEAN DIRECTIVES FOR RESPIRATORY MASKS:

- Directive 89/656/CEE of 30 November 1989 on the use of PPE by workers. It stipulates the employers' obligations
- The PPE required for work must be provided free of charge
- PPE must comply with the legal provisions in force
- The employer must have, at its disposal, the information needed for proper use of the product. The rules and conditions of use must be defined
- The user must be informed, and training provided
- Directive 89/686/CEE of 21 December 1989 on the design, market entry, free circulation of PPE within the European Union. This Directive has evolved and been modified by 95/58/CEE
- The essential requirements to be met by PPE in order to be put on the European market
- The specific texts provide a classification with regard to hazards



PERSONAL PROTECTION EQUIPMENT

SAFETY GLASSES

Providing eye protection for metal, welding, cutting, grinding and sanding applications.



SAFETY GLASSES STANDARD EN 166

- Ideal for general purpose applications protects from dust and paint particles
- Markings on the frame and lens indicate conformity to quality and safety standards

| MODEL | PRODUCT DESCRIPTION | ART NO. | PK QTY | BOX QTY |
|-------|---------------------|-------------|-----------|------------|
| 2025 | Standard glasses | 66254482025 | 1 | 10 |


STANDARDS AND LEGISLATION FOR GLASSES

Directive 89/686/EEC (Design) describes the essential requirements to be met in order to sell protective glasses on the European market.


PPE from the European Union must bear a marking testifying to its compliance with Directive 89/686/EEC. All our glasses complies with Directive 89/686/EEC and EN 166 which describes "Technical Performance standards". Our premium glasses complies with the EN 175 which describes "equipment for eye and face protection during welding and allied process".

The "CE" marking appears on the smallest packaging unit.






UNDERSTANDING LENS MARKING



UNDERSTANDING FRAME MARKING





PERSONAL PROTECTION EQUIPMENT

GLOVES

Nitrile and latex gloves are designed for handling chemical and non-chemical compounds in the automotive market.





NON-STERILE NITRILE GLOVES

- Disposable gloves are designed for handling chemical compounds
- The gloves are powder-free and resistant to disinfectants
- Made from 100% synthetic nitrile rubber and latex-free to prevent skin irritation
- One size fits all

| MODEL | PRODUCT DESCRIPTION | MEDIUM | LARGE | EXTRA LARGE | PK QTY |
|-------|---------------------------------------|-------------|-------------|-------------|-----------|
| 2022 | Nitrile gloves for chemical compounds | 66623398849 | 66254482022 | 66623398850 | 100 |

CERTIFICATIONS:

- Certification ISO 9001:2000 + ISO 13485:2003
- Conformity to technical standards EN 455-1 (pinholes detection)
 + EN 455-2 (physical properties) + EN 455-3 (biological evaluation)
 + Pr EN 455-4 (shelf life determination)
- Mark according to European Directive 93/42/EEC





OVERALLS

Protect clothes from paint, dust and damage with Norton overalls. Overalls are washable and reusable and available in medium, large and extra large sizes.

PAINTING OVERALL

• The light polyester fabric makes the painting overall breathable, antistatic and washable and reusable

TATON

• Available in sizes medium, large and extra-large

| MODEL | SIZE | ART NO. | PK QTY |
|-------|-------------|-------------|--------|
| 8976 | Medium | 66254428976 | 10 |
| 8977 | Large | 66254428977 | 10 |
| 8978 | Extra-large | 66254428978 | 10 |



BODYSHOP OVERALL

- Made from polycotton, the bodyshop overall is breathable, washable and reusable
- Can be worn for all applications, protecting clothes from marks, tears, spills and splashes
- Available in sizes medium, large and extra-large

| MODEL | SIZE | ART NO. | BOX QTY |
|-------|-------------|-------------|------------|
| 8314 | Medium | 07660718314 | 5 |
| 8315 | Large | 0766718315 | 5 |
| 8316 | Extra-large | 07660718316 | 5 |





 (a) In these conditions 'the Company' means Saint-Gobain High Performance Solutions UK Ltd (trading as Saint-Gobain Abrasives) and 'the Customer' means the individual, firm, company or other party with whom the Company contracts. 'Supply' includes (but is not limited to) any supply under a contract of sale. 'International Supply Contract' means such a contract as is described in section 26(3) of the Unfair Contract Terms Act 1977.

(b) No order in pursuance of any quotation or otherwise shall be binding on the Company unless and until such order is accepted by the Company. Any contract made between the Company and the Customer (herein called 'the Contract') shall be subject to these conditions and save as aftermentioned no representative or agent of the Company has authority to agree any terms or make any representations inconsistent with them or to enter into any contract except on the basis of them; any such term representation or contract will bind the Company only if in writing and signed by a director.

(c) Unless otherwise agreed in writing by the Company these conditions shall override any terms and conditions stipulated or referred to by the Customer in his order or pre-contract negotiations.

(d) Any description contained in the Company's catalogues, samples, price lists or other advertising material is intended merely to present a general picture of the Company's products and services and shall not form a representation or be part of the Contract.

(e) In the event that the Company has not given a written

acknowledgement of the Customer's order these conditions, provided the Customer shall have had prior notice of them, shall nonetheless apply to the Contract.

(f) In the event that the Customer orders any goods by telephone, any subsequent written order received from the Customer will be deemed to be a confirmation of the order given on the telephone if and only if the written order is (i) marked with the Company's reference number given to the Customer on the telephone and (ii) marked 'Confirmation Only'. Any written order not so marked will be deemed to be a further order from the Customer and may be accepted accordingly.

(g) The Company reserves the right to correct any employee clerical or typographical errors made at any time.

2. (a) Where goods are made to the Customer's specification, instructions or design, the Customer undertakes full responsibility for the suitability and accuracy of the specification, instructions or design and undertakes to indemnify the Company against any infringement of any patent, design rights, registered design, trade mark, trade name, copyright or other intellectual property rights and any loss, damage or expense which it may incur by reason of such infringement in any country and the Customer undertakes further to indemnify the Company for any loss damage or expense in respect of any liability arising under or by reason of the provisions of the Consumer Protection Act 1987 in relation to the specification or design of such goods.

(b) The Customer warrants that it will pass on to all third parties to whom it may supply the goods all information as to the use and safe handling of the goods as may have been passed on to the Customer by the Company.

3. (a) Subject to any agreement to the contrary the Company's quotations are provisional and may be altered to take account of any changes taking place between the date of quotation and the Company's acceptance of the Customer's order in the price of raw materials, rates of wages and other costs of production or in the Customer's specification, instructions or design or in the event that the Customer orders part only of the quantity referred to in any quotation.

(b) The Company shall be entitled to increase its prices at any time to take account of any increase in the cost to the Company of purchasing any goods or materials or manufacturing working on or supplying any goods or services (including any such increase arising from any error or inadequacy in any specification, instructions or design provided by the Customer or any modification carried out by the Company at the Customer's request) and such increased prices ruling at the date of despatch by the Company shall be substituted for the previous Contract price. All prices quoted are exclusive of VAT and the Customer shall pay any and all taxes duties and other government charges payable in respect of the goods or services.

4. (a) Unless otherwise agreed in writing by the Company, the Company shall deliver the goods by the means most convenient to the Company to the address or addresses specified by the Customer or (in the event that the Customer fails to specify an address) to any address at which the Customer resides or carries on business and off-loading shall be at the Customer's risk.

(b) If the Contract is an International Supply Contract it shall be

deemed to incorporate the latest edition of Incoterms current at the date of the Contract save that in the event of any inconsistency between incoterms and any express term of the Contract the latter shall prevail. The Company shall be under no obligation to give the Customer the notice specified in section 32 (3) of the Sale of Goods Act 1979.

(c) Save in the Case of International Supply Contracts and subject to any agreement in writing by the Company, the risk in goods which the Company agrees to supply shall pass to the Customer on the relevant date as defined in sub paragraph 5 (a) hereof or the date (if earlier) on which, the goods being ready for delivery, delivery is postponed at the Customer's request.

(d) The Company shall not be liable for any loss of or damage sustained by any goods left with the Company howsoever caused and whether or not attributable to negligence on the part of the Company or negligence or wilful default on the part of any servant or agent of the Company.

(e) Should the Company be delayed in or prevented from making delivery of the goods or carrying out the services due to war, governmental or parliamentary restrictions, strike, lockouts, fire, floods, explosions, labour disturbances, trade disputes, damage to or destruction of the goods, breakdown of machinery, shortage of labour or of raw materials or Act of God or due to any other cause whatsoever beyond the reasonable control of the Company the Company shall be at liberty to cancel or suspend the order placed by the Customer without incurring any liability for any loss or damage arising there from.

(f) While the Company will endeavour to deliver the goods or complete the services by any date or within any period agreed upon, such dates and periods are estimates only given in good faith and the Company will not be liable for any failure to deliver or complete by such a date or within such a period. Moreover, the Company shall be entitled to defer delivery until any monies due from the Customer have been received.

5. (a) For the purposes of this paragraph the goods shall mean the whole or any instalment of the goods which the Company has agreed to supply or to which the Company has agreed to carry out work and the relevant date shall be the date on which (i) the Company despatches the goods or (ii) the Customer takes delivery of the goods at the Company's premises, whichever is the earlier, or (iii) (in the case of services) the services or any part thereof are carried out.

(b) Unless otherwise specified in writing by the Company payment for the goods or services or any part thereof shall be made by the customer net cash not later than the end of the month following the month in which the relevant date falls. Time for payment shall be of the essence of the Contract. Without prejudice to any other rights of the Company interest will be payable on all overdue accounts at Barclays Bank PLC base rate plus 4% and for the purpose of paragraphs 6 and 8 hereof the full purchase price of the goods or services shall include any interest payable hereunder.

 (c) Queries or inaccuracies regarding the invoice will only be entertained if the Customer has given the Company written notice of such queries or inaccuracies within 14 days of the invoice date.
 (d) The Customer shall make all payments due in full without any

(d) The Customer shall make all payments due in full without any deduction by way of set-off, counterclaim, discount or abatement, unless the Company expressly agrees otherwise.

6. (a) If the Customer shall fail to make any payment when it becomes due or shall enter into any composition or any arrangement with his creditors or if being an incorporated company shall have an administrative receiver or administrator appointed or shall pass a resolution for winding up or a Court shall make an order to that effect or if there shall be any breach by the Customer of any of the terms and conditions hereof the Company may defer or cancel any further deliveries and treat the Contract as determined but without prejudice to its right to the full purchase price for goods delivered and services provided and damages for any loss suffered in consequence of such determination.

(b) Cancellation by the Customer will only be accepted at the discretion of the Company and in any case on condition that any costs or expenses incurred by the Company up to the date of cancellation and all loss or damage resulting to the Company by reason of such cancellation will be paid by the Customer to the Company forthwith. Acceptance of such cancellation will only be binding on the Company if in writing.

(c) A charge will be made for any costs incurred by the Company due to suspension or deferment of any order by the Customer or in the event that the Customer defaults in collecting, or giving instructions for the delivery of, any goods.

7. (a) No claim for damage in transit, shortage of delivery or loss of goods will be entertained unless the Customer shall have given to the Company written notice of such damage, shortage or loss with reasonable particulars thereof within 14 days of receipt of the goods or (in the case of total loss) of receipt of the invoice or other notification of



despatch. The Company's liability, if any, shall be limited to replacing or (in its discretion) repairing such goods and it shall be a condition precedent to any such liability that the Customer shall if so requested have returned damaged goods to the Company within 14 days of such request. The Customer shall not be entitled to make any claim against the Company for consequential loss arising out of such damage shortage or loss as aforesaid.

(b) Save as otherwise provided in these conditions the Company's liability in respect of any defect in or failure of goods supplied or work done is limited to replacing or (in its discretion) repairing or paying for the repair or replacement of goods which within 12 months of delivery to the Customer are found to be defective by reason of faulty or incorrect design workmanship parts or materials and carrying out again any services which the Company has failed properly to perform in accordance with the Contract. In the event of any error in any weight, dimension, capacity, performance or other description or information which has formed a representation or is part of a contract the Company's liability in respect of any direct loss or damage sustained by the Customer as a result of such error shall not exceed the price of the goods or services in respect of which the description or information is incorrect. Conditions precedent to the Company's liability hereunder shall be that as soon as reasonably practicable the Customer (i) shall have given to the Company reasonable notice of the defect, failure or error

(iii) shall have either returned the goods to the Company or provided authority for the Company's servants or agents to inspect them, as the Company may request. The Company shall have no other or further liability in respect of any direct, indirect or consequential loss or damage sustained by the Customer arising from or in connection with any such defect failure or error as aforesaid.

(c) Where the Company agrees to repair or replace goods or carry out again the services in accordance with the foregoing provisions of this paragraph any time specified for delivery under the Contract shall be extended for such period as the Company may reasonably require.

(d) The Company shall have no liability in respect of any failure of goods caused, whether wholly or in part, by any modification to the goods (save for trimming or dressing the goods for use) carried out by or for the Customer (other than by the Company) without the Company's prior written approval. (e) Save for such terms as may be implied in the Contract by section 12 of the Sale of Goods Act 1979 or section 2 of the Supply of Goods and Services Act 1982 all conditions, warranties and other terms express or implied, statutory or otherwise, are expressly excluded, save insofar as contained herein or as otherwise expressly agreed by the Company in writing PROVIDED that if and insofar as any legislation or any order made thereunder shall make or have made it unlawful to exclude or purport to exclude from the Contract any such term, the foregoing provisions of this paragraph will not apply to any such term.

(f) Nothing in this agreement shall limit the Company's liability for death or personal injury caused as a result of the negligence of the Company.

8. The following provisions shall apply to all goods which under the Contract (other than an International Supply Contract) the Company agrees to supply to the Customer. No failure by the Company to enforce strict compliance by the Customer with such provisions shall constitute a waiver thereof and no termination of the contract shall prejudice limit or extinguish the Company's rights under this paragraph.

(i) Property in the goods shall not pass to the Customer until full payment has been received by the Company for the goods and any other goods supplied by the Company or any of its associated companies.

(iii) The Customer undertakes that until payment has been made in accordance with 8i] abovenot to remove, deface, or cover up any identification marks that the goods are the property of the Company • to store the goods separately from those belonging to the Customer and others

• to allow the Company, its agents and employees, unrestricted access to the Customer's premises or any other location where the goods are stored, for the purpose of removal of the goods.

(iii) The Customer is hereby granted a license by the Company to incorporate the goods in any other products.

(iv) The Customer is hereby licensed to sell on the goods and any products incorporating any of them. The Customer shall, immediately upon receipt of the proceeds of sale, and whether or not payment has become due under paragraph 5 hereof, remit to the Company the full purchase price of the goods sold on less any part thereof which has already been paid and until such amount has been so remitted shall hold such amount as trustee and agent for the Company.

(v) The Customer shall maintain all appropriate insurance in respect

of the goods from the date or dates on which the risk therein passes to him. In the event of any loss or damage occurring while the goods remain the property of the Company the Customer shall immediately on receipt of the insurance monies, remit to the Company the full purchase price of the goods lost or damaged less any part thereof which has already been paid and until such amount has been so remitted shall hold such amount as trustee and agent for the Company. (vi) The licences granted under sub-paragraphs (ii) and (iii) above shall be terminable forthwith at any time upon notice by the Company to the Customer.

- 9. In the case of International Supply Contract property in the goods shall pass to the Customer upon delivery.
- 10. Save as hereinbefore provided and subject to the provisions of section 2(i) of the Unfair Contract Terms Act 1977 the Company shall not be liable to the Customer for any damage or for any direct or consequential loss incurred by the Customer in consequence of any negligence on the part of the Company or negligence or wilful default on the part of its servants or agents or in connection with the supply of any goods or the design or manufacture thereof or in the carrying out of any work or the provision of any information.
- 11. Nothing in these Conditions shall exclude or restrict any liability that the Company may have by virtue of the Consumer Protection Act 1987.
- 12. (a) The Customer shall be responsible for complying with any legislation or regulations governing the importation of the goods supplied by the Company under the Contract into the country of destination and for the payment of any duties on them.
 (b) The Customer shall be liable for and shall indemnify and hold the Company harmless from any and all liability, loss, claims, damages and costs, which the Company may sustain or incur, arising out of or in any way connected with the Customer's failure to comply with paragraphs 12(a) and/or 15 hereof.
- 13. Without affecting any other right or remedy available to it, the Company may terminate any Contract with the Customer with immediate effect by giving written notice to the Customer if the Customer commits a material breach of any term of these Conditions and/or the Contract which breach is irremediable or (if such breach is remediable) fails to remedy that breach within a period of seven (7) days after being notified in writing to do so.
- 14. The Customer shall ensure that in any dealings with the Company, neither it or its employees or agents shall commit any offence under the Bribery Act 2010 ("the Act") including not engaging in any activity, practice or conduct which would constitute an offence under sections 1, 2 or 6 of the Act. The Customer shall inform the Company immediately it becomes aware of any actions between the parties that could constitute an offence under the Act.
- 15. It is the Company's and the Company's group's policy to comply with all applicable sanctions and legal requirements for the import and export of goods, technology and services. The Company is committed to ensuring compliance with all regulatory and licensing requirements relating to international trade. The Company does not permit the supply of any of its goods to any individuals, companies or organisations that are subject to any trade, economic or financial sanctions, embargoes or similar restrictive measures administered, enacted or enforced by the UK, EU, UN or USA ("Sanctioned Entities"). By entering into this Contract the Customer agrees not to re-sell or otherwise transfer the goods supplied by the Company, either directly or indirectly, to any Sanctioned Entities.

16. (a) For the purposes of this paragraph 16, (a) "Applicable Data Protection Laws" means (i) to the extent the UK GDPR applies, the law of the United Kingdom or of a part of the United Kingdom which relates to the protection of personal data; (ii) to the extent the EU GDPR applies, the law of the law of the European Union or any member state of the European Union to which the Supplier is subject, which relates to the protection of personal data, in each case, as updated, amended or replaced from time to time; (b) "EU GDPR" means the General Data Protection Regulation [(EU) 2016/679), as it has effect in EU law; (c) "UK GDPR" has the meaning given to it in section 3(10) (as supplemented by section 205(4)) of the Data Protection Act 2018; and (d) the terms "Data Subject", "Personal Data", "processing", "processor" and "controller" shall have the meanings set out in the UK GDPR.

(b) Each party shall comply with the provisions and obligations imposed on it by the Applicable Data Protection Laws when processing Personal Data in connection with these Conditions. Such processing shall continue for so long as these Conditions are in force and shall be in respect of the following:

(i) Categories of data: Contacts within each of the parties and the ultimate customer details;

(ii) Types of personal data: names, addresses, email addresses, telephone numbers and other contact details;

(iii) Purpose and nature of processing: (i) manage the Contracts between the parties including ordering, fulfilment and billing; and (ii) fulfilment of such Contracts by delivering goods (where relevant). (c) To the extent that a party processes any Personal Data on behalf of the other party, the processing party shall: (i) comply with the provisions and obligations imposed on a processor by the Applicable Data Protection Laws, and any stipulations set out in the Applicable Data Protection Laws as to what shall be included in the contract between the parties shall form a part of, and are incorporated into, these Conditions as if they were set out in full, and any reference to 'documented instructions" (or similar) shall include the provisions of these Conditions; and (ii) not disclose any Personal Data to any Data Subject or to a third party other than at the written request of the other party or as expressly provided for in these Conditions. (d) You agree that we may engage third party providers including any advisers, contractors, or auditors to Process Personal Data ("Sub-Processors"). We shall ensure that our contract with each Sub-Processor shall impose obligations in relation to the Processing of Personal Data on the Sub-Processor that are materially equivalent to the obligations to which we are subject to under these Conditions in relation to the Processing of Personal Data. (e) If either party receives any complaint, notice or communication which relates to the processing of Personal Data by the other party or to either party's compliance with the Applicable Data Protection Laws, or if any Personal Data processed in connection with these Conditions is subject to a personal data breach (as defined in the UK GDPR), it shall immediately notify the other party and provide the other party with reasonable co-operation and assistance in relation to any such complaint, notice, communication or personal data breach.

17. The proper law of all contracts with the Company shall be English Law which shall govern in all respects the construction and effect of such contracts and of these Conditions. The Customer agrees that in the event of any dispute arising out of the Contract or the performance thereof he will submit to the exclusive jurisdiction of the English Courts.

Returns Policy

- You must contact our customer service team within 14 days of receiving your order. We do not accept sale and return without prior agreement in writing, where a 25% or £25 handling fee (whichever is higher) will be issued for returns that are agreed upon.
- It is the customer's responsibility to arrange and cover the costs for shipment, which will need to be returned to our returns depot – this could be located in the UK or EU. Any delivery charges incurred will not be refunded.
- Please ensure the returns document with the returns number, accompanies the product when returned. Once you have packaged your items ready for shipping, clearly write the returns number on the outside of the packaging. Failure to do so could cause delays to any refunds or resolving your query.
- Any returned items need to be returned unused, with no signs of tampering and in the original packaging, which must not be damaged.
- If the returned products are damaged, show signs of tampering or being used, or are damaged in transit in a way that you could have foreseen (such as not being sent back in the original packaging), we withhold the right to refuse any returns (or partial returns). Please refer to Conditions of Sale-General Conditions for the Supply of Goods and Associated Services (Feb 2021) Section 7a, for further information.
- Full refunds will only be issued once we have received the products and they have been checked to ensure they have not been damaged or tampered with in any way. This means they should be in their original packaging, unused without any signs of damage and with a copy of the invoice included. We will confirm that we have received the item and that the product has met our required return conditions – please allow 28 days for your account to be credited.is

PLEASE NOTE:

To obtain or check any prices in this catalogue, please contact the UK Customer Service team on +44 (0)1785 279553, email sga-uk@saint-gobain.com or speak to your local sales representative for further support.

Saint-Gobain High Performance Solutions UK Ltd (trading as Saint-Gobain Abrasives). Unicorn House, Unit 1, Amison Close, Redhill Business Park, Stafford. England. ST16 1WB. Tel: +44(0) 1785 279533 Fax: +44 (0) 1785 213487

Registered Office: Saint-Gobain House. East Leake, Loughborough, Leicestershire LE12 6JU. Registration Number: 245722

SAINT-GOBAIN ABRASIVES NV/SA

INDUSTRIELAAN 129 1070 ANDERLECHT BRUSSELS BELGIUM TEL: +32 2 267 21 00 FAX: +32 2 267 84 24

SAINT-GOBAIN

CONSTRUCTION PRODUCTS CZ A.S DIVIZE ABRASIVES

SMRČKOVA 2485/4 180 00 PRAHA 8 CZECH REPUBLIC TEL: +420 255 719 326 FAX: +420 255 719 321

SAINT-GOBAIN ABRASIVES A/S

DYBENDALSVÆNGET 2 DK-2630 TAASTRUP DENMARK TEL: +45 4675 5244

PO BOX 643706

FORTUNE TOWER OFFICE 2106 JLT BLOCK C (NEXT TO METRO STATION) JUMEIRA LAKE TOWER, DUBAI UNITED ARAB EMIRATES TEL: +971 4 431 5154 FAX: +971 4 431 5434

SAINT-GOBAIN ABRASIVES

TEOLLISUUSTIE 1 33470 YLÖJÄRVI FINLAND TEL: +358 20 7424630

SAINT-GOBAIN ABRASIFS

251 RUE DE L'AMBASSADEUR 78700 CONFLANS FRANCE TEL: +33 (0)1 34 90 40 00 FAX: +33 (0)1 34 90 43 97

SAINT-GOBAIN ABRASIVES GMBH

BIRKENSTRASSE 45-49 D-50389 WESSELING GERMANY TEL: +49 (0) 2236 703-1 +49 (0) 2236 8996-0 +49 (0) 2236 8911-0 FAX: +49 (0) 2236 8911-0 FAX: +49 (0) 2236 8996-10 +49 (0) 2236 8991-30 FÜR DEN FACHHANDEL ÖSTERREICH TEL: +43 (00) 662 430 076

SAINT-GOBAIN HUNGARY KFT.

DIVISION ABRASIVES 2085 PILISVÖRÖSVÁR BÉCSI ÚT 07/5 BRANCH OFFICE: 2040 BUDAÖRS PUSKÁS TIVADAR ÚT 1. HUNGARY TEL: +36 30 217 3256

SAINT-GOBAIN ABRASIVI S.P.A

VIA PER CESANO BOSCONE 4 I-20094 CORSICO MILANO ITALY TEL: +39 02 44 851 FAX: +39 02 44 78 266

SAINT-GOBAIN ABRASIVES S.A.

190 RUE J.F. KENNEDY L-4930 BASCHARAGE GRAND DUCHE DE LUXEMBOURG TEL: +352 50 401 1 FAX: +352 50 16 33 NO. VERT (FRANCE) 0800 906 903

SAINT-GOBAIN ABRASIFS, S.A.

2 ALLÉE DES FIGUIERS AIN SEBAÂ - CASABLANCA MOROCCO TEL: +212 5 22 66 57 31 FAX: +212 5 22 35 09 65

SAINT-GOBAIN ABRASIVES BV

GROENLOSEWEG 28 7151 HW EIBERGEN P.O. BOX 10 7150 AA EIBERGEN THE NETHERLANDS TEL: +31 545 466466 FAX: +31 545 474605

SAINT-GOBAIN ABRASIVES AS

KARIHAUGVEIEN 89 1086 OSLO NORWAY TEL: +47 63 87 06 00 FAX: +47 63 87 06 01

SAINT-GOBAIN HPM POLSKA SP. Z 0.0.

UL. NORTON 1 62-600 KOŁO POLAND TEL: +48 63 26 17 100 FAX: +48 63 27 20 401

SAINT-GOBAIN ABRASIVOS, L. DA

ZONA INDUSTRIAL DA MAIA I-SECTOR VIII, NO. 122 APARTADO 6050 4476 - 908 MAIA PORTUGAL TEL: +351 229 437 940 FAX: +351 229 437 949

SAINT-GOBAIN GLASS,

BUSINESS UNIT ABRASIVI PUNCT DE LUCRU: LOC.VETIS, JUD. SATU MARE 447355, STR. CAREIULUI 11, PARC INDUSTRIAL RENOVATIO ROMANIA TEL: +40 261 839 709

FAX: +40 261 839 710

SAINT-GOBAIN AFRICA

300 JANADEL AVE HALFWAY GARDENS MIDRAND, 1686 SOUTH AFRICA TEL: +27 (0) 12 657 2800 FAX: +27 (0) 11 388 1605

SAINT-GOBAIN ABRASIVOS, S.A.

CTRA. DE GUIPÚZCOA, KM. 7,5 E-31195 BERRIOPLANO (NAVARRA) SPAIN TEL: +34 948 306 000 FAX: +34 948 306 042

SAINT-GOBAIN ABRASIVES AB

GÅRDSFOGDEVÄGEN 18A SE-168 66 BROMMA SWEDEN TEL: +46 8 580 881 00 FAX: +46 8 580 881 30

SAINT-GOBAIN INOVATIF MALZEMELER VE

AŞINDIRICI SAN. TIC. A.Ş. GOLD PLAZA, ALTAY ÇEŞME MAHALLESI, ÖZ SOKAK, NO:19/16 34843 MALTEPE-ISTANBUL, TURKEY TEL: 0090-216-217 12 50 FAX: 0090-216-442 40 74

SAINT-GOBAIN ABRASIVES

UNICORN HOUSE UNIT 1, AMISON CLOSE REDHILL BUSINESS PARK STAFFORD ST16 1WB UNITED KINGDOM TEL: +44 1785 279553



Saint-Gobain Abrasives Unicorn House Unit 1, Amison Close Redhill Business Park Stafford STI6 1WB United Kingdom Tel: +44 1785 279553



www.nortonabrasives.com www.youtube.com/NortonAbrasivesEMEA

Norton is a registered trademark of Saint-Gobain Abrasives. Form # 4540







| | ſ | 2 |
|---|----------|---|
| 2 | _ | = |
| - | ł | J |
| 2 | | ٦ |
| J | | > |
| C | |) |
| Γ | T | ٦ |
| C | ſ | 7 |
| ¢ | | 2 |
| | <i>,</i> | |
| C | _ | _ |
| | | |
| C | | 2 |
| ÷ | - | - |
| ĩ | 1 | 5 |
| ` | ' | ' |
| 1 | | |
| ć | | |
| 2 | | ł |
| | - | 5 |
| Ē | | 5 |
| ź | 2 | |
| Q | | 2 |
| 2 | | 1 |
| 2 | | 2 |
| ľ | ī | ì |
| ٦ | | - |
| f | - | |
| | - | ł |
| Ē | | i |
| | ÷ | 1 |
| | 2 | 1 |
| ł | \$ | 5 |
|) | | |
| 2 | T | 3 |
| 5 | 2 | ł |
| í | | ì |
| 1 | - | ł |
| | | 1 |

